Spatial Gesture Control: Controlling a Laptop with Head Orientation and Smartwatch Pinch Gestures

Vaibhav Bisht[1*]

[1*][Department], [Institution], [City], [Country].

Corresponding author(s). E-mail(s): vaibhavbisht78@gmail.com;

Abstract

We present and evaluate a system that lets a person control a laptop without touching it. The user looks at a calibrated screen location, pinches to grab a virtual volume knob, turns the wrist to change the volume and pinches again to release. Head orientation comes from consumer Sony headphones. Wrist motion and raw photoplethysmography (PPG) come from a Samsung Galaxy Watch over Bluetooth Low Energy, and all inference runs on the laptop behind a fail-closed safety chain. Because the watch cannot see the fingers, we recorded wrist signals with camera hand landmarks as timing ground truth. We evaluated detectors as continuous event detectors, counting caught pinches against false activations per hour of no-gesture time. Wrist PPG alone generalised poorly to a new day (AUC 0.60–0.64), and ten robustness methods did not change this. Fusing the inertial sensors raised worst-split AUC from 0.789 to 0.837, and firing at the score's peak added 4–12 recall points. A three-network 1-D convolutional model on nine raw channels caught about two thirds of pinches on unseen sessions, against 10–28% for tree ensembles, and fired about 0.4 s sooner. Median-based normalisation removed a motion-induced blind spot. We report the system design, data pipeline and results, and analyse the evaluation and labelling practices that determined whether offline results predicted live behaviour.

Keywords: Gesture recognition, Smartwatch, Photoplethysmography, Inertial sensing, Head tracking, Wearable computing, Event detection

1 Introduction

Laptops are still controlled through a keyboard, a pointer or a touch surface, although many people now wear sensors on the head and the wrist for most of the day. Noise-cancelling headphones contain motion sensors that report where the head points, and a smartwatch measures wrist motion and the optical blood-volume signal known as photoplethysmography (PPG). This article asks whether these everyday wearables can replace the keyboard for a simple spatial control: a virtual volume knob that the user looks at, grabs with a finger pinch, turns with the wrist and releases with a second pinch.

The interaction is easy to describe and hard to build. A watch cannot see the fingers, so a pinch must be inferred indirectly from changes in PPG and from small motions of the wrist. Everyday activity such as typing, reaching or scratching produces similar signals, and both signals change between days and strap fits. Three devices with independent clocks take part, and the output changes a real operating-system setting, so a wrong decision must never escalate.

We designed, built and evaluated such a system between 27 July and 7 November 2026, and we report both the engineering and the research that led to a working detector. We address three research questions:

- **RQ1.** Can raw wrist PPG from a stock smartwatch detect the start of a pinch in continuous use, across days?
- **RQ2.** How much do the watch's inertial sensors, the trigger rule and the model family change detection performance?
- **RQ3.** Which evaluation and labelling practices are needed so that offline results predict live behaviour?

Our contributions are:

- A cross-platform desktop coordinator that fuses Sony headset orientation with Samsung Galaxy Watch motion and raw PPG and drives system volume through a recipe engine with a fail-closed safety chain (Section 3).
- A data pipeline that records watch signals with camera hand landmarks as timing ground truth, aligns three clocks and trains one binary detector per gesture label (Sections 4 and 5).
- An empirical study showing that wrist PPG alone generalises poorly to new days, that inertial fusion and a peak trigger improve detection substantially, and that a compact 1-D convolutional network (CNN) on nine raw channels outperforms engineered-feature tree ensembles on unseen sessions (Section 7).
- An event-based evaluation standard applied identically in training and at runtime, and an account of the evaluation pitfalls that inflated earlier results (Sections 6 and 8).

2 Related Work

2.1 Wrist PPG for Gesture Recognition

FinDroidHR classified a vocabulary that included pinch from the optical heart-rate sensor of a commercial smartwatch [1], and fSense used smartwatch PPG to estimate the force of a gesture [2]. Custom hardware recognised finger-level gestures from two green sensors [3], simple hand gestures [4] and gestures from four spatial sensing sites analysed with principal component analysis [5]. These geometries are not interchangeable with the three wavelength streams of a stock watch.

Robustness is the most relevant strand for continuous use. Fang et al. showed that sensor shift degrades PPG gesture recognition and proposed transfer learning [6]; Li et al. classified gesture and force level together [7]. Several headline results depend on other modalities: Eddy et al. segment PPG gestures using accelerometer boundaries [8], the sign-language result of Zhao et al. fuses motion sensors [9], and OpenWatch reports PPG as an addition to inertial data, with an F1 of 90% on unseen people and a 12.5-point gain from PPG [10]. Multimodal wristbands [11, 12], large datasets [13], force estimation [14] and reviews of wearable gesture sensing [15] and wearable PPG [16] complete the picture.

Most published scores are accuracies on prompted, pre-segmented clips, often within one user. None of the works above establishes a continuously running pinch detector from stock-watch PPG with a measured false-activation rate during everyday activity, which is the setting studied here.

2.2 Motion-Based Pinch and Tap Detection

Tsunoda et al. recognised four microgestures on unseen people with 94.7% accuracy from a 4,000 Hz accelerometer on a modified kernel, with accuracy falling sharply below 200 Hz [17]. ViWatch reached about 97% over a week at 100 Hz, but 45% on an unseen person without per-user adaptation [18]. Kim et al. detected 95% of deliberate pinches with a fixed threshold on the high-pass filtered 100 Hz signal [19]. On the watch used here, the raw streams available to applications are 50–100 Hz motion and 25 Hz PPG, so the high-rate route is closed and the ViWatch setting is the closest comparison.

2.3 Robustness Methods for Time Series

For cross-session robustness we screened group distributionally robust optimisation [20], domain-adversarial training [21], correlation alignment [22], random-convolution transforms [23], invariant risk minimisation [24] and feature-statistics mixing [25]. Tree ensembles used extremely randomised trees [26, 27]; derivative experiments used Savitzky–Golay filtering [28].




Fig. 1 System architecture. Head pose, wrist pose and pinch detections meet in one recipe engine, which alone may show the knob and drive the volume. The camera and trainer sit beside the live path and never act at runtime.

3 System Design

3.1 Architecture

Fig. 1 shows the architecture. The headset and watch only sense; every decision runs on the laptop. The desktop application uses Tauri 2 [29], a Rust backend and a React frontend. Head orientation comes from the open-source `sony-head-tracker` [30], embedded in-process on macOS and Windows and run as a loopback UDP bridge on Linux. The Wear OS application reads raw PPG through Samsung's Health Sensor SDK [31] and streams it with motion data over Bluetooth Low Energy (BLE) by default, using `btleplug` [32] on the desktop, or over a Wi-Fi WebSocket. A webcam running MediaPipe hand landmarks [33] is used only for labelling. Training runs offline in Python with PyTorch [34]; inference runs in-process in Rust, with no Python at runtime.

The target interaction has five steps. (1) The user looks at a calibrated location (top right by default) for a dwell time of 400 ms, and a transparent, non-focusable knob appears. (2) A *pinch in* grabs the knob and records the wrist pose and current volume. (3) Wrist roll changes the volume relative to that pose. (4) A *pinch out* releases the knob, keeping the volume, while the knob stays ready for another grab. (5) Looking away hides the knob; Escape cancels everything.

Table 1 Devices and data rates

Device	Data used	Rate
Sony headset	Orientation quaternion	≈25 Hz
Galaxy Watch4+	Rot. vector, lin. accel., gyro	50 Hz
	Raw PPG green, red, IR	25 Hz
	Crown button, wear state	On change
Webcam	21 hand landmarks (labels only)	23–30 fps

Table 2 Volume filters and limits

Stage	Rule
Velocity outlier	Freeze target above max. angular velocity
Jitter rejection	Accept target changes ≥ 0.5 points
Easing	Exponential, 150 ms time constant
Slew limit	≤ 30 points/s, independent of input rate
Write pacing	≥ 100 ms apart, writer thread
Interaction epoch	Drop writes from a released grab
Clamp	0–100

3.2 Head Targeting

During calibration the user faces the screen centre and then each named location, and the system stores a unit quaternion per target. At runtime the nearest target is found by angular distance,

$$\theta = 2 \arccos\big(|q_{\text{cur}} \cdot q_{\text{tgt}}|\big), \tag{1}$$

where the absolute value identifies q and $-q$. A target activates when θ stays below an adjustable threshold for the dwell time. A change in the headset's reset counter means its reference frame moved and invalidates the calibration.

3.3 Wrist-to-Volume Mapping

At grab time the watch orientation Q_s is stored, and each new sample yields

$$Q_{\text{rel}} = Q_s^{-1} Q_{\text{cur}}, \tag{2}$$

from which the twist about the forearm axis is extracted. The volume target is absolute from the grab pose, so errors do not accumulate. The final mapping uses a 1° dead zone and about one volume point per 3°, with a sensitivity setting and a direction switch. Table 2 lists the filters. Native volume calls on macOS take 130–190 ms, so a dedicated writer thread applies the newest target, keeping the sensor event loop free.

Table 3 Measured properties of the watch data path

Quantity	Value
Motion sensor rate	49.8 Hz per sensor
PPG rate	25.0 Hz in every session
PPG timestamp jitter	6–10% of gaps over 60 ms
BLE MTU (Mac)	517 (512 B per notification)
Notifications/s	≈61 before, ≈30 after
Watch CPU at 61/s	App 21%, BLE service 41%
Desktop CPU	App 10%, web view 13%
Live inference	≈0.2 ms/window (debug build)

3.4 Watch Sensing Pipeline

Both transports carry the same JSON envelopes (type, version, device id, sequence, timestamp and payload) and share one decoder. Over BLE the watch is a GATT peripheral and the desktop the central; the desktop assigns the device identity and requires both operating-system bonding and an explicit on-watch trust approval. Motion travels in 100 ms batches and PPG at each sensor flush (10 Hz by default), about 30 notifications per second.

Building this path exposed several faults (Table 3). Fragments sized as MTU$-3 =$ 514 bytes exceeded the 512-byte attribute limit, so Android silently refused every PPG batch over BLE. An unbounded queue grew to seconds of delay when arm movement weakened the radio path, and was then discarded whole; it was replaced by a half-second queue that drops the oldest whole messages. Sending each motion reading separately produced about 61 notifications per second and saturated the link. After batching motion and PPG as separate streams, a 15-minute log showed 20 dropped messages (about 2 s of data), almost all just after reconnects. Timestamps stay on the watch's monotonic clock, while freshness and safety decisions use the desktop's own clock.

3.5 Recipe Engine and Safety

A recipe chains a head stage, a gesture stage and a wrist stage into an action on a virtual device, with conflict detection between recipes that would drive the same output. A pinch-in detection is a one-shot event, and detector silence is not a release. A *paired* stage therefore latches the grab on a fresh pinch-in while the head target is held, ignores repeated starts while grabbed, releases on pinch-out (release wins if both arrive together) and cancels on head exit, Escape, data loss, model change or leaving live mode.

The effects are bounded by a fail-closed chain. An ordering watermark, a quality gate, a window-length check, a fusion freshness check (orientation older than 500 ms is rejected) and a gesture policy each force a release when they reject data. A watchdog releases any grab whose model data has been silent for 750 ms. Inference runs *Off*, *Monitor* (scores but never acts) or *Live* (acts only through explicit intent bindings),

Table 4 Collections used in this study (one participant, left wrist)

Collection	Content	Used for
September–October 2026	17 usable recordings; cue-based labels	Early PPG studies, training for the held-out test
14 October 2026	15 recordings: 9 pinch, 4 fist, 2 everyday activity; strap refitted	One-shot held-out test; mixed-era study
Frozen benchmark	37 recordings, 1,390 events	IMU fusion and trigger studies
October–November 2026	Camera-timed pinch sessions, everyday noise	CNN versus trees, final models
Leave-one-day-out set	372 camera-marked pinches	Table 7

and a saved Live setting is capped to Monitor at start-up. Model bundles are data-only, and their SHA-256 hash and input contract are re-verified on every load.

4 Data Collection and Ground Truth

4.1 Recordings

All recordings were made by a single participant (the author), with the watch on the left wrist. Recordings are immutable bundles of PPG, motion and labels. Pinch is labelled as `pinch_in` (contact), `pinch_hold` and `pinch_out` (release). Fist, thumbs-up and three kinds of everyday noise (typing, mouse use and ordinary activity) serve as negatives. Table 4 summarises the collections used in this article.

4.2 Camera Ground Truth and Clock Alignment

Early labels came from on-screen cues, and each recording had its own lag of up to 1.3 s between cue and execution. We therefore recorded camera ground truth. MediaPipe [33] finds 21 hand landmarks per frame in the application's web view, without network access. Only landmarks are stored, never images. The watch and the browser keep different clocks. Watch timestamps are paired with browser arrival times every 200 ms, and since delivery delay is never negative, the smallest arrival-minus-watch difference estimates the offset.

Pinch contact is marked from the distance between thumb and index tips. A fixed threshold of 0.35 hand sizes missed many real pinches, because apparent distance depends on hand orientation. Those missed pinches were then trained as non-pinches and counted as false activations. Judging each session against its own hand reduced false activations on pinch sessions from 110 to 20 per hour. A later audit found 8 of 163 camera-labelled pinch-in intervals immediately followed by pinch-out with no hold, and queued them for review.

Table 5 The two detector families

	Trees	CNN
Input	2,733 features	9×50 raw values
Model	300 ExtraTrees	3 dilated 1-D CNNs
Training moments	≈1,000–1,300	Tens of thousands
Decision delay	≈0.88 s	≈0.5 s
History needed	5.6 s	11 s

5 Detection Methods

Each label has its own binary detector. Both families below answer the same question at every PPG sample: did the gesture just start? Table 5 compares them.

5.1 Engineered Features and Extremely Randomised Trees

Each PPG sample is z-scored against the preceding 1, 2 and 4 s. Slope, curvature and jerk are computed causally, and 21 statistics are taken over the last 0.3, 0.6 and 1.3 s (1,701 features). The same statistics are computed for each motion axis, its magnitude and its change, plus movement relative to the preceding 3 s (1,032 features). An ensemble of 300 extremely randomised trees [26], with at least 3 samples per leaf and 70% of inputs per split, is trained on the moment 0.88 s after each start as positive, and on matched moments after other gestures, inside holds and in quiet time as negatives.

5.2 Compact 1-D Convolutional Network

Nine channels (accelerometer, gyroscope, PPG green, red and infrared) are resampled to a 50 Hz grid. Each channel x is normalised against its last 11 s using the median and the median absolute deviation (MAD), then squashed:

$$\tilde{x}_t = \sigma\left(\frac{x_t - \mathrm{med}_{11\,\mathrm{s}}(x)}{\mathrm{MAD}_{11\,\mathrm{s}}(x)}\right). \tag{3}$$

The last second (450 values) is the input. Three dilated convolutions (32, 32 and 64 channels, kernel 5, dilation 1, 2 and 4) with batch normalisation feed per-channel max and mean pooling, a 32-unit dense layer with dropout and a single output. Three networks trained with different seeds are averaged. Samples 0.4–0.6 s after a start are positives; samples with no start between 1.2 s before and 0.2 s after are negatives, with at most 40,000 negatives per network and positives weighted up to 20 times. Training uses Adam (learning rate 0.001, weight decay 0.0001), 12 epochs and batches of 256.

5.3 Detection Rule and Threshold Selection

A detection fires at the peak of the score once it exceeds the threshold, ends when the score falls 0.15 below it, and the next detection waits 1.5 s. The threshold is selected on training recordings only. Five models, each trained without one fifth of them, score

the held-out parts in replay, and the threshold that catches the most starts within 30 false activations per hour is kept. The exported model is checked against the trained one before release. Shared fixtures keep the Python and Rust implementations of input building and detection identical.

6 Evaluation Protocol

Detectors are evaluated as continuous event detectors on complete recordings, and training and test recordings are always disjoint. Each emitted event is exactly one of: a *catch* (inside the match window after a labelled start), a *repeat* (another event during a caught gesture), *late*, or a *false activation*. The headline metrics are

$$\mathrm{TAR} = \frac{\#\,\text{caught starts}}{\#\,\text{labelled starts}}, \tag{4}$$

$$\mathrm{FAR} = \frac{\#\,\text{false activations}}{\text{hours with no gesture under way}}. \tag{5}$$

The FAR denominator is deliberately not the total recording time. Pinch sessions are dense, and a rate per hour of recording had hidden a model that fired about 175 times per hour of no-gesture time.

We used five study designs: recording-disjoint cross-validation judged first by worst-split (minimum) AUC; a one-shot held-out day with protocol and techniques frozen before the run; leave-one-day-out testing on camera-timed sessions with everyday noise; replays with real motion bursts spliced in before held-out pinches; and ablations of preprocessing, triggers and labels. Each study records whether its data had been seen before. Explored cross-validation is reported as progress evidence, not as an untouched test. Under a constant-rate Poisson assumption, zero false activations observed in T hours bounds the rate at

$$\lambda_{95\%} \approx \frac{-\ln 0.05}{T} \approx \frac{3}{T} \text{ per hour}, \tag{6}$$

so 30 clean minutes still allow about six false activations per hour.

7 Results

7.1 RQ1: PPG Alone

A PPG "step" at pinch onset appeared in every early pinch session on all three channels, in units of each session's recent past. Its rest controls, however, had been chosen only by distance from gesture edges, and a recheck found 84% of them (1,645 of 1,958) inside gestures, mostly in the middle of long holds. Against mid-hold moments the step separated well (median AUC 0.94). Against fist and thumbs-up starts it reached only about 0.65, needed about 700 ms after the start, and did not transfer between days (0.81 and 0.37 on two other days). As a continuous detector it found under 10% of pinches at about one false activation per minute.

Table 6 Mixed-era robustness screen (AUC over 20 splits)

Method	Min	Mean	Max
Reference A: RGB waveform, HGB	0.676	0.749	0.842
Reference B: z-score, dense MLP	0.661	0.756	0.853
Group DRO [20]	0.618	0.742	0.832
Causal morphology + HGB	0.675	0.785	0.914
MiniRocket-like [23]	0.653	0.745	0.851
Constrained derivative DTW	0.682	0.739	0.816
Feature-space augmentation	0.643	0.743	0.863
CORAL adaptation [22]	0.462	0.533	0.606

On a one-shot held-out day (14 October 2026: 208 pinch starts, 80 everyday-activity moments, 68 fist starts), every October PPG technique scored 0.60–0.64 AUC against non-pinch moments, with intervals reaching about 0.45. Fist starts were not separable from pinch starts (0.37–0.57), and no technique was usable continuously.

A mixed-era study then pooled 32 recordings (the 17 originals and the 15 refitted-strap recordings) in 20 recording-disjoint 60/40 splits. Raw-waveform neural networks were weak (mean AUC 0.47–0.58), and causal normalisation proved essential. Table 6 shows that none of the robustness methods produced a clear gain in worst-split AUC over the base references. The reference PPG-only tree pipeline, over 37 recordings and 20 folds, reached minimum, mean and pooled event AUC of 0.7885, 0.8426 and 0.8105, with 41.15% recall at 15.09 false activations per minute and about 830 ms latency. On recordings without any pinch it fired 19–25 times per minute. *Answer to RQ1: on this watch, PPG carries a real but weak, slow and non-specific onset cue, and PPG alone does not support a continuous detector.*

7.2 RQ2: Inertial Fusion, Trigger Rule and Model Family

On the frozen benchmark (37 recordings, 1,390 events, 20 splits), inertial features alone already outperformed PPG. Fused with PPG they raised worst-split AUC from 0.789 to 0.837, better on 19 of 20 splits. Separation of pinch from other gesture starts rose from 0.70 to 0.79–0.81. At a threshold of 0.5, false activations on recordings without a pinch fell from 19.0 to 12.0 per minute.

The original trigger fired at the first threshold crossing. At low thresholds this was often before the scoring window, and its 1.5 s lockout then blocked the correct firing. Firing at the peak of the score added 4–12 recall points at the same false-activation budget, at a cost of 35–90 ms of latency. Shifting labels earlier by 200–350 ms converted only about three false activations per minute into catches, so most remaining false activations were genuine responses to other movement.

Table 7 reports leave-one-day-out results for the CNN on 372 camera-marked pinches. On new sessions the CNN caught about two thirds of pinches, against 10–28% for the tree ensembles, and fired about 0.4 s sooner. A still-hand rule applied during training removed every moving moment, so the model never learned that movement is not a pinch. The best configuration trains without that rule and with everyday noise.

Table 7 CNN variants, leave one day out, 372 camera-marked pinches

Training	Caught	FAR noise (/h)	FAR pinch (/h)
October only, no noise (earlier)*	204 (55%)	143	23
With still-hand rule	146 (39%)	23	20
Without the rule, with noise	**161 (43%)**	**7**	49†
Rule only at runtime	130 (35%)	3	16

FAR noise: false activations per hour on unseen everyday-noise sessions; FAR pinch: on pinch sessions.
*Trained on most October pinches, so not unseen. †Dominated by one day; other days 0–28/h.

Table 8 Detection after a spliced motion burst (ends 1 s before the pinch)

	Pinch in		Pinch out	
Burst	Roll.	Med.	Roll.	Med.
None	92%	92%	98%	98%
3–6 rad/s, 2 s	0%	93%	5%	98%
2.5–6 rad/s, 4 s	0%	87%	4%	89%
2–6 rad/s, 6 s	0%	58%	6%	28%
2–6 rad/s, 8 s	0%	16%	0%	4%

The final pinch-in and pinch-out models caught 15 of 20 and 18 of 21 pinches on held-out sessions. The participant reports that both work in the paired volume interaction. *Answer to RQ2: inertial fusion and the peak trigger each improve detection substantially, and the compact CNN on raw channels clearly outperforms engineered-feature trees on unseen sessions.*

7.3 A Normalisation Blind Spot

The first CNN normalised each channel by a rolling 10 s mean and standard deviation. A burst of wrist motion raised the gyroscope deviation from about 0.03 to about 1 rad/s, shrinking a following pinch roughly thirty-fold until the burst left the window. No training pinch had experienced this: the largest 1 s gyroscope RMS before any of 459 pinch starts was 0.62 rad/s, whereas everyday noise reached 14 rad/s. Replays with real bursts spliced in (Table 8) show that the median/MAD scaling of (3) removes the blind spot for bursts up to about 4 s; motion lasting 6 s or more still causes a 3–6 s blackout.

7.4 Further Variations

Table 9 summarises the variations that were tried and rejected or deferred. A three-stage curriculum (newest clean sessions, then older camera-labelled sessions, then noise) reached 78.9% recall for pinch-in (15/19, median latency 469 ms) and 52.6% for pinch-out (10/19, 390 ms) at zero false activations on a reserved validation pair. Training on the newest clean data plus noise alone did not transfer to older sessions

Table 9 Variations tried

Variation	Result	Decision
Retrain on own false alarms	Recall 27% vs 31%, no fewer false activations	Off
2 s window, fourth convolution	49–51% vs 45% at ≈20/h; chosen threshold exceeded budget on noise	Deferred
Self-supervised pre-training	27 vs 7 false activations/h on noise; 152 vs 168 catches at equal FAR	Rejected
Still-hand rule in training	Model never learns that movement is not a pinch	Off for CNN
Fixed camera-mark threshold	110 false activations/h on pinch sessions	Per-session marks (20/h)
Pinch-shape and Haar-wavelet features	No gain for PPG + IMU; wavelet detail did not set a pinch apart	Not adopted

(4.9–31.4% recall). Because the same pair chose the threshold and supplied the metric, and it contains only 19 starts, this is validation evidence only.

7.5 Double-Pinch Gating

For a double-pinch gesture we specified an envelope of data preconditions and context gates, outside which the detector abstains, followed by candidate checks before any model score counts. On 278 camera-timed contacts, gates and checks kept about 80% of single pinches. They cut candidate jolts from 76 to 0.6 per minute during arm movement and from 40 to 0.4 during wrist twists. These thresholds are starting values to be re-measured at 100 Hz.

7.6 System Performance

Every optimisation was measured before it was made, on an Apple M3 laptop. Appending to the full dataset buffer fell from 452 μs to 0.1 μs, and the old path had also corrupted row order beyond 200,000 rows. Repeated raw-signal viewer requests fell from a full 52 ms re-parse to 1.3 μs from a bounded cache. Status events at orientation rate fell from up to 200 to about 10 per second. Processing a long recording in the trainer fell from 7.26 to 2.23 s, and the release binary shrank from 17.5 to 12.0 MB. Live inference costs about 0.2 ms per window in a debug build.

8 Discussion

8.1 RQ3: What Made Offline Results Predictive

The largest errors in this project came from evaluation rather than from code. Four practices inflated results before they were corrected: rest controls that were really mid-gesture, explored recordings reused as tests, false-activation rates over the wrong denominator, and per-window AUC used as if it were a release metric. Two labelling practices mattered as much as any model change. Cue-based labels carried a per-recording lag of up to 1.3 s, and a fixed camera threshold silently turned real pinches

into negatives. Training-time filters also change what a model learns: the still-hand rule, meant to reduce false activations, prevented the model from learning that movement is not a pinch. *Answer to RQ3: offline results became predictive only once evaluation replayed whole recordings through the deployed trigger, counted false activations per hour of no-gesture time, protected test sets from exploration and used camera-timed, per-session labels.*

8.2 Implications

For stock smartwatches, inertial sensing should be treated as the primary pinch signal, with PPG as a complementary channel. This agrees with OpenWatch's finding that PPG adds to inertial data rather than replacing it [10]. Small raw-signal networks with robust normalisation and everyday negatives generalise better than large engineered feature sets. Finally, the interaction design matters. Gating gestures on gaze dwell and requiring a paired release make occasional false detections far less costly than in an always-armed detector.

8.3 Threats to Validity

Internal validity. Thresholds were chosen on training data only, but most collections were explored during development; only the 14 October test was a true one-shot test. Camera labels depend on landmark accuracy and clock alignment, whose residual error was not independently measured.

External validity. All data come from one participant, one watch and one wrist, mostly at 50 Hz motion; pinches made while moving are rare. Results may not transfer to other people, devices or activities.

Construct validity. False activations were measured on recorded everyday-noise sessions rather than on full days of natural use, so the hourly rates are estimates over limited exposure (see (6)).

9 Limitations and Future Work

Sessions recorded on 14 October remain poorly detected (12–18%) by every model trained on other days, against 63–75% on 3–4 November. The next step is a sealed test, collected after freezing the model, preprocessing, thresholds and protocol. It should span several days with strap refits, and include 30–60 minutes of continuous everyday activity per session and pinches made while moving, recorded at 100 Hz. Per-user or per-session adaptation, which raised ViWatch from 45% to 97% [18], is the most promising modelling direction. A 2 s input window with stricter threshold selection is a second candidate. On the engineering side, open items are Wi-Fi peer authentication, physical validation on Windows and Linux, signed packaging and a BLE battery trial. The same look-pinch-turn interaction can then be extended to brightness and scrolling.

10 Conclusion

A consumer headset and smartwatch can control a laptop through a look-pinch-turn interaction. Head orientation selects the control, a compact CNN on watch motion

and PPG detects pinch in and pinch out, and wrist roll sets the value, all behind a fail-closed safety chain. Wrist PPG alone was not sufficient on a stock watch. Inertial fusion, camera-timed labels and event-based evaluation were what turned the detector from a promising offline score into a working interaction.

Acknowledgements. [Acknowledgements, or remove this heading.]

Declarations

- **Funding:** [State funding sources, or "Not applicable".]
- **Conflict of interest/Competing interests:** The author declares no competing interests. [Confirm, and use the heading the journal requires.]
- **Ethics approval and consent to participate:** All recordings were made with the author as the only participant; no other people took part. [Confirm whether an ethics approval or waiver is required for self-recorded physiological data, and state it.]
- **Consent for publication:** [Not applicable, or state.]
- **Data availability:** [State where the recordings can be obtained, or "available from the author on reasonable request".]
- **Materials availability:** [Not applicable, or state.]
- **Code availability:** [State the repository URL and licence, or the access conditions.]
- **Author contribution:** V.B. designed and built the system, collected and analysed the data, and wrote the manuscript. [Confirm.]

References

[1] Zhang, *et al.*: FinDroidHR: Smartwatch gesture input with optical heartrate monitor. Proc. ACM Interact. Mob. Wearable Ubiquitous Technol. (2018) https://doi.org/10.1145/3191788

[2] Buddhika, *et al.*: fSense: Unlocking the dimension of force for gestural interactions using smartwatch PPG sensor. In: Proc. Augmented Human International Conference (2019). https://doi.org/10.1145/3311823.3311839

[3] Zhao, *et al.*: PPG-based finger-level gesture recognition leveraging wearables. In: Proc. IEEE INFOCOM (2018). https://doi.org/10.1109/INFOCOM.2018.8486006

[4] Subramanian, Savur, Sahin: Using photoplethysmography for simple hand gesture recognition. In: Proc. IEEE System of Systems Engineering Conference (SoSE) (2020). https://doi.org/10.1109/SoSE50414.2020.9130489

[5] Ruan, *et al.*: Principal component analysis of photoplethysmography signals for improved gesture recognition. Frontiers in Neuroscience (2022) https://doi.org/10.3389/fnins.2022.1047070

[6] Fang, *et al.*: Exploration on the negative effects of sensor shifts in photoplethysmography-based gesture recognition and a solution based on transfer learning. IEEE Transactions on Instrumentation and Measurement (2023) https://doi.org/10.1109/TIM.2023.3268469

[7] Li, *et al.*: Feasibility of wearable PPG for simultaneous hand gesture and force level classification. IEEE Sensors Journal (2023) https://doi.org/10.1109/JSEN.2023.3241126

[8] Eddy, *et al.*: Discrete gesture recognition using multimodal PPG, IMU, and single-channel EMG recorded at the wrist. IEEE Sensors Letters (2024) https://doi.org/10.1109/LSENS.2024.3447240

[9] Zhao, *et al.*: Towards low-cost sign language gesture recognition leveraging wearables. IEEE Transactions on Mobile Computing (2021) https://doi.org/10.1109/TMC.2019.2962760

[10] Bonazzi, et al.: OpenWatch: A Multimodal Benchmark for Hand Gesture Recognition on Smartwatches. arXiv:2605.04791v2 (2026). https://arxiv.org/html/2605.04791v2

[11] Wang, *et al.*: A novel PPG-FMG-ACC wristband for hand gesture recognition. IEEE Journal of Biomedical and Health Informatics (2022) https://doi.org/10.1109/JBHI.2022.3194017

[12] [Author list to be completed]: Multi-modality gesture recognition for portable wearables: A high-integration system combining electromyography, inertial measurement unit, and photoplethysmography. Engineering Applications of Artificial Intelligence (2026) https://doi.org/10.1016/j.engappai.2026.115547

[13] Hauptmann, *et al.*: μDPad: A large-scale multimodal PPG and IMU dataset for wrist-worn microgesture recognition. In: ACM Conference Proceedings (2026). https://doi.org/10.1145/3776574.3831197

[14] Hu, *et al.*: WatchForce: Wrist-worn PPG and IMU sensing for hand force estimation. Computer Methods and Programs in Biomedicine (2026) https://doi.org/10.1016/j.cmpb.2026.109547

[15] Tchantchane, *et al.*: Review of hand gesture recognition systems based on non-invasive wearable sensors. Advanced Intelligent Systems (2023) https://doi.org/10.1002/aisy.202300207

[16] Charlton, *et al.*: The 2023 wearable photoplethysmography roadmap. Physiological Measurement (2023) https://doi.org/10.1088/1361-6579/acead2

[17] Tsunoda, *et al.*: [title to be completed]. In: Proc. Int. Conf. Mobile and Ubiquitous Multimedia (MUM) (2024). https://www.iplab.cs.tsukuba.ac.jp/paper/

international/tsunoda_MUM2024.pdf

[18] [Authors to be completed]: ViWatch [full title to be completed]. In: Proc. ACM Symposium on User Interface Software and Technology (UIST) (2023). https://www.cs.virginia.edu/\texttildelowstankovic/psfiles/ViWatch_UIST_%20FINAL.pdf

[19] Kim, *et al.*: [title to be completed]. In: Proc. ACM CHI Conference on Human Factors in Computing Systems (2025). arXiv:2503.02308. https://arxiv.org/abs/2503.02308

[20] Sagawa, S., Koh, P.W., Hashimoto, T.B., Liang, P.: Distributionally Robust Neural Networks for Group Shifts. arXiv:1911.08731 (2019)

[21] Ganin, et al.: Domain-Adversarial Training of Neural Networks. arXiv:1505.07818 (2015)

[22] Sun, B., Saenko, K.: Deep CORAL: Correlation Alignment for Deep Domain Adaptation. arXiv:1607.01719 (2016)

[23] Dempster, A., Schmidt, D.F., Webb, G.I.: MiniRocket: A Very Fast (Almost) Deterministic Transform for Time Series Classification. arXiv:2012.08791 (2020)

[24] Arjovsky, M., Bottou, L., Gulrajani, I., Lopez-Paz, D.: Invariant Risk Minimization. arXiv:1907.02893 (2019)

[25] Zhou, K., Yang, Y., Qiao, Y., Xiang, T.: Domain Generalization with MixStyle. arXiv:2104.02008 (2021)

[26] Geurts, P., Ernst, D., Wehenkel, L.: Extremely randomized trees. Machine Learning **63**(1), 3–42 (2006) https://doi.org/10.1007/s10994-006-6226-1

[27] scikit-learn developers: ExtraTreesClassifier, scikit-learn documentation. https://scikit-learn.org/stable/modules/generated/sklearn.ensemble.ExtraTreesClassifier.html. Accessed 7 Nov. 2026

[28] Savitzky, A., Golay, M.J.E.: Smoothing and differentiation of data by simplified least squares procedures. Analytical Chemistry **36**(8), 1627–1639 (1964) https://doi.org/10.1021/ac60214a047

[29] Tauri Contributors: Tauri 2.0. https://v2.tauri.app/. Accessed 7 Nov. 2026

[30] Slattery, N.: sony-head-tracker: Sony headphone motion sensors as a low-latency head tracker, release v2.2.0. https://github.com/NicholasSlattery/sony-head-tracker. Accessed 7 Nov. 2026

[31] Samsung Electronics: Samsung Health Sensor SDK. https://developer.samsung.com/health/sensor/overview.html. Accessed 7 Nov. 2026

[32] deviceplug: btleplug: Rust cross-platform host-side Bluetooth LE access library. https://github.com/deviceplug/btleplug. Accessed 7 Nov. 2026

[33] Google: MediaPipe Hand Landmarker task guide. https://ai.google.dev/edge/mediapipe/solutions/vision/hand_landmarker. Accessed 7 Nov. 2026

[34] PyTorch Foundation: PyTorch. https://pytorch.org/. Accessed 7 Nov. 2026