

Linear regression: Abalone growth and pH example

Megan Zhao

2026-05-15

Table of contents

Set up	1
Abalone example	2
a. Questions and hypotheses	2
b. Cleaning	2
c. Exploratory data visualization	2
d. Abalone model	4
Model fitting	4
Diagnostics	4
Model summary	4
Generating predictions	5
Why generate model predictions?	6
Visualizing model predictions and data	7
Creating a table with model coefficients, 95% confidence intervals, and more . .	8

Set up

```
library(tidyverse) # general use
library(janitor) # cleaning data frames
library(here) # file/folder organization
library(readxl) # reading .xlsx files
library(ggeffects) # generating model predictions
library(flextable) # creating tables
```

```
# abalone data from Hamilton et al. 2022
# read in data from excel (HOLY PEAK)
# pull 'Abalone IMTA_growth and pH.xlsx' from 'data' file using 'here' function
abalone <- read_xlsx(here("data", "Abalone IMTA_growth and pH.xlsx"))
```

Abalone example

Data from Hamilton et al. 2022. “Integrated multi-trophic aquaculture mitigates the effects of ocean acidification: Seaweeds raise system pH and improve growth of juvenile abalone.”
<https://doi.org/10.1016/j.aquaculture.2022.738571>

a. Questions and hypotheses

Question: How does pH predict abalone growth (measured in change in shell surface area per day, $\text{mm}^2 \text{d}^{-1}$)?

H_0 : there is no effect of pH on abalone growth (don’t put significance in hypothesis, just for common phrasing)

H_A : there is an effect of pH on abalone growth


b. Cleaning

```
# create new object from 'abalone' data set
abalone_clean <- abalone |>
  # clean column names
  clean_names() |>
  # select columns of interest
  select(mean_p_h, change_in_area_mm2_d_1_25) |>
  # rename columns for clarity
  rename(mean_ph = mean_p_h,
         change_in_area = change_in_area_mm2_d_1_25)
```

Don’t forget to look at your data! Use `View(abalone_clean)` in the Console.

c. Exploratory data visualization

```
# base layer: ggplot
ggplot(data = abalone_clean, # starting data frame
       aes(x = mean_ph, # x-axis: pH, y-axis: shell surface area change
           y = change_in_area)) +
# first layer: geom point to represent individual observations
geom_point(size = 4,
           stroke = 1,
           fill = "firebrick4",
           shape = 21)
```



Where does the missing value come from?

The missing value comes from a pair of tanks in which the pH sensor malfunctioned, so there is no pH reading from those tanks.

Don't forget to turn your warnings off either in the individual code chunk or in the YAML at the top of the file.


d. Abalone model

Model fitting

```
# create linear object called abalone_model object
abalone_model <- lm(
  change_in_area ~ mean_ph, # formula: change in shell SA as a function of pH
  data = abalone_clean      # data frame: clean abalone data
)
```

Diagnostics

```
# create diagnostic plots
par(mfrow = c(2, 2)) # displays plots in a 2x2 grid
plot(abalone_model)  # display diagnostic plots
```



Model summary

```
# more information about the model
summary(abalone_model)
```

Call:

```
lm(formula = change_in_area ~ mean_ph, data = abalone_clean)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-0.42714	-0.29282	0.08769	0.21258	0.43965

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-18.5010	6.1601	-3.003	0.01488 *
mean_ph	2.9827	0.7596	3.926	0.00348 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.3063 on 9 degrees of freedom

(1 observation deleted due to missingness)

Multiple R-squared: 0.6314, Adjusted R-squared: 0.5905

F-statistic: 15.42 on 1 and 9 DF, p-value: 0.003477

What is the slope estimate (with standard error?)

$$\beta_1 = 2.98 \pm 0.76$$

What is the intercept estimate (with standard error?)

$$\beta_0 = -18.5010 \pm 6.16$$

Generating predictions

```
# creating a new object called abalone_preds
abalone_preds <- ggpredict(
  abalone_model,      # model object
  terms = "mean_ph"   # predictor (in quotation marks)
)

# display the predictions
abalone_preds
```

```
# Predicted values of change_in_area
```

mean_ph	Predicted	95% CI
7.94	5.19	4.83, 5.54
7.95	5.21	4.86, 5.55
8.06	5.53	5.30, 5.76
8.10	5.67	5.46, 5.88
8.10	5.67	5.46, 5.88
8.14	5.77	5.55, 5.98
8.15	5.81	5.59, 6.04
8.33	6.36	5.92, 6.80

Look at the column names using `colnames(abalone_preds)` in the Console.

What are the column names?

'x', 'predicted', 'std.error', 'conf.low', 'conf.high', 'group' (not going to worry about 'group' column for now)

Look at the actual object (by clicking on it in Environment).

Look at the class of the object using `class(abalone_preds)` in the Console.

What is this type of object?

This is a ggeffects object but it is also a data frame

View `abalone_preds` like a data frame.

Why generate model predictions?

This dataset does not include any actual observations of abalone growth at $\text{pH} = 8$.

However, the model can tell us a prediction for what abalone growth could be if $\text{pH} = 8$ based on the existing data.

Figure out what abalone growth the model would predict at $\text{pH} = 8$.

```
# finding the model prediction at a specific value
ggpredict(
  abalone_model,      # model object
  terms = "mean_ph[8]" # predictor (in quotation marks) and predictor value in brackets
)
```

Predicted values of change_in_area


mean_ph	Predicted	95% CI
8	5.36	5.08, 5.64

How would you interpret this?

At pH = 8, the model predicts abalone shell growth of 5.36 (95% CI: 5.08, 5.64) mm²

Visualizing model predictions and data

```
# base layer: ggplot
# using clean data frame
ggplot(data = abalone_clean,
       aes(x = mean_ph,
           y = change_in_area)) +
# first layer: points representing abalones
geom_point(size = 4,
           stroke = 1,
           fill = "firebrick4",
           shape = 21) +
# second layer: ribbon representing confidence interval
# using predictions data frame
geom_ribbon(data = abalone_preds,
          aes(x = x,
              y = predicted,
              ymin = conf.low,
              ymax = conf.high),
          alpha = 0.1) +
# third layer: line representing model predictions
# using predictions data frame
geom_line(data = abalone_preds,
         aes(x = x,
             y = predicted)) +
# axis labels
labs(x = "Mean pH",
     y = expression("Change in shell area (*mm2~d-1*)")) +
# theme
theme_minimal()
```



Creating a table with model coefficients, 95% confidence intervals, and more

Note: this function is from `flextable`.

```
as_flextable(abalone_model)
```

	Estimate	Standard Error	t value	Pr(> t)	
(Intercept)	-18.501	6.160	-3.003	0.0149	*
mean_ph	2.983	0.760	3.926	0.0035	**

Signif. codes: 0 <= '***' < 0.001 < '**' < 0.01 < '*' < 0.05

Residual standard error: 0.3063 on 9 degrees of freedom

Multiple R-squared: 0.6314, Adjusted R-squared: 0.5905

F-statistic: 15.42 on 9 and 1 DF, p-value: 0.0035

END OF ABALONE EXAMPLE