

CRAFT

Effects & Parameter Reference

CRAFT takes a loaded sample and transmutes it — then prints the result back to a sample you can play. Each of the three slots holds one effect; the slots run in order, top to bottom. Audition the chain live with **Button 2** (parameters update in real time as you turn them), then **Render** to save the processed audio as a new file or over the source.

READING THIS GUIDE

- 1. Every parameter is **0–100** unless a fixed value set is listed.
- 2. **mix** blends dry ↔ processed; **tone** shapes brightness.
- 3. What you audition is exactly what gets printed — preview and render share the same engine.

copy Copy — Generation Loss

The vintage-sampler capture: re-records the sound through degraded conversion. “A copy of a copy.”

PARAM	RANGE	WHAT IT DOES
rate	48k 32k 27k 22k 16k 12k	Sample-rate reduction (sample-and-hold decimation). Lower rates make the sample duller, grainier, and more openly aliased — the classic vintage digital character.
bits	16 12 10 8 6	Bit-depth crush (quantization). 16 is transparent; lower depths add quantization noise, grit, and older-sampler texture.
drive	0–100	Input coloration: how hard the signal hits the capture stage before the transfer curve. Higher adds drive and overload.
tone	clean soft ring leak bad	Capture bandwidth filter. clean is open; through soft / ring / leak it gets progressively darker (ring adds a resonant, telephone-ish bite) down to bad , heavily band-limited.
curve	lin comp warp noisy	Non-linear transfer curve. lin clips hard; comp soft-compresses; warp adds asymmetric (even-harmonic) shape; noisy softens and adds grain.
wear	0–100	Age & wear instability: slow gain wobble plus a low bed of correlated hiss — the looseness of an old machine.

dial Dial — Between Stations

Ring modulation: the heterodyne whistle you get tuning between two radio stations. Bell, robot, inharmonic tones.

PARAM	RANGE	WHAT IT DOES
tune	0–100	Carrier frequency, ~30 Hz to ~3 kHz (exponential). Sets the pitch/character of the ring tone — low is a tremolo-like throb, high is metallic.
beat	0–100	Detune of a second carrier (0–30 Hz). The two carriers beat against each other to give the wavering “between stations” movement.
shape	0–100	Carrier waveform morph, sine → square. Higher is harsher and more metallic (richer carrier harmonics).
depth	0–100	Ring-modulation amount. 0 passes the signal through; 100 is full ring (carrier fully multiplies the signal).
tone	0–100	Post low-pass (~800 Hz–18 kHz) to tame the harsh upper partials the ring creates — keeps it musical.
mix	0–100	Dry/wet blend of the ring-modded signal against the original.

snap Snap — Transient Burn

Detects attacks and burns the front edge. Punches drums, plucks and chops into old hardware; sustain stays mostly clean.

PARAM	RANGE	WHAT IT DOES
sense	0–100	Transient sensitivity — how easily attacks are detected. Higher reacts to smaller transients.
burn	0–100	Drive/overload applied to the detected attack — the amount of saturation poured onto the front edge.
edge	0–100	High-frequency bite added on the transient — makes attacks clickier and more cutting.
decay	0–100	How long the burn lasts after the attack (~2–300 ms). Short = a click; longer = punch and smear.
clip	0–100	Overload shape, soft (rounded tanh) → hard (clipped). Changes the character of the burn.
mix	0–100	Blends the burned-transient layer with the original sample.

warm Warmth — Body Sat

The musical one. Adds midrange weight, density and saturation — like printing hot through a desk or tape stage.

PARAM	RANGE	WHAT IT DOES
drive	0–100	Saturation amount — pushes the body stage harder for more harmonic density and thickness.
tone	0–100	Dark ↔ bright tilt. Below 50 leans darker, 50 is neutral, above 50 adds air and bite.
body	0–100	Low-mid mass (~320 Hz). Adds weight and fundamental body to thin samples.
glue	0–100	Compression/leveling. Higher makes the sample feel denser, glued and more forward.
grit	0–100	Asymmetry — adds even-harmonic saturation for warmer, more analog-feeling color.
mix	0–100	Dry/wet blend of the saturated body against the original.

warp Warp — Wow & Flutter

Tape speed instability: pitch warble, dropouts and age — a modulated delay line warps the playback speed.

PARAM	RANGE	WHAT IT DOES
wow	0–100	Slow drift depth (~0.7 Hz) — the lazy, seasick pitch wander of a worn tape.
flut	0–100	Fast flutter depth (~7 Hz) — quick pitch shimmer/warble layered on top of wow.
rate	0–100	Overall modulation speed (~0.25×–4×), scaling both wow and flutter together.
drop	0–100	Tape dropouts — random, smoothed amplitude dips, as if the oxide is failing.
tone	0–100	Head-bump / darkening. Rolls off the top end for that dull, well-played-tape feel.
mix	0–100	Dry/wet blend of the warped signal against the original.

howl Howl — Feedback Fold

A tiny internal feedback network with a wavefolder in the loop — metallic, resonant, can scream. Bounded so it never truly runs away.

PARAM	RANGE	WHAT IT DOES
gain	0–100	Input drive — how hard the signal hits the feedback/fold network.
feed	0–100	Feedback amount. Higher gets more resonant and unstable — capped below true runaway and soft-limited in the loop.
time	0–100	Comb time / pitch (~3 kHz–100 Hz). Short times ring at a high metallic pitch; longer times drop the resonance lower.
fold	0–100	Wavefold amount inside the loop — more folding tears the harmonics apart for an aggressive, glassy edge.
damp	0–100	Darkens and stabilizes the feedback path, taming harsh runaway highs. Raise it if howl gets too hot.
mix	0–100	Dry/wet blend of the feedback-fold result against the original.

CRAFT · six slots of transmutation — copy · dial · snap · warm · warp · howl