

Initiative for Modeling the Legal Analysis Methodology

Technical manual for the LAM content generation service

Disclaimer

The views expressed in this report are purely those of the Author(s) and may not, in any circumstances, be interpreted as stating an official position of the European Commission. The European Commission does not guarantee the accuracy of the information included in this study, nor does it accept any responsibility for any use thereof. Reference herein to any specific products, specifications, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favouring by the European Commission. All care has been taken by the author to ensure that s/he has obtained, where necessary, permission to use any parts of manuscript s including illustrations, maps, and graphs, on which intellectual property rights already exist from the titular holder(s) of such rights or from her/his or their legal representative.

Document metadata

Reference	WP 4.1 & WP 4.2: Technical manual for the LAM content generation service
Corporate Author	Publications Office of the European Union
Author	Eugeniu Costetchi
Reviewers	Juraj Kuba, Miltiadis Charitos, Marcin Baryn
Contractor	Infeurope
Framework contract	FC No 10688/ OF No 36269
Work package	WP 4.1 & WP 4.2
Delivery date	19 Feb 2021
Suggested readers	system administrators, software developers, future users

Abstract

This document provides technical guidance on how to install and configure LAM Validator and LAM content generator, two micro-services developed in the context of the initiative for modelling the Legal Analysis Methodology (LAM).

The LAM validator is used to perform validation of RDF content after it is exported from VocBench 3 platform. The validation procedure is based on SHACL data shape checking and is done using LAM-SKOS-AP application profile.

The LAM content generator is used to generate, from valid RDF files, the HTML representation, PDF representation and index files in JSON representation.

Contents

1	Introduction	5
2	Scope	5
3	Target audience	5
4	Technology background	6
5	Requirements	6
6	Installation	7
7	Usage	9
	7.1 LAM Validator	9
	7.2 LAM Generation Services	12
	7.3 LAM Dedicated Triple Store	14
8	Configuration	14
	8.1 LAM Validator	16
	8.2 LAM Generation Service	18
	8.3 LAM dedicated triple store	18
9	Makefile targets	19
10	Indexes fields	20
	Appendices	24

1 Introduction

This document provides technical guidance on how to install and configure LAM Validator and LAM content generator, two micro-services developed in the context of the initiative for modelling the Legal Analysis Methodology (LAM).

The LAM validator is used to perform validation of RDF content after it is exported from VocBench 3 platform. The validation procedure is based on SHACL data shape checking and is done using LAM-SKOS-AP application profile.

The LAM content generator is used to generate, from valid RDF files, the HTML representation, PDF representation and index files in JSON representation.

The employed infrastructure technology for the micro-service management is based on Docker introduced in Section 4.

This document describes the installation and configuration procedures along with stating the scope, target audience and introducing briefly the Docker technology.

2 Scope

This document aims at covering the installation and configuration instructions for the suite of the following software services:

1. LAM RDF validator
2. LAM content generator

3 Target audience

The target audience for this document comprises the following groups and stakeholders:

- System administrators
- Developers in charge
- Technical users

4 Technology background

Infrastructure and deployment configuration rely on the *Docker technology* [1, 2]. Docker is a set of platform as a service (PaaS) products that use OS-level virtualisation to deliver software in packages called containers. Containers are isolated from one another and bundle their own software, libraries and configuration files; they can communicate with each other through well-defined channels. All containers are run by a single operating system kernel and therefore collectively, use fewer resources than virtual machines.

Docker technology is chosen because it solves the problem known in the system administration world as the “dependency hell”, which refers to three specific issues: conflicting dependencies, missing dependencies, and platform differences.

Docker solved these issues by providing the means for images to package an application along with all of its dependencies easily and then run it smoothly in disparate development, test and production environments.

Docker Compose is a tool for defining and running multi-container Docker applications or application suites. It uses YAML files to configure the application’s services and performs the creation and start-up and shutdown process of all the containers with a single command. The `docker-compose` command line interface (CLI) utility allows users to run commands on multiple containers at once, for example, building images, scaling containers, running containers that were stopped, and more. Commands related to image manipulation, or user-interactive options, are not relevant in Docker Compose because they address one container. The *docker-compose.yml* file is used to define an application’s services and includes various configuration options.

The services and applications enumerated in Section 2 are packaged into Docker images. The associated `docker-compose.yml` file defines the suite of applications and micro-service configurations in order to be deployed and ran together with ease. This manual explains how to run and configure this suite of Docker containers using Docker Compose tool.

5 Requirements

Although Docker can be executed on any platform, for performance and security reasons we recommend using a Linux OS with kernel version 5.4.x or higher. The

services have been tested on Ubuntu 20 server.

There is a range of ports that must be available on the host machine as they will be bound to by different docker services. Although the system administrator may choose to change them by changing the values in of specific environment variables. The inventory of pre-configured ports is provided in Table 1.

Service name		HTTP port UI	HTTP port API	Mounted volume
LAM validator		10002	10001	rdf- validator -shacl- shape
LAM Service	Generation	8050	4050	
LAM triple store	dedicated	3010		lam-fuseki

Table 1: Port usage inventory

The minimal hardware requirements are as follows

1. CPU: Dual core 3Ghz
2. RAM: 8Gb
3. SDD system: 2Gb
4. SDD data: 8Gb

6 Installation

In order to run the services it is necessary to have Docker [2] service and docker-compose tool installed. To install them follow the instructions provided on the official websites

1. Docker - <https://docs.docker.com/engine/install>
2. Docker Compose - <https://docs.docker.com/compose/install>

In case you are using Debian-like OS such as Ubuntu, you may simply run the following Bash commands to install and set the appropriate permissions.

```
sudo apt -y install docker.io docker-compose git make
sudo groupadd docker
sudo usermod -aG docker $USER
newgrp docker
```

Please note that the *docker.io* package is installed rather than the *docker-ce* one.

Next, to launch the services, clone the Git repository containing the *docker-compose.yml*, *.env* file and the *Makefile*.

```
git clone https://github.com/meaningfy-ws/lam-workflow.git
cd lam-workflow
```

You may choose to adjust these files as necessary on your system. Then change directory into the *lam-workflow* folder and Makefile commands to start and stop services will be available. To start services run

```
make start-services
```

To stop the services run

```
make stop-services
```

Downloading the Docker images will be triggered automatically on first request to start the services.

To start the services using Makefile

```
make location=</your-custom/shapes/location> validator-set-shacl-
  shapes
make start-services
```

To stop the services using Makefile

```
make stop-services
```

To start services without Makefile first prepare the volume with LinkedPipes ETL configurations file like this

```
docker rm temp | true
docker volume rm rdf-validator-shacl-shapes | true
```



```
docker volume create rdf-validator-shacl-shapes
docker container create --name temp -v rdf-validator-shacl-shapes:/
  data busybox
docker cp <your-custom/shapes/location>. temp:/data
docker rm temp
```

then start the services

```
docker-compose --file docker/docker-compose.yml --env-file docker/.
  env up -d
```

To stop the services run

```
docker-compose --file docker/docker-compose.yml --env-file docker/.
  env down
```

The detailed explanation on how to configure them is provided in the Configuration section for each of these services (See Section 8.1).

7 Usage

After running the following `make` command:

```
make start-services
```

described in detail in Section 6, all services will be available at either `localhost` or your configured domain name. The specific ports for each service are specified in table 1.

The following explanation of usage for the services assumes that you have access to `localhost`.

7.1 LAM Validator

API

To access the online documentation and testing grounds for the LAM Validator API service visit the following link <http://localhost:10001/ui>. You'll be greeted with an interface like in Figure 1.




Figure 1: LAM Validator API documentation

Here you can find the definition for each API endpoint, the HTTP methods, request structure, and the possibility to test the endpoints.

UI

To access the user interface for the LAM Validator service visit the following link <http://localhost:10002>. You'll be greeted with an interface like in Figure 2 containing 2 pages.




Figure 2: LAM File Validator UI page

Here you can access the services for file validation (Figure 2) and SPARQL endpoint validation (Figure 3).




Figure 3: LAM SPARQL Endpoint Validator UI page

7.2 LAM Generation Services

API

To access the online documentation and testing grounds for the LAM Generation Services API service visit the following link <http://localhost:4050/ui>. You'll be greeted with an interface like in Figure 4.




Figure 4: LAM Generation Services API documentation

Here you can find the definition for each API endpoint, the HTTP methods, request structure, and the possibility to test the endpoints.

UI

To access the user interface for the LAM Generation Services visit the following link <http://localhost:8050>. You'll be greeted with an interface like in Figure 5 containing 2 pages.




Figure 5: LAM Generation Services home page

Here you can request the LAM report in 2 formats (Figure 6), the LAM indexes, or both report formats and indexes in a zipped format.




Figure 6: LAM Generation Services report generation

7.3 LAM Dedicated Triple Store

To access the LAM Fuseki triple store service visit the following link `http://localhost:3010`. You'll be requested the login credentials which can be found in Table 4. After logging in, you'll be greeted with an interface like in Figure 7.




Figure 7: LAM Fuseki home

For more information on how to use Fuseki read the available documentation available at jena.apache.org.

8 Configuration

The deployment suite of micro-services is defined `docker-compose.yml` file. At deployment and at runtime, the service configurations are provided through OS environment variables available in the `.env` file. The role of the `.env` file is to enable the system administrators to easily change default configurations as necessary in the context of their environment.

The suite of micro-services is built, started and shut down via `docker-compose`, a tool designed especially for managing multi-container Docker applications, by describing

them in a single file. Then, with a single command, you create and build, start or stop all the services using that configuration file.

In order to avoid hard coding parameters, docker-compose allows you to define them externally. You have the option to define them as operating system level environment variables or provide them in a single file, which is passed as a parameter to the docker-compose tool using the `-env-file` command line argument. Having them in a single file makes much more sense and it is more pragmatic, as you can see and manage all parameters in one place, add the file to the version control system (the contents of the file will evolve and be in sync with the actual code) and have different files for different environments.

The file is usually named `.env` and contains all of the parameters that you want to be able to change and that you need to build and run the defined containers.

Having the parameters in an `.env` file is very useful in a multitude of scenarios, where you would want to have different configurations for different environments where you might want to deploy. As a more specific example, consider a continuous delivery pipeline and the URLs and ports you want your containers to bind (or to connect) to. You thus can easily have two `.env` files, one named `test.env` and one named `acceptance.env`. Each file would have the same declared variables, but with different values for each of the continuous delivery pipeline stage where it's being deployed. The benefit is that you deploy and test/use the same containers/artifacts and are able to configure them, on the spot, according to the environment that they are integrated with.

Let's take, for example, the RDF Validator API Docker container, which is defined, in the `docker-compose.yml` file as it follows:

```
lam-validator-api:
  container_name: lam-validator-api
  image: meaningfy/lam-validator-api:latest
  ports:
    - ${RDF_VALIDATOR_API_PORT}:${RDF_VALIDATOR_API_PORT}
  env_file: .env
  restart: always
  networks:
    - mydefault
```

The variable used in the definition of this service is just one, `RDF_VALIDATOR_API_PORT`. And the place where docker-compose will look for that variable is specified in the

`env_file:` `.env` line.

Now, if you look in the “.env” file, you will quickly see that the variable is defined as `RDF_VALIDATOR_API_PORT=10001`. Change the value of the port, rebuild the micro-services and RDF Differ will no longer be listening on 10001, but on the new port that you specified.

This section describes the important configurations options available for each of the services.

8.1 LAM Validator

LAM validator application exposes an API and an UI and does not depend on any additional services as everything is encapsulated into the Docker image.

The configuration options are summarised below.

Description	Value	Associated variable
Validator Service UI port	10002	<code>RDF_VALIDATOR_UI_PORT</code>
Validator Service UI location	<code>http://lam-validator-ui</code>	<code>RDF_VALIDATOR_UI_LOCATION</code>
Validator Service API port	10001	<code>RDF_VALIDATOR_API_PORT</code>
Validator Service API location	<code>http://lam-validator-api</code>	<code>RDF_VALIDATOR_API_LOCATION</code>

Table 2: LAM Validator configuration

Note, when validating SPARQL endpoints, the fully qualified domain name of the machine must be specified. As a consequence, “localhost” domain will not work as expected.

Configure SHACL Shapes Files

The docker image for the LAM validation API service pulled from **docker hub** already contains the required SHACL shape files, as defined in this **repository**.

If you want to change the SHACL shapes files, you can use the following customiza-

tion implemented using **docker's volumes** mechanism. This implementation has been chosen as it requires no in service code modifications from the end-user's side.

An externally defined volume `rdf-validator-shacl-shapes` which will contain the custom files is coupled with the `rdf-validator-api` docker container to use when validating. The coupling of the volume to the service container is done with the following statement, which is not included in the default docker compose configuration.

```
volumes:
- rdf-validator-shacl-shapes:${RDF_VALIDATOR_SHACL_SHAPES_LOCATION}
```

The lines above map the custom shapes that have been copied to the docker volume with the internal location of the container which has been defined in the `.env` file.

You have to copy these 2 lines in the `lam-validator-api` container definition in the `docker-compose.yml` file after the `image: meaningfy/lam-validator-api:latest` line.

Additionally, the externally defined volume has to be specified in the `docker-compose.yml` file:

```
volumes:
  rdf-validator-shacl-shapes:
    external: true
```

To make the custom shapes available to the container create the volume and run the `make` commands, indicating the location of your shapes through the `location` variable.

```
make build-volumes
make location=<location to shapes> set-shacl-shapes
```

NOTE: Make sure that the location specified ends with a trailing slash `/`, otherwise the command will not work properly and the templates will not be copied to the docker volume.

Example:

```
make location=/shapes/location/ set-shacl-shapes
```

After this, restart the `lam-validator-api` container for the effects to take place.

8.2 LAM Generation Service

LAM Generation Service application exposes an API and an UI for generating the LAM reports (in HTML and PDF formats) and the document index files. It depends on a dedicated triple store which will contain the LAM dataset indicated by the `LAM_FUSEKI_QUERY_URL` described in table 4 environment variable.

The configuration options are summarised below.

Description	Value	Associated variable
LAM Generation Service UI port	8050	<code>LAM_UI_PORT</code>
LAM Generation Service UI location	<code>http://lam-generation-service-ui</code>	<code>LAM_UI_LOCATION</code>
LAM Generation Service API port	4050	<code>LAM_API_PORT</code>
LAM Generation Service API location	<code>http://lam-generation-service-api</code>	<code>LAM_API_LOCATION</code>

Table 3: LAM Generation Service configuration

8.3 LAM dedicated triple store

LAM Generation Services depends on a Fuseki triple store and query the data required for the LAM reports and index files.

The available configurations are described below.

Description	Value	Associated variable
Admin account password	admin	<code>LAM_FUSEKI_ADMIN_PASSWORD</code>
User name	admin	<code>LAM_FUSEKI_USERNAME</code>
Password	admin	<code>LAM_FUSEKI_PASSWORD</code>
Folder where Fuseki stores data	<code>./data/diff</code>	<code>LAM_FUSEKI_DATA_FOLDER</code>
Additional arguments passed to JVM	<code>-Xmx2g</code>	<code>LAM_FUSEKI_JVM_ARGS</code>
URL	<code>http://rdf-differ-fuseki</code>	<code>LAM_FUSEKI_LOCATION</code>

Table 4 continued from previous page

LAM Fuseki port	3030	LAM_FUSEKI_PORT
LAM Fuseki External port	3010	LAM_FUSEKI_EXTERNAL_PORT
LAM Fuseki location	http://lam-fuseki	LAM_FUSEKI_LOCATION
Fuseki LAM dataset location	/lam/query	LAM_FUSEKI_QUERY_URL

Table 4: LAM Generation Services dedicated triple store configuration

9 Makefile targets

Makefile targets provide a convenient and easy way of running different tools that the software packages provide. The usage is **make *target***.

Following is a list of available targets along with the description.

- **install** - Upgrades PIP to the latest version and installs the local requirements
- **test** - Runs pytest which in turns executes the unit and BDD tests which are ran using headless Chrome. You need to successfully run the **install** target beforehand, as it installs the necessary prerequisites (the chrome browser and the driver which corresponds to that specific chrome browser version)
- **test-with-ui** - Runs pytest which in turns executes the unit and BDD tests which are ran using the fully UI enabled Chrome. You need to successfully run the **install** target beforehand, as it installs the necessary prerequisites (the chrome browser and the driver which corresponds to that specific chrome browser version). A "Chrome is being controlled by automated test software" message will be displayed on the top. Please wait for the tests to finish and do not interact with the browser window(s) driven by the BDD tests.
- **build-services** - Uses docker-compose to build all the services defined in the docker/docker-compose.yml file.
- **start-services** - Uses docker-compose to start the services defined in the docker/docker-compose.yml file.
- **stop-services** - Uses docker-compose to stop the services defined in the docker/docker-compose.yml file.

- **generate-indexes** - Uses eds4jinja2 to generate the indexes that will later be sent to Elasticsearch for indexing.
- **generate-content** - Uses eds4jinja2 to generate the content that will be integrated in the portal.
- **generate-tests-from-features** - Based on the feature files, this target generates the missing Python test code.

10 Indexes fields

1. CELEX

- **classURI**: The URI of the class (for example `http://publications.europa.eu/resources/authority/lam/c_108`)
- **types**: The RDF type(s) (for example `http://www.w3.org/2004/02/skos/core#Concept`)
- **authors**: The author(s) of the current class (for example `http://publications.europa.eu/resource/authority/corporate-body/CONSIL`)
- **resourceTypes**: The resource type (for example `http://publications.europa.eu/resource/authority/resource-type/STRATEGY_COMMON`). This is also known as the type of act (`lamd:md_fm\endverbatim`).
- **collections**: The collection that the current class is part of (for example `http://publications.europa.eu/resources/authority/lam/class_30THER`)
- **dnClassValues**: Class or subclass according to CDM.
- **dc**: The Eurovoc concept for this specific class.
- **ct**: The subject matter concept for this specific class.
- **cc**: The directory code for this specific class.
- **labels**: The label(s) of the current class (for example "Common strategy , Common strategy , Common strategy , Common strategy (CFSP number), Common strategy (CFSP number), Common strategy (CFSP number)")

- **notes:** The notes of the current class (for example "Proposal: strategy_council .")
- **examples:** The examples for the current class (for example "32003E0897, Common Strategy 2003/897/CFSP of the European Council of 12 December 2003 amending Common Strategy 1999/877/CFSP on Ukraine in order to extend the period of its application , Stratégie commune 2003/897/PESC du Conseil européen du 12 décembre 2003 modifiant la stratégie commune 1999/877/PESC à l'égard de l'Ukraine afin de proroger sa période d'application, 32003E0897, Common Strategy 2003/897/CFSP of the European Council of 12 December 2003 amending Common Strategy 1999/877/CFSP on Ukraine in order to extend the period of its application , Stratégie commune 2003/897/PESC du Conseil européen du 12 décembre 2003 modifiant la stratégie commune 1999/877/PESC à l'égard de l'Ukraine afin de proroger sa période d'application")

2. Classes

- **classURI:** The URI of the class (for example http://publications.europa.eu/resources/authority/lam/c_108)
- **types:** The RDF type(s) (for example <http://www.w3.org/2004/02/skos/core#Concept>)
- **AU:** The author(s) of the current class (for example <http://publications.europa.eu/resource/authority/corporate-body/CONSIL>)
- **FM:** The resource type (for example http://publications.europa.eu/resource/authority/resource-type/STRATEGY_COMMON). This is also known as the type of act (`lamd:md_fm`).
- **collections:** The collection that the current class is part of (for example http://publications.europa.eu/resources/authority/lam/class_30THER)
- **CDM_CLASS:** Class or subclass according to CDM.
- **DC:** The Eurovoc concept for this specific class.
- **CT:** The subject matter concept for this specific class.
- **CC:** The directory code for this specific class.
- **DN_CLASS:** The CELEX class.

- **labels:** The label(s) of the current class (for example "Common strategy , Common strategy , Common strategy , Common strategy (CFSP number), Common strategy (CFSP number), Common strategy (CFSP number)")
- **notes:** The notes of the current class (for example "Proposal: strategy_council .")
- **examples:** The examples for the current class (for example "32003E0897, Common Strategy 2003/897/CFSP of the European Council of 12 December 2003 amending Common Strategy 1999/877/CFSP on Ukraine in order to extend the period of its application , Stratégie commune 2003/897/PESC du Conseil européen du 12 décembre 2003 modifiant la stratégie commune 1999/877/PESC à l'égard de l'Ukraine afin de proroger sa période d'application, 32003E0897, Common Strategy 2003/897/CFSP of the European Council of 12 December 2003 amending Common Strategy 1999/877/CFSP on Ukraine in order to extend the period of its application , Stratégie commune 2003/897/PESC du Conseil européen du 12 décembre 2003 modifiant la stratégie commune 1999/877/PESC à l'égard de l'Ukraine afin de proroger sa période d'application")

3. Properties

- **propertyURI:** The URI of the property (for example http://publications.europa.eu/resources/authority/lam/md_SUSPEND_PAR)
- **types:** The URI of the type of the property (for example <http://www.w3.org/2004/02/skos/core#Concept>)
- **propertyCollections:** The URI(s) of the collection(s) that the property is part of (for example http://publications.europa.eu/resources/authority/lam/class_MSEA)
- **propertyCollectionLabels:** The label(s) of the collections that the property is part of (for example "Amendment to/Earlier related instruments")
- **propertyTypes:** The type(s) of the property (for example "object property")
- **skosDefinitions:** The SKOS definition(s) of the property (for example

"Partial suspension (SP) - similar as Suspension")

- **editorialNotes:** The editorial notes for the property (for example "08/11/2019: Differences between suspension and partial suspension? Is this really needed?")
- **examples:** The examples for the property (for example "<j.0:resource_legal_term-of-office rdf:datatype=\"http://www.w3.org/2001/XMLSchema#string\">VII (2020-2025)</j.0:resource_legal_term-of-office>")
- **historyNotes:** The history notes for the property (for example "Used by EUR-Lex quick search. Relevant for search in internal numbers for ECB, therefore this property is created in some ECB documents on purpose.")
- **scopeNotes:** The scope notes for the property (for example "32013R0298 → 32004R0314")
- **notations:** The notations for the property (for example "SUSPEND_PAR")
- **labels:** The labels for the property (for example "Link: Partially suspends document")

Appendices

References

- [1] D. Merkel. Docker: lightweight linux containers for consistent development and deployment. *Linux journal*, 2014(239):2, 2014.
- [2] Solomon Hykes. Docker, 2013. URL <http://www.docker.com>.