git rebase 成功之后如何撤销(*)

 Firm陈
 □ 已于 2022-07-21 11:12:15 修改
 ● 3391
 ♠ 收藏 5

 分类专栏:
 开发工具系列
 文章标签:
 git

 T发工具系列
 专栏收录该内容
 0 订阅
 25 篇文章
 订阅专栏

git rebase Q 过程中可以使用git --abort/--continue来进行操作,成功之后如何撤销呢?

首先执行git reflog查看本地记录

```
chengde@chengde-ThinkPad-T470p:~/workspace/src/vision algo$ git reflog
a3e5bed HEAD@{0}: checkout: moving from dev to chengde/add ds5ir
49a0e2d HEAD@{1}: checkout: moving from chengde/add ds5ir to dev
a3e5bed HEAD@{2}: rebase finished: returning to refs/heads/chengde/add ds5ir
a3e5bed HEAD@{3}: rebase: adjust ds5 ir data save file formate
2f0408c HEAD@{4}: rebase: add ds5 ir data getting example
9996bfe HEAD@{5}: rebase: compile samples:algo app success only
4128056 HEAD@{6}: rebase: ds5 depth ir image data getting api bugfix and workround
577ac8e HEAD@{7}: rebase: add right sample
49a0e2d HEAD@{8}: rebase: checkout dev
02a3260 HEAD@{9}: commit: adjust ds5 ir data save file formate
a05d84a HEAD@{10}: checkout: moving from chengde/add ir bak to chengde/add ds5ir
bf23698 HEAD@{11}: checkout: moving from chengde/add ds5ir to chengde/add ir bak
a05d84a HEAD@{12}: checkout: moving from chengde/add ir bak to chengde/add ds5ir
bf23698 HEAD@{13}: commit (amend): adjust ds5 ir data save file formate
60d4473 HEAD@{14}: commit (amend): adjust ds5 ir data save file formate
Obb8123 HEAD@{15}: commit (amend): adjust ds5 ir data save file formate
dde2287 HEAD@{16}: commit (amend): adjust ds5 ir data save file formate
5795ebl HEAD@{17}: commit: adjust ds5 ir data save file formate
11066d6 HEAD@{18}: checkout: moving from chengde/add ir debug to chengde/add ir bak
7de8187 HEAD@{19}: commit (amend): add ds5 ir data getting example
826da93 HEAD@{20}: commit (amend): add ds5 ir data getting example
a05d84a HEAD@{21}: checkout: moving from chengde/add ds5ir to chengde/add ir debug
a05d84a HEAD@{22}: checkout: moving from chengde/add ir debug to chengde/add ds5ir
36cc04 HEAD@{26}: commit: just for test to itustion of continente on itustion
```

可知本次rebase之前的id 为:

```
1 | 02a3260 HEAD@{9}: commit: adjust ds5 ir data save file formate
```

所以执行

git reset --hard 02a3260 即可

※ 文章知识点与官方知识档案匹配,可进一步学习相关知识

CS入门技能树〉Git入门〉版本管理 14861 人正在系统学习中