

LINUX SHELL PROGRAMMING

Operating System Lab

Introduction

2

- ❑ Many people says that Linux is a command based operating system.
- ❑ So many of us thinks that Linux is not so user friendly OS.
- ❑ But it is not true. Linux is a GUI based OS with a Shell which is more powerful than its counter part in Windows OS.
- ❑ We will be familiar with some shell commands.

Identity

3

- Type ***uname*** and Linux will tell his name to you

```
$ uname  
Linux
```

- If you want to know your name type ***whoami***

```
$ whoami  
user1  
$ who am i  
user1      tt3a      Jan 12 07:14  
$ who  
user1      tty3a     Jun 10 09:15  
user2      tty3c     Jun 10 09:25
```

Manual

4

- For each command Linux contains manual. To view the manual : ***man*** *name*
 - ▣ ***man*** *uname*

Creating Files

5

- There are two commands to create file.
 - ▣ *touch*
 - ▣ *cat*

```
$ touch sample  
$ touch sample1 sample2 sample3
```

- The size of the file would be zero bytes since *touch* doesn't allow to store anything in a file.
- Useful to create several empty files quickly.

Creating Files (Cont.)

6

- Store lines in a file

```
$ cat > test  
Hello world  
I love my country
```

- After completion of writing press the keys ***ctrl+d***.
- In Unix the keys ***ctrl+d*** indicate the EOF or end of file character.

Creating Files (Cont.)

7

- To see the contents of the file test

```
$ cat test  
Hello world  
I love my country
```

- It can concatenate the contents of two files and store them in the third file.

```
$ cat sample1 sample2 > newsample
```

- This would create newsample which contains contents of sample1 followed by that of sample2.

```
$ cat sample1 sample2 >> newsample
```

File Operations

8

- To copy a file : **cp**
 - ▣ Copy source to destination or multiple sources to directory
 - ▣ **-i** [prompt before overwrite]
 - ▣ **-r** [copy directories recursively]
 - ▣ **-u** [copy only when the src file is newer than the dest file or when the dest file is missing]

```
$ cp /usr/home/chapter1 /usr/newhome/ch1
```


File Operations (Cont.)

9

- ❑ To remove a file or directory : **rm**
 - ❑ **-f** [ignore nonexistent files, never prompt]
 - ❑ **-i** [prompt before any removal]
 - ❑ **-r** [remove the contents of directories recursively]
 - ❑ **-v** [explain what is being done]

```
$ rm -i /usr/home/chapter1
```

```
$ rm -r home
```

File Operations (Cont.)

10

- To move or rename a file : **mv**
 - ▣ rename src to dest or move src(s) to directory
 - ▣ **-i** [prompt before overwrite]
 - ▣ **-u** [move only when the src file is newer than the dest file or when the dest file is missing]
 - ▣ **-v** [explain what is being done]

```
$ mv olddir newdir  
$ mv file1 file2 newdir
```

Directory and File Listings

11

- ❑ To list information about directory or files : **ls**
- ❑ This command contains some options.
 - ❑ -a [do not hide entries starting with .]
 - ❑ -A [do not list implied . and ..]
 - ❑ -h [print sizes in human readable format]
 - ❑ -l [use a long listing format]
 - ❑ -S [sort by file size]

Directory and File Listings (Cont.)

12

- Any file name which begins with a '.' is treated as a hidden file.

```
$ ls -a  
.  
..  
Home1  
Dev0  
Sample1
```

- . stands for the current directory.
- .. stands for the parent previous directory.

Directory and File Listings (Cont.)

13

```
$ ls p*
```

pakde

pommies

```
$ ls ?ain
```

gain

main

Pain

```
$ ls /mydir/*x
```

cc_fax

i_tax

myUnix

```
$ ls [aeiou]*
```

area

even

ion

```
$ ls [!aeiou]*
```

dell

sam

```
$ ls [a-m][c-z][4-9]??
```

az6ps

Directory and File Listings (Cont.)

14

```
$ ls -l
```

```
total 22
```

-rwxr-x--x	1	user1	group	24 Jun 06 10:12	carribeans
-rwxr-x-wx	1	user1	group	23 Jun 06 00:05	kangaroos
-rwxr-xr-x	1	user1	group	12 Jun 06 12:54	kiwis
drwxr-xr-x	1	user1	group	10 Jun 06 11:09	mydir
-rwxr-xrwx	2	user1	group	22 Jun 06 14:04	pakde
-rwxrwxr-x	2	user1	group	16 Jun 06 22:25	pommies
-rwxr-xr-x	1	user1	group	04 Jun 06 23:16	springboks
-rwxr-xr-x	1	user1	group	04 Jun 06 10:17	zulus

Directory and File Listings (Cont.)

15

File Type	Meaning
-	Ordinary file
d	Directory file
c	Character special file
b	Block special file
l	Symbolic link
s	Semaphore
p	Named pipe
m	Shared memory file

Directory and File Listings (Cont.)

16

- To create Link

```
$ ln poem mypoem
```

- Avoids unnecessary duplication of the same file contents in different directories.
- By default any new file that we create has one link whereas any new directory we create has two links.

Directory and File Permissions

17

- Each file or directory has 3 security groups.
 - ▣ Owner
 - ▣ Group
 - ▣ All Others
- Each security group has 3 flags that control the access status : read, write, execute
- They are listed as 'rwx' or a "-" if the access is turned off.
 - ▣ rwxrwxrwx[read, write and executable for owner, group and all others]
 - ▣ rw-r--r--[read and write by owner, read only for group and all others]

Directory and File Permissions (Cont.)

18

- ❑ To change the permissions type chmod
 - ❑ u, g, o or all [whose permission you are changing]
- ❑ + or - [type of change: add or subtract permission]
- ❑ combination of r, w or x [which permission you are changing: read, write or execute]
- ❑ To change Permission
 - ❑ chmod [who] [+/-/=] [permissions] file

Directory and File Listings (Cont.)

19

- file or directory [name of file or directory to change]
 - ▣ `chmod go+rw file1 file2` add read and write access for group and others for files 'file1' and 'file2'
 - ▣ `chmod a+rw file1` add read, write and execute for everyone for 'file1'.
 - ▣ `chmod 555 file1`

```
$ chmod go-x myfile  
$ chmod go+r,go-w myfile  
$ chmod go=r,u=rw myfile  
$ chmod +w myfile  
$ chmod 744 myfile
```

A Bit of Mathematics

20

- ❑ Calculator is invoked at shell prompt by typing **bc**.
- ❑ The input to the calculator is taken line by line.
- ❑ By typing **bc** at prompt the calculator mode starts and the \$ the prompt disappears.
- ❑ Typing quit ends tryst with bc.

```
$ bc
10/2*2
10
2.5*2.5+2
8.25
quit
```

A Bit of Mathematics (Cont.)

21

- Working with floats

```
$ bc
scale = 1
22/7
3.1
2.25+1
3.35
quit
```

- After Setting the scale variable if the answer of an expression turns out more than what scale can provide then the value in scale is ignored and the correct answer is displayed.

A Bit of Mathematics (Cont.)

22

- Working with different base

```
$ bc
obase=16
ibase=2
11010011
89275
1000+100
C
quit
```

- By setting the variable `ibase` to 2 and `obase` to 16 all input that is supplied is taken as binary whereas all output is displayed in hexadecimal.

A Bit of Mathematics (Cont.)

23

- Working with functions

```
$ bc
Sqrt(196)
14
$ bc -l
s(3.14)
0
quit
```

- Trigonometric functions expect their arguments in radians and not in degrees.

A Bit of Mathematics (Cont.)

24

- Working with variables

```
$ bc
a=4
b=5
c=b-a
c
1
quit
```

```
$ bc
for(i=1 ; i<=5 ; i++) i
1
2
3
4
5
quit
```

```
$ bc
4+2
6
.+1
7
quit
```


A Bit of Mathematics (Cont.)

25

- Another math related command in Unix: ***factor***
- If a positive number less than 2^{46} is types in then it factorise the number and print its prime factors. Each one is printed the proper number of times.

```
$ factor 15
15: 3 5
$ factor
15
15: 3 5
28
28: 2 2 7
to quit: ctrl+d or q
```

A Bit of Mathematics (Cont.)

26

- Another math related command in Unix: ***factor***
- If a positive number less than 2^{46} is types in then it factorize the number and print its prime factors. Each one is printed the proper number of times.

```
$ factor 15
15: 3 5
$ factor
15
15: 3 5
28
28: 2 2 7
to quit: ctrl+d or q
```

Redirection

27

- **Input redirection:**

- `<` -get input from file instead of the keyboard

- **Output redirection:**

- `>` -send output to file instead of the terminal window

- **Append output:**

- `>>` -command is used to append to a file if it already exists

Redirection (Cont.)

28

□ Example:

```
$ ls -l > note.txt
```

Calender

29

- To view calendar in the shell: ***cal***

```
$ cal  
$ cal 2012  
$ cal January 2101  
$ cal 2 1997  
$ cal feb 2001  
$ cal sep 1752
```

File Viewing

- To output the first lines of files : *head file1 file2 file3 ...*
- Print the first 10 lines of each file to standard output
- With more than one file , precede each with a header giving the file name
 - *-n* [output the last n lines, instead of the last 10]

File Viewing

- To output the last lines of files : ***tail file1 file2 file3 ...***
- Print the last 10 lines of each file to standard output
- With more than one file, precede each with a header giving the file name
 - **-n** [output the last n lines, instead of the last 10]

File Viewing

- To sort lines of a text files : ***sort file1 file2 file3...***
- Write sorted concatenation of all file(s) to standard output.

File Viewing

- To print the number of lines, words and bytes in files :
wc file1 file2 file3 ...
- print byte, word, and newline counts for each file and a total line if more than one file is specified.
 - **-l** [print the newline counts]
 - **-w** [print the word counts]

Piping

- The input of a command may come from the output of another command.
- This is accomplished with the `|` pipe operator.
- **How to view the lines 15-20 of a file named `a.txt` ?**

Piping

- The input of a command may come from the output of another command.
- This is accomplished with the `|` pipe operator.
- How to view the lines 15-20 of a file named `a.txt`?
 - *head -20 a.txt | tail -5*

Grep

- grep matches a pattern in a given a list of files or standard input and outputs only the matching lines.
 - ***grep*** pattern filename
 - ***grep abc file.txt***
- grep patterns are case sensitive by default.
- Some options
 - ***-i*** [case insensitive search]
 - ***-c*** [count of total matches]
 - ***-E*** [regular expressions can be provided as patterns]
 - ***-n*** [display the line numbers of the matched lines]

Find

- search for files in a directory hierarchy.
- By default, find returns all files below the current working directory.
 - *find*
- To search a pattern : *find -name '*txt*'*
- To search for a file type :
 - *find -type d* [find all directories]
 - *find -type f* [find all regular files]
- Find executes the '*-print*' action by default. To change it to style such as '*ls*' : *find -type f -ls*

Find

- To search all the directories
 - not recommended
 - ***find / -name "myfile" -type f***
- To search a specific directory
 - ***find /home/dir1 -name "myfile" -type f***
- To search multiple directories
 - ***find dir1 dir2 -name "myfile" -type f***
- To Search for all files owned by a user
 - ***find -user userid***
- To take an action
 - ***find -type f -name '*ch*' -exec chmod a+rwx {} \;***
 - {} is replaced with the name of the file
 - The ; indicates the end of the command.

Thanks