

A transfer of data from operational database to a data warehouse database when all repairs on a given vehicle are completed and value of attribute `status` is 'completed' in all rows representing the mechanics that belong to a team involved in the repair.

- (1) In the first step, if the new mechanics are involved in a repair team then information about such mechanics is copied from `MECHANIC` table in an operational database into `MECHANIC` table into a data warehouse database. A new value of `mechanic-key` is automatically generated for each new row in `MECHANIC` table in a data warehouse database.
- (2) Next, if a new repair team was formed then information about a new repair team is transferred from `MECHANIC` table in an operational database to `REPAIR TEAM` table in a data warehouse database. The total number of mechanics that belong to a repair team is counted in `MECHANIC` table in an operational database and value of `team-key` is automatically generated. Then a single row is inserted into `REPAIR TEAM` table in a data warehouse database.
- (3) In the next step, information about a phone number of an owner is retrieved from `OWNER` table in an operational database. If a retrieved phone number already exists in `CUSTOMER` table in a data warehouse database then there is no need to add information about a new customer. Otherwise, information about a new owner of repaired vehicle is copied from `OWNER` table in an operational database to `CUSTOMER` table in a data warehouse database. Information about owner's phone number is selected from the tables `MECHANIC` and `VEHICLE` located an operational database. A vehicle registration number is taken from `MECHANIC` table in an operational database and used to find owner's phone number in `VEHICLE` table in an operational database. A value of `owner-key` in `CUSTOMER` table in a data warehouse database is automatically generated.
- (4) In the next step, information about vehicle registration number is retrieved from `MECHANIC` table in an operational database. If a retrieved registration number already exists in `VEHICLE` table in a data warehouse database then there is no need to add information about a new vehicle. Otherwise information about a new vehicle is copied from `VEHICLE` table in an operational database into `VEHICLE` table in a data warehouse database. A value of `vehicle-key` in `VEHICLE` table in a data warehouse database is automatically generated.
- (5) Finally, it is possible to add a new row to `REPAIR` table in a data warehouse database. The values of the attributes: `owner-key`, `vehicle-key` and `team-key` are available from the previous steps. A value of an attribute `when-started` is taken from `MECHANIC` table in an operational database. A value of an attribute `when-completed` is equal to the current date and time. The values of the attributes `total-costs`, `total-time` and `total-parts` are calculated from the contents of an operational database.

---