

Lecture 8:


Training Neural Networks,

Part 2

Last time: Activation Functions


Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$



tanh


$$\tanh(x)$$



ReLU


$$\max(0, x)$$

Good default choice



Leaky ReLU

$$\max(0.1x, x)$$




Maxout


$$\max(w_1^T x + b_1, w_2^T x + b_2)$$

ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$




Last time: Weight Initialization



Initialization too small:

Activations go to zero, gradients also zero,


No learning =(



Initialization too big:

Activations saturate (for tanh),


Gradients zero, no learning =(



Initialization just right:

Nice distribution of activations at all layers,
Learning proceeds nicely =)

Last time: Data Preprocessing



Last Time: Batch Normalization

[Ioffe and Szegedy, 2015]

Input: $x : N \times D$

Learnable scale and shift parameters:

$$\gamma, \beta : D$$

Learning $\gamma = \sigma$,
 $\beta = \mu$ will recover the
identity function!

$$\mu_j = \frac{1}{N} \sum_{i=1}^N x_{i,j}$$

Per-channel mean,
shape is D

$$\sigma_j^2 = \frac{1}{N} \sum_{i=1}^N (x_{i,j} - \mu_j)^2$$

Per-channel var,
shape is D

$$\hat{x}_{i,j} = \frac{x_{i,j} - \mu_j}{\sqrt{\sigma_j^2 + \epsilon}}$$

Normalized x,
Shape is N x D

$$y_{i,j} = \gamma_j \hat{x}_{i,j} + \beta_j$$

Output,
Shape is N x D

Today

- Improve your training error:
 - (Fancier) Optimizers
 - Learning rate schedules
- Improve your test error:
 - Regularization
 - Choosing Hyperparameters

Optimization


```
# Vanilla Gradient Descent
```

```
while True:
```

```
    weights_grad = evaluate_gradient(loss_fun, data, weights)
```

```
    weights += - step_size * weights_grad # perform parameter update
```

may have many problems in practice.




Optimization: Problems with SGD

What if loss changes quickly in one direction and slowly in another?

What does gradient descent do?

The intuitive idea is that the loss landscape looks like a taco shell. It's sort of very sensitive in one direction, and not sensitive in the other direction.




Loss function has high **condition number**: ratio of largest to smallest singular value of the Hessian matrix is large

Optimization: Problems with SGD

What if loss changes quickly in one direction and slowly in another?

What does gradient descent do?


Very slow progress along shallow dimension, jitter along steep direction



Loss function has high **condition number**: ratio of largest to smallest singular value of the Hessian matrix is large

Optimization: Problems with SGD


What if the loss function has a **local minima** or **saddle point**?



Optimization: Problems with SGD

What if the loss function has a **local minima** or **saddle point**?

Zero gradient,
gradient descent
gets stuck



Optimization: Problems with SGD


What if the loss function has a **local minima** or **saddle point**?

Saddle points much more common in high dimension

Saddle point means at my current point, some directions the loss goes up, and some directions goes down. That's probably going to happen everywhere in high dimensions.

A local minima say that of all those directions that I can move, every one of them causes the loss to go up. In fact that seems pretty rare in very high dimension problem.

gradient nears 0.




Dauphin et al, "Identifying and attacking the saddle point problem in high-dimensional non-convex optimization", NIPS 2014

Optimization: Problems with SGD

Our gradients come from minibatches so they can be noisy!

$$L(W) = \frac{1}{N} \sum_{i=1}^N L_i(x_i, y_i, W)$$

$$\nabla_W L(W) = \frac{1}{N} \sum_{i=1}^N \nabla_W L_i(x_i, y_i, W)$$



SGD + Momentum

There's a really, really simple strategy, the idea of adding a momentum term to our stochastic gradient descent.

SGD

$$x_{t+1} = x_t - \alpha \nabla f(x_t)$$

```
while True:
    dx = compute_gradient(x)
    x -= learning_rate * dx
```

The idea is that we maintain a velocity over time, and we add our gradient estimates to the velocity. Then we step in the direction of the velocity, rather than stepping in the direction of the gradient.

- Build up “velocity” as a running mean of gradients
- Rho gives “friction”; typically rho=0.9 or 0.99

SGD+Momentum

$$v_{t+1} = \rho v_t + \nabla f(x_t)$$

$$x_{t+1} = x_t - \alpha v_{t+1}$$

```
vx = 0
while True:
    dx = compute_gradient(x)
    vx = rho * vx + dx
    x -= learning_rate * vx
```

Sutskever et al, “On the importance of initialization and momentum in deep learning”, ICML 2013


SGD + Momentum

Local Minima

Saddle points




Poor Conditioning



Gradient Noise

imagine the ball rolling down the hill, picking up speed as it comes down. when the ball pass the point of local minima, the point still has velocity even though it doesn't have gradient. The noise is averaged out.



— SGD

— SGD+Momentum

SGD + Momentum

kind of similar idea in TD learning

SGD+Momentum

$$v_{t+1} = \rho v_t - \alpha \nabla f(x_t)$$

$$x_{t+1} = x_t + v_{t+1}$$

```
vx = 0
while True:
    dx = compute_gradient(x)
    vx = rho * vx - learning_rate * dx
    x += vx
```

SGD+Momentum

$$v_{t+1} = \rho v_t + \nabla f(x_t)$$

$$x_{t+1} = x_t - \alpha v_{t+1}$$

```
vx = 0
while True:
    dx = compute_gradient(x)
    vx = rho * vx + dx
    x -= learning_rate * vx
```


You may see SGD+Momentum formulated different ways,
but they are equivalent - give same sequence of x

Sutskever et al, "On the importance of initialization and momentum in deep learning", ICML 2013

Nesterov Momentum


the difference is at which point you calculate gradient(red)

Momentum update:



Combine gradient at current point with velocity to get step used to update weights

Nesterov Momentum



“Look ahead” to the point where updating using velocity would take us; compute gradient there and mix it with velocity to get actual update direction

Nesterov, “A method of solving a convex programming problem with convergence rate $O(1/k^2)$ ”, 1983
Nesterov, “Introductory lectures on convex optimization: a basic course”, 2004
Sutskever et al, “On the importance of initialization and momentum in deep learning”, ICML 2013


Nesterov Momentum

$$v_{t+1} = \rho v_t - \alpha \nabla f(x_t + \rho v_t)$$
$$x_{t+1} = x_t + v_{t+1}$$

Change of variables $\tilde{x}_t = x_t + \rho v_t$ and rearrange:


$$v_{t+1} = \rho v_t - \alpha \nabla f(\tilde{x}_t)$$
$$\tilde{x}_{t+1} = \tilde{x}_t - \rho v_t + (1 + \rho)v_{t+1}$$
$$= \tilde{x}_t + v_{t+1} + \rho(v_{t+1} - v_t)$$

Annoying, usually we want update in terms of $x_t, \nabla f(x_t)$



“Look ahead” to the point where updating using velocity would take us; compute gradient there and mix it with velocity to get actual update direction

Nesterov Momentum



- SGD
- SGD+Momentum
- Nesterov

AdaGrad

```
grad_squared = 0
while True:
    dx = compute_gradient(x)
    grad_squared += dx * dx
    x -= learning_rate * dx / (np.sqrt(grad_squared) + 1e-7)
```

You're going to keep a running estimate, or a running sum of all the squared gradients that you see during training. Now rather than having a velocity term, instead we have this grad squared term, and during training, we're going to just keep adding the squared gradients to this grad squared term.


Added element-wise scaling of the gradient based on the historical sum of squares in each dimension

“Per-parameter learning rates”
or “adaptive learning rates”

Duchi et al, “Adaptive subgradient methods for online learning and stochastic optimization”, JMLR 2011

AdaGrad

```
grad_squared = 0
while True:
    dx = compute_gradient(x)
    grad_squared += dx * dx
    x -= learning_rate * dx / (np.sqrt(grad_squared) + 1e-7)
```




Q: What happens with AdaGrad?

Progress along “steep” directions is damped;
progress along “flat” directions is accelerated

AdaGrad

```
grad_squared = 0
while True:
    dx = compute_gradient(x)
    grad_squared += dx * dx
    x -= learning_rate * dx / (np.sqrt(grad_squared) + 1e-7)
```



Q2: What happens to the step size over long time? Decays to zero

RMSProp: “Leaky AdaGrad”

AdaGrad

```
grad_squared = 0
while True:
    dx = compute_gradient(x)
    grad_squared += dx * dx
    x -= learning_rate * dx / (np.sqrt(grad_squared) + 1e-7)
```




RMSProp

```
grad_squared = 0
while True:
    dx = compute_gradient(x)
    grad_squared = decay_rate * grad_squared + (1 - decay_rate) * dx * dx
    x -= learning_rate * dx / (np.sqrt(grad_squared) + 1e-7)
```

Tieleman and Hinton, 2012

RMSProp



- SGD
- SGD+Momentum
- RMSProp
- AdaGrad
(stuck due to decaying lr)

in general, we tend not to use AdaGrad so much when training NN.

Adam (almost)

why not combine the ideas in Momentum and RMPPProp ?

```
first_moment = 0
second_moment = 0
while True:
    dx = compute_gradient(x)
    first_moment = beta1 * first_moment + (1 - beta1) * dx
    second_moment = beta2 * second_moment + (1 - beta2) * dx * dx
    x -= learning_rate * first_moment / (np.sqrt(second_moment) + 1e-7))
```

Kingma and Ba, "Adam: A method for stochastic optimization", ICLR 2015

Adam (almost)

```
first_moment = 0
second_moment = 0
while True:
    dx = compute_gradient(x)
    first_moment = beta1 * first_moment + (1 - beta1) * dx
    second_moment = beta2 * second_moment + (1 - beta2) * dx * dx
    x -= learning_rate * first_moment / (np.sqrt(second_moment) + 1e-7))
```

Momentum

AdaGrad / RMSProp

Sort of like RMSProp with momentum

Q: What happens at first timestep?

second_moment is very close to zero, and normally
we make a very very large step at the beginning.

Kingma and Ba, "Adam: A method for stochastic optimization", ICLR 2015

Adam (full form)

```
first_moment = 0
second_moment = 0
for t in range(1, num_iterations):
    dx = compute_gradient(x)
    first_moment = beta1 * first_moment + (1 - beta1) * dx
    second_moment = beta2 * second_moment + (1 - beta2) * dx * dx
    first_unbias = first_moment / (1 - beta1 ** t)
    second_unbias = second_moment / (1 - beta2 ** t)
    x -= learning_rate * first_unbias / (np.sqrt(second_unbias) + 1e-7))
```

Momentum

Bias correction

AdaGrad / RMSProp

Bias correction for the fact that
first and second moment
estimates start at zero

Kingma and Ba, "Adam: A method for stochastic optimization", ICLR 2015

Adam (full form)

```
first_moment = 0
second_moment = 0
for t in range(1, num_iterations):
    dx = compute_gradient(x)
    first_moment = beta1 * first_moment + (1 - beta1) * dx
    second_moment = beta2 * second_moment + (1 - beta2) * dx * dx
    first_unbias = first_moment / (1 - beta1 ** t)
    second_unbias = second_moment / (1 - beta2 ** t)
    x -= learning_rate * first_unbias / (np.sqrt(second_unbias) + 1e-7))
```

Momentum

Bias correction


AdaGrad / RMSProp

Bias correction for the fact that first and second moment estimates start at zero

Adam with $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\text{learning_rate} = 1e-3$ or $5e-4$ is a great starting point for many models!

Kingma and Ba, "Adam: A method for stochastic optimization", ICLR 2015


Adam



- SGD
- SGD+Momentum
- RMSProp
- Adam


Learning rate schedules

SGD, SGD+Momentum, Adagrad, RMSProp, Adam all have **learning rate** as a hyperparameter.



Q: Which one of these learning rates is best to use?


SGD, SGD+Momentum, Adagrad, RMSProp, Adam all have **learning rate** as a hyperparameter.



Q: Which one of these learning rates is best to use?

A: All of them! Start with large learning rate and decay over time


Learning Rate Decay



Step: Reduce learning rate at a few fixed points. E.g. for ResNets, multiply LR by 0.1 after epochs 30, 60, and 90.

What you do for setting learning rate decay is try with no decay, see what happens. Then kind of eyeball the loss curve and see where you think you might need decay.

Learning Rate Decay



Step: Reduce learning rate at a few fixed points. E.g. for ResNets, multiply LR by 0.1 after epochs 30, 60, and 90.

Cosine: $\alpha_t = \frac{1}{2}\alpha_0 (1 + \cos(t\pi/T))$


α_0 : Initial learning rate

α_t : Learning rate at epoch t

T : Total number of epochs

Loshchilov and Hutter, “SGDR: Stochastic Gradient Descent with Warm Restarts”, ICLR 2017
Radford et al, “Improving Language Understanding by Generative Pre-Training”, 2018
Feichtenhofer et al, “SlowFast Networks for Video Recognition”, arXiv 2018
Child et al, “Generating Long Sequences with Sparse Transformers”, arXiv 2019

Learning Rate Decay




Step: Reduce learning rate at a few fixed points. E.g. for ResNets, multiply LR by 0.1 after epochs 30, 60, and 90.

Cosine: $\alpha_t = \frac{1}{2}\alpha_0 (1 + \cos(t\pi/T))$

α_0 : Initial learning rate
 α_t : Learning rate at epoch t
 T : Total number of epochs

Loshchilov and Hutter, “SGDR: Stochastic Gradient Descent with Warm Restarts”, ICLR 2017
Radford et al, “Improving Language Understanding by Generative Pre-Training”, 2018
Feichtenhofer et al, “SlowFast Networks for Video Recognition”, arXiv 2018
Child et al, “Generating Long Sequences with Sparse Transformers”, arXiv 2019

Learning Rate Decay



Step: Reduce learning rate at a few fixed points. E.g. for ResNets, multiply LR by 0.1 after epochs 30, 60, and 90.

Cosine: $\alpha_t = \frac{1}{2}\alpha_0 (1 + \cos(t\pi/T))$

Linear: $\alpha_t = \alpha_0(1 - t/T)$


α_0 : Initial learning rate

α_t : Learning rate at epoch t

T : Total number of epochs

Devlin et al, "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding", 2018

Learning Rate Decay



Step: Reduce learning rate at a few fixed points. E.g. for ResNets, multiply LR by 0.1 after epochs 30, 60, and 90.

Cosine: $\alpha_t = \frac{1}{2}\alpha_0 (1 + \cos(t\pi/T))$

Linear: $\alpha_t = \alpha_0(1 - t/T)$

Inverse sqrt: $\alpha_t = \alpha_0/\sqrt{t}$


α_0 : Initial learning rate

α_t : Learning rate at epoch t

T : Total number of epochs

Vaswani et al, "Attention is all you need", NIPS 2017

Learning Rate Decay: Linear Warmup



High initial learning rates can make loss explode; linearly increasing learning rate from 0 over the first ~5000 iterations can prevent this


Empirical rule of thumb: If you increase the batch size by N , also scale the initial learning rate by N

Goyal et al, "Accurate, Large Minibatch SGD: Training ImageNet in 1 Hour", arXiv 2017

First-Order Optimization

- (1) Use gradient form linear approximation
- (2) Step to minimize the approximation


kind of a first-order Taylor approximation, so we can't step too far in that direction.



Second-Order Optimization

Hessian matrix: a matrix of second derivatives

- (1) Use gradient **and Hessian** to form **quadratic** approximation
- (2) Step to the **minima** of the approximation



Second-Order Optimization

second-order Taylor expansion:

$$J(\boldsymbol{\theta}) \approx J(\boldsymbol{\theta}_0) + (\boldsymbol{\theta} - \boldsymbol{\theta}_0)^\top \nabla_{\boldsymbol{\theta}} J(\boldsymbol{\theta}_0) + \frac{1}{2} (\boldsymbol{\theta} - \boldsymbol{\theta}_0)^\top \mathbf{H} (\boldsymbol{\theta} - \boldsymbol{\theta}_0)$$

Solving for the critical point we obtain the Newton parameter update:

$$\boldsymbol{\theta}^* = \boldsymbol{\theta}_0 - \mathbf{H}^{-1} \nabla_{\boldsymbol{\theta}} J(\boldsymbol{\theta}_0)$$

good: doesn't have a learning rate.

Q: Why is this bad for deep learning?

Second-Order Optimization

second-order Taylor expansion:

$$J(\boldsymbol{\theta}) \approx J(\boldsymbol{\theta}_0) + (\boldsymbol{\theta} - \boldsymbol{\theta}_0)^\top \nabla_{\boldsymbol{\theta}} J(\boldsymbol{\theta}_0) + \frac{1}{2} (\boldsymbol{\theta} - \boldsymbol{\theta}_0)^\top \mathbf{H} (\boldsymbol{\theta} - \boldsymbol{\theta}_0)$$

Solving for the critical point we obtain the Newton parameter update:

$$\boldsymbol{\theta}^* = \boldsymbol{\theta}_0 - \mathbf{H}^{-1} \nabla_{\boldsymbol{\theta}} J(\boldsymbol{\theta}_0)$$

Hessian has $O(N^2)$ elements
Inverting takes $O(N^3)$
 N = (Tens or Hundreds of) Millions

Q: Why is this bad for deep learning? impractical in deep learning.

Second-Order Optimization

$$\theta^* = \theta_0 - H^{-1} \nabla_{\theta} J(\theta_0)$$

- Quasi-Newton methods (**BGFS** most popular):
instead of inverting the Hessian ($O(n^3)$), approximate inverse Hessian with rank 1 updates over time ($O(n^2)$ each).
- **L-BFGS** (Limited memory BFGS):
Does not form/store the full inverse Hessian.

L-BFGS

- **Usually works very well in full batch, deterministic mode** i.e. if you have a single, deterministic $f(x)$ then L-BFGS will probably work very nicely
- **Does not transfer very well to mini-batch setting.** Gives bad results. Adapting second-order methods to large-scale, stochastic setting is an active area of research.

Le et al, "On optimization methods for deep learning, ICML 2011"


Ba et al, "Distributed second-order optimization using Kronecker-factored approximations", ICLR 2017

In practice:


- **Adam** is a good default choice in many cases; it often works ok even with constant learning rate
- **SGD+Momentum** can outperform Adam but may require more tuning of LR and schedule
 - Try cosine schedule, very few hyperparameters!
- If you can afford to do full batch updates then try out **L-BFGS** (and don't forget to disable all sources of noise)

Improve test error

Beyond Training Error




Better optimization algorithms
help reduce training loss



But we really care about error on
new data - how to reduce the gap?

Early Stopping: Always do this



Stop training the model when accuracy on the validation set decreases
Or train for a long time, but always keep track of the model snapshot
that worked best on val


Model Ensembles

1. Train multiple independent models
2. At test time average their results

(Take average of predicted probability distributions, then choose argmax)

Enjoy 2% extra performance

How to improve single-model performance?



Regularization

Regularization: Add term to loss

$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1) + \boxed{\lambda R(W)}$$

In common use:

L2 regularization

$$R(W) = \sum_k \sum_l W_{k,l}^2 \quad (\text{Weight decay})$$

L1 regularization

$$R(W) = \sum_k \sum_l |W_{k,l}|$$

Elastic net (L1 + L2)



$$R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$$

Regularization: Dropout

It's more common in fully connected layers, but you sometimes see this in convolutional layers, as well.

In each forward pass, randomly set some neurons to zero

Probability of dropping is a hyperparameter; 0.5 is common



Srivastava et al, "Dropout: A simple way to prevent neural networks from overfitting", JMLR 2014

Regularization: Dropout

```
p = 0.5 # probability of keeping a unit active. higher = less dropout
```

```
def train_step(X):
```

```
    """ X contains the data """
```

```
    # forward pass for example 3-layer neural network
```

```
    H1 = np.maximum(0, np.dot(W1, X) + b1)
```

```
    U1 = np.random.rand(*H1.shape) < p # first dropout mask
```

```
    H1 *= U1 # drop!
```

```
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
```

```
    U2 = np.random.rand(*H2.shape) < p # second dropout mask
```


```
    H2 *= U2 # drop!
```

```
    out = np.dot(W3, H2) + b3
```

```
    # backward pass: compute gradients... (not shown)
```

```
    # perform parameter update... (not shown)
```

Example forward
pass with a
3-layer network
using dropout




Regularization: Dropout

How can this possibly be a good idea?

for classifying cats, the network might learn that one neuron for having a ear, one neuron for having a tail, one neuron for being furry, and then it can combine these things together to decide whether or not it's a cat.

Forces the network to have a redundant representation;
Prevents co-adaptation of features




But now if we have drop out, then in making the final decision about catness, the network cannot depend too much on any of these features. Instead, it kind of needs to distribute its idea of catness across many different features. This might help prevent overfitting somehow.

Regularization: Dropout

How can this possibly be a good idea?

after you apply dropout, we're kind of computing this subnetwork using some subset of the neurons. Now every different potential dropout mask leads to a different potential subnetwork. Now dropout is kind of learning a whole ensemble of networks all at the same time that all share parameters.



Dropout is training a large **ensemble** of models (that share parameters).

Each binary mask is one model
by the way, you're never gonna sample all the things

An FC layer with 4096 units has
 $2^{4096} \sim 10^{1233}$ possible masks!

Only $\sim 10^{82}$ atoms in the universe...

Dropout: Test time

Q: what happens at test time ?

Dropout makes our output random!

$$\begin{array}{c} \text{Output} \\ \text{(label)} \end{array} \quad \boxed{y} = f_W \left(\begin{array}{c} \text{Input} \\ \text{(image)} \end{array} \quad \boxed{x}, \begin{array}{c} \boxed{z} \\ \text{Random} \\ \text{mask} \end{array} \right)$$

Previously, we've had our neural network, $y = f_w(x)$. But now our network is also taking this additional input z , which is some like random dropout mask. Having randomness at test time is maybe bad.

Want to “average out” the randomness at test-time

$$y = f(x) = E_z[f(x, z)] = \int p(z) f(x, z) dz$$


But this integral seems hard ...

Dropout: Test time

Want to approximate the integral

$$y = f(x) = E_z [f(x, z)] = \int p(z) f(x, z) dz$$

Consider a single neuron.



At test time we have: $E[a] = w_1x + w_2y$

During training we have:
$$\begin{aligned} E[a] &= \frac{1}{4}(w_1x + w_2y) + \frac{1}{4}(w_1x + 0y) \\ &\quad + \frac{1}{4}(0x + 0y) + \frac{1}{4}(0x + w_2y) \\ &= \frac{1}{2}(w_1x + w_2y) \end{aligned}$$

**At test time, multiply
by dropout probability**

Dropout: Test time

```
def predict(X):  
    # ensembled forward pass  
    H1 = np.maximum(0, np.dot(W1, X) + b1) * p # NOTE: scale the activations  
    H2 = np.maximum(0, np.dot(W2, H1) + b2) * p # NOTE: scale the activations  
    out = np.dot(W3, H2) + b3
```

At test time all neurons are active always

=> We must scale the activations so that for each neuron:

output at test time = expected output at training time

Dropout Summary

```
""" Vanilla Dropout: Not recommended implementation (see notes below) """
```

```
p = 0.5 # probability of keeping a unit active. higher = less dropout
```

```
def train_step(X):
```

```
    """ X contains the data """
```

```
    # forward pass for example 3-layer neural network
```

```
    H1 = np.maximum(0, np.dot(W1, X) + b1)
```

```
    U1 = np.random.rand(*H1.shape) < p # first dropout mask
```

```
    H1 *= U1 # drop!
```

```
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
```

```
    U2 = np.random.rand(*H2.shape) < p # second dropout mask
```

```
    H2 *= U2 # drop!
```

```
    out = np.dot(W3, H2) + b3
```

```
    # backward pass: compute gradients... (not shown)
```

```
    # perform parameter update... (not shown)
```

```
def predict(X):
```

```
    # ensembled forward pass
```

```
    H1 = np.maximum(0, np.dot(W1, X) + b1) * p # NOTE: scale the activations
```

```
    H2 = np.maximum(0, np.dot(W2, H1) + b2) * p # NOTE: scale the activations
```

```
    out = np.dot(W3, H2) + b3
```

drop in train time

scale at test time

More common: “Inverted dropout”

```
p = 0.5 # probability of keeping a unit active. higher = less dropout

def train_step(X):
    # forward pass for example 3-layer neural network
    H1 = np.maximum(0, np.dot(W1, X) + b1)
    U1 = (np.random.rand(*H1.shape) < p) / p # first dropout mask. Notice /p!
    H1 *= U1 # drop!
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
    U2 = (np.random.rand(*H2.shape) < p) / p # second dropout mask. Notice /p!
    H2 *= U2 # drop!
    out = np.dot(W3, H2) + b3

    # backward pass: compute gradients... (not shown)
    # perform parameter update... (not shown)

def predict(X):
    # ensembled forward pass
    H1 = np.maximum(0, np.dot(W1, X) + b1) # no scaling necessary
    H2 = np.maximum(0, np.dot(W2, H1) + b2)
    out = np.dot(W3, H2) + b3
```

test time is unchanged!



Regularization: A common pattern

Training: Add some kind of randomness

$$y = f_W(x, z)$$

actually, when you train networks with batch normalization, sometimes you don't need dropout at all.

Testing: Average out randomness (sometimes approximate)

$$y = f(x) = E_z[f(x, z)] = \int p(z)f(x, z)dz$$


But dropout is somewhat nice because you can tune the regularization strength by varying the parameter p .

Example: Batch Normalization


Training:
Normalize using stats from random minibatches

Testing: Use fixed stats to normalize

Regularization: Data Augmentation



Regularization: Data Augmentation



Data Augmentation

Horizontal Flips



Data Augmentation

Random crops and scales

Training: sample random crops / scales


ResNet:

1. Pick random L in range $[256, 480]$
2. Resize training image, short side = L
3. Sample random 224×224 patch

Testing: average a fixed set of crops

ResNet:

1. Resize image at 5 scales: $\{224, 256, 384, 480, 640\}$
2. For each size, use 10 224×224 crops: 4 corners + center, + flips



Data Augmentation

Color Jitter

Simple: Randomize
contrast and brightness



More Complex:

1. Apply PCA to all [R, G, B] pixels in training set
2. Sample a “color offset” along principal component directions
3. Add offset to all pixels of a training image

(As seen in *[Krizhevsky et al. 2012]*, ResNet, etc)


Data Augmentation

Get creative for your problem!

Random mix/combinations of :

- translation
- rotation
- stretching
- shearing,
- lens distortions, ... (go crazy)

Automatic Data Augmentation



Cubuk et al., "AutoAugment: Learning Augmentation Strategies from Data", CVPR 2019

Regularization: A common pattern

Training: Add random noise

Testing: Marginalize over the noise

Examples:

Dropout

Batch Normalization

Data Augmentation

Regularization: DropConnect

Training: Drop connections between neurons (set weights to 0)

Testing: Use all the connections

Examples:



Dropout

Batch Normalization

Data Augmentation

DropConnect

rather than zeroing out the activations,
instead we randomly zero out some of
the values of the WEIGHT matrix.



Wan et al, "Regularization of Neural Networks using DropConnect", ICML 2013

Regularization: Fractional Pooling

Training: Use randomized pooling regions

Testing: Average predictions from several regions

Examples:

cool idea, not so commonly used: randomize the pooling region, not fixed 2x2 region any more.


Dropout

Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling



Graham, "Fractional Max Pooling", arXiv 2014

Regularization: Stochastic Depth

Training: Skip some layers in the network

Testing: Use all the layer

Examples:

Dropout

Batch Normalization


Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth

The idea is that we have a very deep network. We're going to randomly drop layers from the network. During training, we're going to only use some subset layers. During test time, we'll use the whole network.



Huang et al, "Deep Networks with Stochastic Depth", ECCV 2016

Regularization: Cutout

Training: Set random image regions to zero

Testing: Use full image

Examples:

Dropout

Batch Normalization


Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth

Cutout / Random Crop



Works very well for small datasets like CIFAR,
less common for large datasets like ImageNet

DeVries and Taylor, "Improved Regularization of
Convolutional Neural Networks with Cutout", arXiv 2017

Regularization: Mixup

Training: Train on random blends of images

Testing: Use original images

Examples:

Dropout

Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth

Cutout / Random Crop

Mixup



Randomly blend the pixels of pairs of training images, e.g. 40% cat, 60% dog

CNN

Target label:

cat: 0.4

dog: 0.6

Zhang et al, “*mixup*: Beyond Empirical Risk Minimization”, ICLR 2018

Regularization - In practice

Training: Add random noise

Testing: Marginalize over the noise

Examples:

Dropout

Batch Normalization

Data Augmentation

DropConnect

Fractional Max Pooling

Stochastic Depth

Cutout / Random Crop

Mixup

- Consider dropout for large fully-connected layers
- Batch normalization and data augmentation almost always a good idea
- Try cutout and mixup especially for small classification datasets

Choosing Hyperparameters

(without tons of GPUs)

Choosing Hyperparameters

Step 1: Check initial loss

Turn off weight decay, sanity check loss at initialization
e.g. $\log(C)$ for softmax with C classes

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Try to train to 100% training accuracy on a small sample of training data (~5-10 minibatches); fiddle with architecture, learning rate, weight initialization

Loss not going down? LR too low, bad initialization

Loss explodes to Inf or NaN? LR too high, bad initialization

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Use the architecture from the previous step, use all training data, turn on small weight decay, find a learning rate that makes the loss drop significantly within ~ 100 iterations

Good learning rates to try: $1e-1$, $1e-2$, $1e-3$, $1e-4$

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for $\sim 1-5$ epochs

Choose a few values of learning rate and weight decay around what worked from Step 3, train a few models for $\sim 1-5$ epochs.

Good weight decay to try: $1e-4$, $1e-5$, 0

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for $\sim 1-5$ epochs

Step 5: Refine grid, train longer

Pick best models from Step 4, train them for longer ($\sim 10-20$ epochs) without learning rate decay

Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample



Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for ~1-5 epochs


Step 5: Refine grid, train longer


Step 6: Look at loss curves


Look at learning curves!



Losses may be noisy, use a scatter plot and also plot moving average to see trends better







Choosing Hyperparameters

Step 1: Check initial loss

Step 2: Overfit a small sample

Step 3: Find LR that makes loss go down

Step 4: Coarse grid, train for ~1-5 epochs

Step 5: Refine grid, train longer

Step 6: Look at loss curves


Step 7: GOTO step 5

Hyperparameters to play with:

- network architecture
- learning rate, its decay schedule, update type
- regularization (L2/Dropout strength)

[This image](#) by Paolo Guereta is licensed under [CC-BY 2.0](#)

Cross-validation “command center”



Random Search vs. Grid Search

*Random Search for
Hyper-Parameter Optimization*
Bergstra and Bengio, 2012




Illustration of Bergstra et al., 2012 by Shayne
Longpre, copyright CS231n 2017

Summary

- Improve your training error:
 - Optimizers
 - Learning rate schedules
- Improve your test error:
 - Regularization
 - Choosing Hyperparameters

Next time: CNN Architecture Design