

## 28" ENCLOSURE WITH SCREW-ON COVER

EN2800 | [On-Q](#)



<b>ATLANTIC PACIFIC</b> <small>COMMUNITY BUILDERS</small>	
<small>Receivable Stamp Matrix V</small> <b>SHOP DRAWING / SUBMITTAL REVIEW</b> <small>This is to certify that this submission has been checked for accuracy, completeness, and compliance with the contract requirements. This certification does not relieve the Subcontractor of their responsibility for complying fully with the contract documents. The Subcontractor shall not be relieved of this responsibility by the Architect's approval of this submittal unless the Subcontractor has specifically informed the Contractor and Architect in writing of such deviations at the time of the submittal.</small>	
Project:	Submitted for Review
Reviewed by:	Curtis Owens
Date:	10/07/2024
Submittal Number:	10-0000-1.0

  

<b>RECEIVED BY</b> <b>ATLANTIC PACIFIC</b> <small>COMMUNITY BUILDERS</small>	
<b>10/07/24</b>	

### FEATURES & BENEFITS

This 28" enclosure is the perfect solution for a basic structured wiring system. It features larger top openings that make pulling wire easier as well as additional knockouts, more side lances, and side tabs for more flexible mounting. It includes a screw-on cover.

Also available with Hinged & No Covers.



- Flanged covers hide drywall openings
- Drywall depth indicators
- Flush and surface installation
- Mounting tabs provide correct flush-mount position for standard installations
- Patented mounting system offers versatile module mounting options
- Literature pouch included for dealer information
- Includes self-adhesive cable identification table
- Cover included
- Made in the USA

### SPECIFICATIONS

#### GENERAL INFO

Color: Glossy White  
 Finish: Protective Powder Coat  
 Type: Screw-On

#### LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes  
 cULus: Yes  
 UL Listing No: ANSI/UL 1863;ANSI/UL 985;ANSI/UL 1023; CAN/CSA-C22.2 No. 182.4-1990;ULC-S545;CSA C32.2



**Date Received:**

2/10/2026

No. 144.1 (2006) -- (Communication Circuit Accessory) and (Security Equipment - Fire Alarm Equipment)

#### DIMENSIONS

Depth (US): 3.7"

Height (US): 28.1"

Width (US): 14.3"

Product Weight (US): 15.82 lb

#### TECHNICAL INFORMATION

Humidity: Max 93% non-condensing

Material: 20 Gauge CRS

Minimum Depth Requirement (US): 3.7"

Mounting: Surface or Flush



**Date Received:**

2/19/2026  
**2/10/2026**