

User Profile:

A profile is a database object - a named set of resource limits to:

- Restrict database usage by a system user

- Enforce password practices – how user passwords are created, reused, and validated.

- Profile is a collection of resource usage and password related attributes that you can assign to user.

- you can set the individual resource limits using profile.

- Multiple users can share a profile and you can have unlimited number of profile in an oracle database

- profile help you to limit the number of sessions a user can simultaneously keep open, the length of time

- these session can be maintained, usage of CPU and other resources..

- Profile is basically used to set the user policy

Profiles are assigned to users as part of the CREATE USER or ALTER USER commands.

Profile parameters and limit:

- > Resource Parameters: which are concerned purely with limiting resource usage

- > Password Parameters: used for enforcing password related security policies

Resource Parameter:

to ensure that a single user or a set of user doesn't monopolize the database and server resources.

eg.

- connect_time: total time a session may remain connected to the database

- cpu_per_session: limits the total CPU time used during a session

- idle_time: time to remain idle (define in minute)

- logical_reads_per_session: limits the total number of data blocks read (from SGA memory area plus disk read)

Password parameter:

Failed_login_attempts:

- number of consecutive attempts a user can make before being locked out

- password_life_time: time limit for using a particular password (define in days)

- password_grace_time: sets the time period during which you will be warned that your password has expired. After the grace period is exhausted, you cannot connect to the database with that password.

Password_lock_time:

- specifies the number of days a user will be locked out after reaching the max number of unsuccessful login attempts

password_reuse_time:

- specifies the number of days that must pass before you can reuse the same password.

Password_reuse_max:

- determines how many times you need to change your password before you can reuse a particular password.

By default user inherit the DEFAULT profile.

Profiles only take effect when resource limits are "turned on" for the database as a whole.

- Specify the RESOURCE_LIMIT initialization parameter.

RESOURCE_LIMIT = TRUE

Let check the parameter value.

SQL> show parameter resource_limit

NAME	TYPE	VALUE
resource_limit	boolean	FALSE

ALTER SYSTEM SET RESOURCE_LIMIT = TRUE;
System altered.
SQL> show parameter resource_limit

NAME	TYPE	VALUE
resource_limit	boolean	TRUE

Practice:

1. Create profile
2. assign the profile to user and see the impact
3. update profile
4. drop profile

If you drop the profile that is assigned to user, the user will inherit the DEFAULT profile.