



# Experimental Investigation of the Effect of Gasoline Fuel on Engine Performance, NO<sub>x</sub> reduction, and Engine Wear of a 38.8L Military Heavy Duty CIDI Diesel Engine Applying EGR

**Anand Kumar Pandey** Symbiosis Institute Of Technology

**Milankumar Nandgaonkar** College of Engineering

**C Sonawane, Vishal Kumbhar, and Anil Varghese** Symbiosis Institute Of Technology

**Citation:** Pandey, A.K., Nandgaonkar, M., Sonawane, C., Kumbhar, V. et al., "Experimental Investigation of the Effect of Gasoline Fuel on Engine Performance, NO<sub>x</sub> reduction, and Engine Wear of a 38.8L Military Heavy Duty CIDI Diesel Engine Applying EGR," SAE Technical Paper 2022-01-1027, 2022, doi:10.4271/2022-01-1027.

Received: 13 Apr 2022

Revised: 22 Jun 2022

Accepted: 24 Jun 2022

## Abstract

Rapidly depleting oil reserves and strict pollution regulations have made it necessary to find a substitute for diesel fuel. In the context of the multi-fuel strategy program, gasoline has improved the fuel availability for both combat and commercial highway vehicles with diesel engines. This study examines the effect of gasoline fuel on the engine wear, performance, and emission of a military, heavy-duty, supercharged diesel engine. In a CIDI diesel engine, the use of Gasoline has been considered to be significantly sustainable with engine performance and reduced pollutants. For this research a military heavy-duty, 38.8 L, 585kW, diesel engine, the EGR technique was used for gasoline and diesel fuels.

Furthermore, the impact of nanoparticles on NO<sub>x</sub> emissions was also explored. NO<sub>x</sub> emission reduces in diesel

engines by using the EGR technique. Two test fuels were tested in their trials for a total of 100 hours of engine endurance assessment. After every 20 hours of engine operation, 100 mL of lube oil was extracted from the oil sump and tested for elemental analysis. Ferrography and atomic absorption spectroscopy have been used to measure the composition of metal wear debris. It was used to evaluate the metal wear on the exposed cylinder liner. A new engine part was used to perform durability tests for test fuels. For gasoline-powered engines, metal wear was estimated to be 10 to 12 percent higher than for diesel-powered engines. Gasoline fuel's engine performance was 4.5% lower than diesel fuel. When the engine was running on Gasoline, NO<sub>x</sub> emissions were reduced by 28%, and nanoparticle emissions were also reduced.

## Introduction

Diesel engines are mainly encountered in frontline combat operations and heavy-duty highway vehicles. A diesel engine with a supercharger improves power, reduces fuel consumption, and improves engine durability. Roughly 85% and 5-15% of vehicles rely on diesel and Gasoline fuel respectively. Whereas, approximately 27% and 33% of petroleum diesel and Gasoline fuel respectively, are extracted from crude oil refinery processes [29]. Therefore, surplus Gasoline fuel is available as an alternative fuel for diesel [30].

A multi-fuel strategies initiative has been initiated in response to the rapid reduction of petroleum oil deposits. Due to an abundance of Gasoline fuel, all combat ground and heavy-duty highway vehicles can be operated with Gasoline fuel without considerably sacrificing the diesel engine's performance and exhaust emissions. This alternate approach

promotes logistical optimization and homogeneity, and also improves the economics. [Table 1](#) summarizes the diesel and gasoline fuel qualities.

Gasoline diesel engines can be utilized in military combat vehicles and heavy-duty highway vehicles. The heating value of Gasoline is less. As a result, employing Gasoline fuel could result in a performance penalty [1,2,4,32]. Consequently, for optimal performance with dual fuel diesel/Gasoline, the fuel injection pump must be tuned to balance the quantity of fuel per cycle by increasing the volume of Gasoline [3,4,5,7].

In selecting suitable alternative fuel, engine wear is one of the most critical performances due to the non-lubricating quality of Gasoline fuel and fuel dilution with lubricating oil [26]. Diesel engine components that are most likely to wear are cylinder liner, piston rings, piston pin, crankshaft, camshaft, engine valves, and all engine bearings. All metallic

slight penalty of power, specific fuel consumption, and engine wear.

## Acknowledgments

The authors extend thanks to the defense R&D organization for granting the project grant and the army workshop for providing a test engine for this research study.

## References

- Boverie, S., Heredia, G., Gonzalez-Cantos, A., Ollero, A. et al., "Fuzzy Modelling, Control, and Bifurcation-Based Stability Analysis of a Gasoline Direct Injection Engine," *Proc. IMechE, Part D, J. Automobile Engineering*, Vol. 223, 1459-1479, 2009.
- Leach, B., Zhao, H., Li, Y., and Ma, T., "Two-Phase Fuel Distribution Measurements in a Gasoline Direct Injection Engine with An Air-Assisted Injector Using Advanced Optical Diagnostics," *Proc. IMechE, Part D, J. Automobile Engineering* 221 (2007): 663-673.
- Hwang, I.G., Choi, K., Kim, J., Myung, C.-L. et al., "Experimental Evaluation of Combustion Phenomena in and Nanoparticle Emissions from a Side-Mounted Direct-Injection Engine with Gasoline and Liquid-Phase Liquefied Petroleum Gas Fuel," *Proc. IMechE, Part D, J. Automobile Engineering* 226 (2011): 12-122.
- Qiao, A.P., Li, Y.Q., and Gao, F., "Improving the Theoretical Cycles of Four-Stroke Internal Combustion Engines and Their Simulation Calculations," *Proc. IMechE, Part D, J. Automobile Engineering* 220 (2006): 219-225.
- Na, B.C., Ri, Y., Myun, P., Si, C. et al., "Design Improvement of a High-Pressure Fuel Pump for Gasoline Direct Injection Engines," *Korea Proc Instn Mech Engrs Part D* 216 (2002): 83-90.
- Park, C., Kim, S., Kim, H., Lee, S. et al., "Effect of a Split-Injection Strategy on the Performance of Stratified Lean Combustion for a Gasoline Direct-Injection Engine," *Proc. IMechE, Part D: J. Automobile Engineering* 225 (2011): 1415-1426.
- Choi, S., Jang, J.U., Lee, S., and Lee, S.-K., "Identification of the Contribution of a Coherent Vibration Source in a Gasoline Direct-Injection Engine Using a Two-Input Single-Output Model," *Proc IMechE, Part D, J Automobile Engineering* 227, no. 12 (2013): 1698-1705.
- Wang, T.-Y., Peng, Z.-J., and Wagg, D., "In-cylinder Air Motion Characteristics with Variable Valve Lift in a Spark Ignition Engine. Part1: Swirl Flow," *Proc. IMechE, PartD, J. Automobile Engineering* 225 (2010): 479-497.
- Tonini, S., Gavaises, M., Arcoumanis, C., Theodorakakos, A. et al., "Multi-component Fuel Vaporization Modelling and Its Effect on Spray Development in Gasoline Direct Injection Engines," *Proc. IMechE, Part D, J. Automobile Engineering* 221 (2007): 1321-1342.
- Ye, Z.-M. and Li, Z.-J., "Impact of Lean-Burn Control Technology on the Fuel Economy and NOx Emission of Gasoline Engines," *Proc. IMechE Part D, J. Automobile Engineering* 224 (2010): 1041-1058.
- Zhan, R., Eakle, S.T., and Weber, P., "Simultaneous Reduction of PM, H.C., CO and NOx Emissions from a GDI Engine," SAE Technical Paper 2010-01-0365 (2010), <https://doi.org/10.4271/2010-01-0365>.
- Kidoguchi, Y., Yang, C., and Miwa, K., "Effects of Fuel Properties on Combustion and Emission Characteristics of a Direct-Injection Diesel Engine," SAE Technical Paper 2000-01-1851 (2000), <https://doi.org/10.4271/2000-01-1851>.
- Feng, Q., Jalali, A., Fincham, A.M., Wang, Y.L. et al., "Soot Formation in Flames of Model Biodiesel Fuels," *Combustion Flame* 159, no. 5 (2012): 1876-1893.
- Wang, Z., Wang, J.-X., Shuai, S.-J., Wang, Y.-J. et al., "Study of Multimode Combustion System With Gasoline Direct Injection," *Journal of Engineering for Gas Turbines and Power* 129 (2007): 1079-1087.
- Hoffmann, G., Befrui, B., Berndorfer, A., Piock, W.F. et al., "Fuel System Pressure Increase for Enhanced Performance of GDI Multi-Hole Injection Systems," SAE Technical Paper 2014-01-1209 (2014), <https://doi.org/10.4271/2014-01-1209>.
- Hedge, M., Weber, P., Gingrich, J., Alger, T. et al., "Effect of EGR on Particle Emissions from a GDI Engine," *SAE Int. J. Engines* 4, no. 1 (2011): 650-666.
- Ciatti, S.A., Miers, S.A., and Ng, H.K., "Influence of EGR on Soot/NOx Production in a Light-Duty Diesel Engine," ASME Paper, ICEF2005-1327, 2005.
- Kim, Y., Kim, Y., Jun, S., Lee, K. et al., "Strategies for Particle Emissions Reduction from GDI Engines," SAE Technical Paper 2013-01-1556 (2013), <https://doi.org/10.4271/2013-01-1556>.
- Ming, Z., Jun, Z., Stefano, C., and Luigi, L., "Particulate Matter Emission Suppression Strategies in a Turbocharged Gasoline Direct-Injection Engine," *Journal of Engineering for Gas Turbines and Power*, ASME 139 (2017): 102801-102808.
- Cavina, N., Businaro, A., Rojo, N., Cesare, M.D. et al., "Combustion and Intake/Exhaust Systems Diagnosis Based on Acoustic Emissions of a GDI TC Engine," *Energy Procedia, Science Direct* 101 (2016): 677-684.
- Eastwood, P., *Particulate Emissions from Vehicles*. Vol. 20 (West Sussex, UK: Wiley, 2008)
- Kittelson, D.B., "Particles and Nanoparticles: A Review," *J. Aerosol Sci.* 29, no. 5 (1998): 575-588.
- Pandey, A. and Nandgaonkar, M., "Performance, Emission and Pump Wear Analysis of JP-8 Fuel for Military Use on a 558 kW, CIDI Diesel Engine," *SAE Int. J. Fuels Lubr.* 3, no. 2 (2010): 238-245.
- Pocock, G. and Courtney, S.J., "Some Quantitative Aspects of Ferrography," *Wear* 67 (1981): 287-301.
- Hofman, M.V. and Johnson, J.H., "The Development of Ferrography as a Laboratory Wear Measurement Method for the Study of Engine Operating Conditions on Diesel Engine Wear," *Wear* 44 (1977): 183-199.
- Kalam, M.A. and Majsuki, H.H., "Use of an Additive in Biofuel A to Evaluate Emissions, Engine Component Wear and Lubrication Characteristics," *Proc IMechE, Part D: J Automobile Engineering* 216 (2002).

27. Agarwal, A.K., Bigwe, J., and Das, L.M., "Wear Assessment in a Biodiesel Fuelled Compression Ignition Engine," *ASME* 820 125 (2003).
28. TSI, "Engine Exhaust Particle Sizer (T.M.) Spectrometer", model- 3938, Operation and Service Manual.
29. Heywood, J.B., *Internal Combustion Engine Fundamentals* (New York: McGraw- Hill, 1998)
30. Stone, R., *Introduction to Internal Combustion Engines*, 4th ed. (London: Macmillan Press, 2012)
31. Eastwood, P., *Particulate Emissions from Vehicles*. Vol. 20 (West Sussex, UK: Wiley, 2008)
32. Kidoguchi, Y., Yang, C., and Miwa, K., "Effects of Fuel Properties on Combustion and Emission Characteristics of a Direct-Injection Diesel Engine," SAE Technical Paper [2000-01-1851](https://doi.org/10.4271/2000-01-1851) (2000), <https://doi.org/10.4271/2000-01-1851>.
33. Dadam, Sumanth Reddy, Michiel Van Nieuwstadt, Lehmen, Allen, Ravi, Vinod Kumar, Kumar, Vivek, and Bhat, Rohit. "A Unique Application of Gasoline Particulate Filter Pressure Sensing Diagnostics." *SAE International Journal of Passenger Cars-Mechanical Systems* 14, no. 06-14-02-0007 (2021): 105-116.
34. Dadam, S.R., Jentz, R., and Meissner, H., "Diagnostic Evaluation of Exhaust Gas Recirculation (EGR) System on Gasoline Electric Hybrid Vehicle," SAE Technical Paper [2020-01-0902](https://doi.org/10.4271/2020-01-0902) (2020), <https://doi.org/10.4271/2020-01-0902>.
35. Dadam, S.R., Ali, I., Zhu, D., and Kumar, V., "Effects of Differential Pressure Measurement Characteristics on High Pressure-EGR Estimation Error in SI-Engines," *International Journal of Engine Research* (2021): 14680874211055580.
36. Kumar, V., Dadam, S.R., Zhu, D., and Mehring, J., "Fuel-Economy Performance Analysis with Exhaust Heat Recovery System on Gasoline Engine," *SAE International Journal of Engines* 15, no. 03-15-06-0045 (2022).
37. Pandey, A., Nandgaonkar, M., Suresh, S., and Varghese, A., "The Effect of Cerium Oxide Nano Particles Fuel Additive on Performance, Combustion, NOx Reduction and Nano Particle Emission of Karanja and Jatropha Biodiesel in a Military 585 kW CIDI Engine," SAE Technical Paper [2019-01-0262](https://doi.org/10.4271/2019-01-0262) (2019). <https://doi.org/10.4271/2019-01-0262>.
38. Kumbhar, V., Pandey, A.K., Varghese, A., and Wanjari, S., "Application of Biodiesel for 12-cylinder, Supercharged Military Combat Vehicle," *International Journal of Ambient Energy* (2022). <https://doi.org/10.1080/01430750.2020.1725632>.
39. Pandey, A., Sivakumar, P., Nandgaonkar, M., and Suresh, S., "Comparison and Evaluation of Engine Wear, Combustion and Emissions Performance between Diesel, Karanja and Jatropha Oil Methyl Ester Biodiesel in a 780 hp Military Diesel Engine," SAE Technical Paper [2014-01-1395](https://doi.org/10.4271/2014-01-1395) (2014). <https://doi.org/10.4271/2014-01-1395>.
40. Pandey, A., Nandgaonkar, M., Pandey, U., and Suresh, S., "Experimental Investigation of the Effect of Karanja Oil Biodiesel with Cerium Oxide Nano Particle Fuel Additive on Lubricating Oil Tribology and Engine Wear in a Heavy Duty 38.8L,780 HP Military CIDI Diesel Engine," SAE Technical Paper [2018-01-1753](https://doi.org/10.4271/2018-01-1753) (2018). <https://doi.org/10.4271/2018-01-1753>.

## Definitions/Abbreviations

**Symbol** - Description, Units

**cst** - Centi stokes

**°C** - Degree centigrade

**kW** - Kilo watt

**MJ** - Mega joule

**Vol** - Volume

**wt** - Weight