



UNCLASSIFIED//FOUO



Pseudocode, Logic and Design

1

UNCLASSIFIED



- **DECISION STRUCTURES AND BOOLEAN LOGIC**

UNCLASSIFIED ²

2



Learning Objectives

- 4.1 Introduction to Decision Structures**
- 4.2 Dual Alternative Decision Structures**
- 4.3 Comparing Strings**
- 4.4 Nested Decision Structures**
- 4.5 The Case Structure**
- 4.6 Logical Operators**
- 4.7 Boolean Variables**

3

3



UNCLASSIFIED



4.1 Introduction to Decision Structures

A decision structure (or selection structure) allows a program to perform actions only under certain conditions

Different types of decisions include

- **If, also called single alternative**
- **If then else, also called dual alternative**
- **Case structure for multiple alternative decisions**

UNCLASSIFIED 4

4




4.1 Introduction to Decision Structures (2 of 3)

The if statement

- An action only occurs if the decision is true
*If condition Then
 Statement
 Statement
 End If*
- A diamond symbol is used in flowcharts

Figure 4-1 A simple decision structure for an everyday task



5

5



4.1 Introduction to Decision Structures (3 of 3)

Relational Operators

- Determines whether a specific relationship exists between two values
- Used within the condition, a Boolean expression

$x > y$ $x < y$ $x >= y$ $x <= y$ $x == y$ $x != y$

Table 4-1 Relational operators

Operator	Meaning
>	Greater than
<	Less than
>=	Greater than or equal to
<=	Less than or equal to
==	Equal to
!=	Not Equal to

6

6




4.2 Dual Alternative Decision Structures (1 of 2)

If then else statement

- Executes one group of statements if it's Boolean expression is true, or another group if its Boolean expression is false

Figure 4-8 A dual alternative decision structure



7

7



UNCLASSIFIED

4.2 Dual Alternative Decision Structures



*If condition Then
statement
statement*

*Else
statement
statement*

End if


If temperature < 40 Then
Display "A little cold"
Display "Get a coat!"

Else
Display "Nice weather"
Display "And sunny!"

End if


UNCLASSIFIED 8

8



UNCLASSIFIED

4.3 Comparing Strings (1 of 2)



Most languages allow you to compare strings

Program 4-3

```

1 // A variable to hold a password.
2 Declare String password
3
4 // Prompt the user to enter the password.
5 Display "Enter the password."
6 Input password
7
8 // Determine whether the correct password
9 // was entered.
10 If password == "prospero" Then
11     Display "Password accepted."
12 Else
13     Display "Sorry, that is not the correct password."
14 End If

```

Program Output (with Input Shown in Bold)

```

Enter the password.
ferdinand [Enter]
Sorry, that is not the correct password.

```

Program Output (with Input Shown in Bold)


```

Enter the password.
prospero [Enter]
Password accepted.

```

UNCLASSIFIED 9

9



4.3 Comparing Strings (2 of 2)

Other String Concerns


- String and strings can be compared

name1 == name 2
- String and string literals can be compared

Month != "October"
- String comparisons are generally case sensitive
- You can also determine whether one string is greater than or less than another string (allows for sorting strings)

10

10




4.4 Nested Decision Structures (1 of 3)

Decisions are nested in order to test more than one condition


If then if else example

Figure 4-15 A nested decision structure




11

11



UNCLASSIFIED

4.4 Nested Decision Structures (2 of 3)



The if then else if statement can make nested logic simpler to write

```

If score < 60 Then
    Display "Grade is F."
Else If score < 70 Then
    Display "Grade is D."
Else If score < 80 Then
    Display "Grade is C."
Else If score < 90 Then
    Display "Grade is B."
Else
    Display "Grade is A."
End If
        
```

UNCLASSIFIED 12

12




4.5 The Case Structure

The case structure lets the value of a variable or an expression determine which path of execution the program will take

- Can be used as an alternative to nested decisions

Figure 4-18 A case structure



13

13



UNCLASSIFIED

4.6 Logical Operators (1 of 4)



Logical Operators are used between conditions to create complex Boolean expressions

- **AND** – Both conditions must be true
- **OR** – Either condition must be true
- **NOT** – Reverses the truth of an expression

UNCLASSIFIED 14

14



4.6 Logical Operators (2 of 4)

AND example

*If temperature < 20 AND minutes > 12 Then
Display "The temperature is in the danger zone."
End If*

OR example

*If temperature < 20 OR temperature > 100 Then
Display "The temperature is in the danger zone."
End If*

NOT example

*If NOT (temperature > 100) Then
Display "This is below the maximum temperature."
End If*

15

15



UNCLASSIFIED

4.6 Logical Operators (3 of 4)



Short-Circuit Evaluation: Supported by many languages for increased performance

- **AND operator:** If the expression on the left side of the AND operator is false, the expression on the right side will not be checked.
- **OR operator:** If the expression on the left side of the OR operator is true, the expression on the right side will not be checked.

UNCLASSIFIED 16

16



4.6 Logical Operators (4 of 4)

Range Checking

- Often used for range checking
 - When checking for a number **inside** a range, use AND

```
If x >= 20 AND x <= 40 Then
    Display "The value is in the acceptable range."
End If
```

- When checking for a number **outside** a range, use OR

```
If x < 20 OR x > 40 Then
    Display "The value is outside the acceptable range."
End If
```

17

17



UNCLASSIFIED

4.7 Boolean Variables



A variable of the Boolean data type can hold one or two values: true or false

```
Declare Boolean isLunchTime
If time >= 12 then
    Set isLunchTime = True
Else
    Set isLunchTime = False
End If
```

UNCLASSIFIED 18

18