

# PhyDGET



James B. Pease

6 August, 2021

## Contents

<b>Introduction</b>	<b>2</b>
Authors . . . . .	2
What is PhyDGET? . . . . .	2
How do I cite PhyDGET? . . . . .	2
<b>Getting Started</b>	<b>2</b>
Requirements . . . . .	2
Installation . . . . .	3
<b>Preparing your data</b>	<b>3</b>
Phylogeny . . . . .	3
RNA-Seq Count File . . . . .	3
<b>Basic usage</b>	<b>3</b>
Specifying Models . . . . .	4
<b>Program Parameters</b>	<b>6</b>
phydget . . . . .	6
<b>Version History</b>	<b>7</b>
<b>License</b>	<b>7</b>

---

*Version 0.3.0*

---

## Introduction

### Authors

James B. Pease (<http://www.peaselab.org>)

### Contributors:

David de la Cerda

### What is PhyDGET?

Phylogenetic Differential Gene Expression Tool (PhyDGET) is a method for analyzing the changes in transcriptome-wide expression levels gene by gene on a phylogeny. PhyDGET is a merger in method and thinking between Phylogenetic Comparative Methods and Differential Gene Expression. PhyDGET first performs a log2 counts-per-million transformation and filters low-coverage genes to prepare them for phylogenetic testing. PhyDGET then parallelizes the passage of these data to BayesTrait-v3, which tests each gene's expression level as a quantitative trait evolving on the tree. Using BayesTrait's likelihood ratio test framework, you can specify a range of branch rate-shifting models to test what genes' expression levels are changing on the targeted branches. Note that this is NOT a traditional differential expression framework using linear regression models with control vs. treatment. The goal of PhyDGET is to estimate species-specific expression levels for each gene and examine them phylogenetically as quantitative traits.

### How do I cite PhyDGET?

Citation forthcoming.

Please also include the URL <https://www.github.com/peaselab/phydget> in your methods section where the program is referenced.

**You should also cite BayesTraits (see info at URL below)**

---

## Getting Started

### Requirements

- Python 3.x (2.x will not work) <https://www.python.org/downloads/>
- Numpy for Python3 <http://www.numpy.org>
- Scipy for Python3 <https://www.scipy.org>
- BayesTraits (V3.0.1) <http://www.evolution.rdg.ac.uk/BayesTraitsV3.0.1/BayesTraitsV3.0.1.html>

## Installation

No installation of PhyDGET itself is required, the scripts should work as long as the Requirements (above) are installed. The repository can be cloned or downloaded as a .zip file from GitHub.

```
git clone https://www.github.com/peaselab/phydget
```

---

## Preparing your data

### Phylogeny

An ultrametric phylogenetic tree in Nexus format should be used. The tree will be passed to BayesTraits directly, so we recommend consulting the BayesTraits manual further for additional details about the preparation of phylogenetic trees for that software. We recommend preparation of trees using the *ape* package from R. <https://cran.r-project.org/web/packages/ape/>

### RNA-Seq Count File

Data file should be a tab-separated file with a single header line and gene names in the first column.

## Basic usage

PhyDGET can be run with all flags in the command line:

```
python3 phydget.py --data DATAFILE.tsv --tree TREEFILE.nwk --out  
OUTPUT.txt --models MODEL1:S1 --samples S1:S1a,S1b,S1c --samples  
S2:S2a,S2b,S2c ...
```

or by placing command line flags in a plain-text file, with one line per flag.

```
python3 phydget.py JOBFIL
```

Example of jobfile:

```
# PhyDGET Job Command File  
--data DATAFILE.tsv  
--tree TREEFILE.nwk  
--threads 4  
--transform log2cpm  
--out OUTPUT.txt  
--bt-exec BayesTraitsV3  
--models M1:S1  
--models M2:S2  
--models M12:S1+S2
```

```
--samples S1:S1a,S1b,S1c
--samples S2:S2a,S2b,S2c
--samples S3:S3a,S3b,S3c
--samples S4:S4a,S4b,S4c
```

*Note: Lines startwith with # will be ignored and can be used for keeping notes or metadata in the job file.*

- Individual sample names (S1a, S1b, S2a, etc.) must match headers in the `--data` counts table.
- Sample names (S1, S2, etc.) must match the tips of `--tree` phylogeny and specified names in the `--model` parameters (see below).

## Specifying Models

The model syntax of PhyDGET accommodates one or more alternative rate categories for quantitate trail value shifts on a branch. There is no need to specify the null model, it will run automatically. Note that for all models, the `--sample` must be provided (see Single Terminal Branch below for syntax).

### Single Terminal Branch

For a single alternative rate category on a terminal branch, the syntax is:

```
--model MODEL1:S1 --sample S1:S1a,S1b,S1c --sample S2:S2a,S2b,S2c
--sample S3:S3a,S3b,S3c --sample S4:S4a,S4b,S4c
```

This will attach an alternative rate category for the branch leading to taxon S1. This species label must match your phylogeny tip label exactly.

The labels corresponding to each species must be included as several `--sample` lines in the format shown above. These sample labels must match the headers on the expression tabular data file exactly. All species on the tree provided must have a `--sample` entry.




Figure 1: Model Example 1: Single Terminal Branch

### Single Ancestral Branch

For a single alternative rate category on ancestral branch, the syntax is:

```
--model MODELNAME:S1+S2+S3
```

This places the most recent common ancestor branch of S1, S2, and S3 in the alternative rate category. The + signs are used to separate the taxa jointly specifying their most recent common ancestor.




Figure 2: Model Example 2: Single Ancestral Branch

### Multiple Branches, Single Rate

```
--model MODELNAME:S1+S2+S3,S1
```

This places the S1+S2+S3 ancestral branch and the S4 terminal branch both under a single common alternative rate category. The , separates different branches that are under the same rate.




Figure 3: Model Example 3: Multiple Branches under a single rate

### Multiple Branches, Multiple Rates

```
--model MODELNAME:S1,S2:S3
```

This places the S1 and S2 branches under one alternative rate category, and the S3 branch under a separate alternative rate category. The : separates the branch or branches under different rate categories.

### Transform

The options for transformation (`--transform`) are:




Figure 4: Model Example 3: Multiple Branches under multiple rate

- **log2cpm** (default): Divide each value by the total number of counts per sample times  $10^6$  (counts-per-million), then log2 transform.
- **log2**: Logarithm base 2 transformation without sample-size normalization.
- **cpm**: Divide each value by the total number of counter per sample times  $10^6$  (counts-per-million).
- **none**: Do not transform the data. Not recommended unless you data are already log-transformed by your own method.

### BayesTraits3 Parameters

The specifics of the parameters for BayesTrait are listed in the BayesTrait manual.

## Program Parameters

### phydget

*PhyDGET: Phylogenetic Differential Gene Expression Tool*

*Author: James B. Pease*

#### Parameters

**--data** (required) = input expression data filepath (csv format) (type=file path, default=None)

**--model** (required) = Enter one model or specify a file path of a text file containing multiple models. Models syntax described in the manual. (type=None, default=None)

**--out** (required) = output file path (csv format) (type=file path, default=None)

**--sample** (required) = SA:A1,A1,A3 SB:B1,B2,B3, ... Species id (must match the phylogeny tip labels) followed by comma-separated individual sample ids (must match the headers on the data file). (type=None, default=None)

**--tree** (required) = input tree file path (Nexus format) (type=file path, default=None)  
**--bt-burnin/--btburnin** = BayesTrait number of burn-in steps. (type=integer, default=1000000)  
**--bt-exec/--btexec** = BayesTrait executable path (type=None, default=BayesTraitV3)  
**--bt-iter/--btiter** = BayesTrait number of iterations used per stone in the stepping stone sampling. (type=integer, default=10000000)  
**--bt-priors/--btpriors** = BayesTrait uniform prior range. (type=float, default=(-10, 30))  
**--bt-stoneiter/--btstoneiter** = BayesTrait number of iterations used per stone in the stepping stone sampling. (type=integer, default=20000)  
**--bt-stones/--bt-stones** = BayesTrait number of stones used in the stepping stone sampling. (type=integer, default=200)  
**--keep-files/--keepfiles** = Keep all temporary files (flag, default=False)  
**--temp-dir/--tempdir** = temporary folder for files (type=None, default=PhyDGETtmp)  
**--temp-prefix/--temp-prefix** = Temporary Directory Prefix (type=None, default=PhyDGETRun)  
**--test-gene/--testgene** = Enter exact gene name from first column of input csv file to do a test run on a single gene. (type=None, default=None)  
**--threads** = Number of threads for parallelization (type=integer, default=2)  
**--transform** = Data transformation type (see manual for details). (type=None, default=log2cpm) Choices: ('none', 'log2', 'cpm', 'log2cpm')  
**--verbose** = extra screen output (flag, default=False)

## Version History

- **0.3.0:** First public release

## License

PhyDGET is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version. MVFtools is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public

License for more details. You should have received a copy of the GNU General Public License along with PhyDGET. If not, see <http://www.gnu.org/licenses/>.