


Practical – 3

Aim : To Implementation of Max-Heap sort algorithm

Algorithm :



Program / Code :

```
#include <iostream>
#include <vector>
using namespace std;
```

```
void heapify(vector<int> &arr, int n, int i)
{
    int largest = i;
    int left = 2 * i + 1;
    int right = 2 * i + 2;

    if (left < n && arr[left] > arr[largest])
```

```
        largest = left;

    if (right < n && arr[right] > arr[largest])
        largest = right;

    if (largest != i)
    {
        swap(arr[i], arr[largest]);
        heapify(arr, n, largest);
    }
}

void heapsort(vector<int> &arr)
{
    int n = static_cast<int>(arr.size());

    for (int i = n / 2 - 1; i >= 0; i--)
        heapify(arr, n, i);

    for (int i = n - 1; i > 0; i--)
    {
        swap(arr[0], arr[i]);
        heapify(arr, i, 0);
    }
}

int main()
{
    vector<int> arr = {64, 34, 25, 12, 22, 11, 90};

    heapsort(arr);

    cout << "Sorted array using heap sort:\n";
    for (int value : arr)
        cout << value << ' ';

    cout << '\n';
    return 0;
}
```

OUTPUT:

● PS C:\Users\pusap\Downloads\c++> C:\Users\pusap\Downloads\c++\heapsort.exe
Sorted array using heap sort:
11 12 22 25 34 64 90

Time Complexity :

Time Complexity :

for ($i = n/2, i > 1; i--$) $\rightarrow n$
max heapify (arr, n, i) $\rightarrow \log n$
for ($i = n; i > 1; i--$) $\rightarrow n$
swap ($arr[i], arr[1]$) $\rightarrow 1$
max heapify ($arr, i-1, 1$) $\rightarrow \log n$

$$T(n) = n \times \log n + n + 1 \times \log n$$

$$= n \log n + n \log n$$

$$T(n) = O(n \log n)$$

⇒ Best case :

for $i = n/2$ to 1
max heapify (arr, n, i) $\rightarrow n$
for $i = n$ to 2
swap heapify ($arr, i-1, 1$) $\rightarrow \log n$

$$T(n) = O(n) + n \times O(\log n)$$

$$= O(n \log n)$$

ii) Average case :

for $i = n/2$ to 1
max heapify (arr, n, i) $\rightarrow n$
for $i = n$ to 2
swap ($arr[i], arr[1]$)
max heapify ($arr, i-1, 1$) $\rightarrow \log n$
 $T(n) = n + \log n$
 $= O(n \log n)$

iii) Worst case :

max heapify from root to lowest level
 $\rightarrow \log n$
max heapify $\rightarrow \log n$
 $T(n) = n \times \log(n) \rightarrow O(n \log n)$

Conclusion :

The Max-Heap Sort algorithm was successfully implemented and executed to sort the elements in ascending order. The program verified a consistent time complexity of $O(n \log n)$ across the best, average, and worst cases using an in-place binary heap structure