


Evaluating Denoising Methods for 3D Ultrasound Uterus Segmentation with DynUNet

Marija Habijan, Juraj Perić, Irena Galić

Faculty of Electrical Engineering, Computer Science and Information Technology
Osijek, Croatia

Motivation

- Uterus morphology is key for fertility and pregnancy
- 3D ultrasound = non-invasive, detailed imaging
- Segmentation is challenging: noise, artifacts, variability
- Need robust automatic methods



Research Goal

- Propose pipeline:
 - Fully automatic uterus segmentation
- Denoising + DynUNet segmentation
 - Compare 7 denoising methods + baseline
 - Show effect on segmentation accuracy

Dataset Description

- UterUS dataset
 - 315 3D ultrasound volumes
 - 141 volumes with expert-annotated uterine cavity masks
 - 174 unannotated cases




Figure 1. Example of ultrasound volumes from UterUS dataset

Pre-processing

- CLAHE + Butterworth
- DWT + Threshold
- CLAHE + Median Filter
- Median-Mean Hybrid Filter
- Unsharp Masking + Bilateral Filter
- Perona–Malik Anisotropic Diffusion
- 3D DnCNN denoising model

Proposed Method




Figure 2. Multi-branch preprocessing and segmentation pipeline for 3D uterus segmentation using DynUNet. A raw 3D ultrasound image is processed through seven pipelines: (1) no preprocessing (baseline), (2) CLAHE + Butterworth filtering, (3) DWT + Thresholding, (4) CLAHE + Median filtering, (5) Median–Mean hybrid filtering, (6) Unsharp Masking + Bilateral filtering, (7) Perona–Malik diffusion, and (8) 3D DnCNN denoising model.

DynUNet




Figure 3. DynUNet architecture. The network processes 3D ultrasound patches of size 128^3 with one input channel. The encoder progressively downsamples the input through four convolutional blocks (16–128 channels) before reaching a 256-channel bottleneck. The decoder then upsamples through three stages with skip connections from the encoder, and a final $1 \times 1 \times 1$ convolution with sigmoid activation produces the uterus segmentation mask.

Training Setup

- 5-fold cross-validation (subject-level separation)
- Adam optimizer, LR = $1e-4$,
- 100 epochs
- Sliding window inference
- Hardware: Nvidia A6000, MONAI + PyTorch

Results

Table 1. Evaluation of the DynUNet segmentation models without and with different pre-processing pipelines using the DSC metric on validation and test set.

| | 3D DynUNet [DSC %] | |
|-----------------------------------|-----------------------|-----------------|
| | <i>Validation Set</i> | <i>Test Set</i> |
| Baseline | 83.72 | 60.60 |
| CLAHE + Butterworth | 84.50 | 64.36 |
| DWT + Threshold | 84.76 | 69.61 |
| CLAHE + Median Filter | 84.81 | 65.42 |
| Median-Mean Hybrid Filter | 86.43 | 50.43 |
| Unsharp Maskin + Bilateral Filter | 85.60 | 56.70 |
| Perona-Malik | 84.97 | 64.40 |
| DNCNN | 85.76 | 71.95 |

Results




Figure 4. An example of test image, ground truth and obtained segmentation mask with DSC 92.03 %.

Conclusion

- Denoising critical for robust US segmentation
- DnCNN yields best results (Dice +11%)
- Next: explore advanced denoising (transformers, diffusion)
- Potential clinical integration for fertility diagnostics

Evaluating Denoising Methods for 3D Ultrasound Uterus Segmentation with DynUNet

Marija Habijan, Juraj Perić, Irena Galić

Faculty of Electrical Engineering, Computer Science and Information Technology
Osijek, Croatia