

ALL PVC VENT PIPE PENETRATING R/A SPACES TO BE ENCLOSED BY CHASES. DOMESTIC HOT WATER DOMESTIC COLD WATER SANITARY WASTE AND VENT SERVICE CPVC INSIDE ABOVE GRADE SOL VENT SOL VENT CONNECTION 1/2' ARMAFLEX INSULATION PIPE INSIDE, BELOW GRADE SOL VENT CONNECTION INSULATION SCHEDULE 40 PVC SCHEDULE 40 PVC PIPE SOL VENT SOL VENT DUTSIDE BUILDOUT CONNECTION INSULATION

1/2' ARMAFLEX

EXISTING 3' VENT LINE

REVISIONS

2

3

PIPING MATERIAL LEGEND

NOTE: PROVIDE ENTIRE PIPING

INSULATION TO SYSTEM.


품

٤

(F3)	€ 2	(F1)	TYPE	
FLOOR DRAIN	HAND SINK	WATER CLOSET	DESCRIPTION	FIXTURE SCHEDULE
AMERICAN STANDARD OR APPR. EQUAL	AMERICAN STANDARD OR APPR. EQUAL	AMERICAN STANDARD OR APPR. EQUAL	MODEL	
2	_	_	QTY.	

NEW PLUMBING FIXTURES TO CONNECT TO EXISTING SEWER LINE (VERIFY SIZE & LOCATION IN FIELD) PL 刀 DIAGRAM

NOT TO SCALE **JMBING** <u>고</u> SE



1/2" C.W eclipse

S FE

اِيْ اِيْ

M.A. DRAWN REMODEL SCALE DATE LOCATED AT 8 2302 WHITE OAK В HOUSTON TX

PLUMBING PLAN FOR A PROPOSED

S S B

U

9. VISITING THE SITE: EACH BIDDER SHALL VISIT THE SITE OF THE PROPOSED WORK AND SHALL FULLY INFORM HIMSELF REGARDING THE FACILITIES, NO ADDITIONAL COMPENSATION WILL BE ALLOWED FOR WORK OR MATERIALS OMITTED FROM THE BIDDER'S CONTRACT PROPOSED DUE TO HIS FAILURE TO SO INFORM HIMSELF BE SUCH INVESTIGATION.

11. INSULATE ALL EXPOSED PIPING UNDER LAVATORY WITH TRUEBRO INC. HANDILAV GUARD INSULATION KIT. INSTALL LAVATORY PER HANDICAPPED REQUIREMENT.

10. GUARANTEE ALL WORK AND MATERIALS FURNISHED UNDER CONTRACT FOR A PERIOD OF ONE YEAR FROM THE DATE OF ACCEPTANCE BY THE OWNER AND THE ARCHITECT.

7. THE DIMENSIONS, OR ROUGH-IN DIMENSIONS INDICATED SHALL BE VERIFIED BY CONTRACTOR AND ADJUSTED IF REQUIRED BY EQUIPMENT, AND/OR FIELD CONDITIONS.

6. THE PLUMBING CONTRACTOR SHALL CLOSELY COORDINATE THEIR WORK WITH THE OTHER TRADES TO AVOID CONFLICTS OR OBSTRUCTIONS AND SHALL NOTIFY THE ARCHITECT AND/OR ENGINEER OF

8. SANITARY SEWER SHALL BE LAID AT MIN. SLOPE OF 1/4" PER FOOT SLOPE.

5. THE PLUMBING CONTRACTORS SHALL REMOVE ALL DEBRIS RESULTING FROM THEIR WORK. THEY SHALL ALSO CLEAN ALL FIXTURES AND EQUIPMENT UPON COMPLETION OF HIS WORK AND PRIOR TO FINAL INSPECTION BY THE ARCHITECT AND/OR ENGINEER.

4. ALL WORK SHALL BE SUBJECTED TO ARCHITECTS AND/OR THE ENGINEERS INSPECTION, AND ANY FAULTY WORK, BROKEN FIXTURES, LEAKING PIPES, ETC.. SHALL BE REPAIRED OR REPLACED AT THE PLUMBING CONTRACTORS EXPENSE.

3. ALL PIPING SYSTEMS SHALL BE INSTALLED BY WORKMEN SKILLED IN THIS TRADE AND SHALL BE PROPERLY SUPPORTED HORIZONTALLY AND VERTICALLY.

2. IF THE PLUMBING CONTRACTOR WISHES TO SUBSTITUTE FIXTURES, TRIM, PIPING, OR DRAWING, HE MUST SUBMIT SHOP DRAWINGS OR CUT SHEETS FOR ARCHITECT'S AND/OR OWNERS APPROVAL.

1. THE PLUMBING CONTRACTOR SHALL SECURE ALL PERMITS AND PAY ALL REQUIRED FEE OF HIS PORTION OF THE WORK.

GENERAL PLUMBING NOTES:

- PROPOSE NEW WALK IN COOLER. COOLER FAN TO DRAIN INTO EXISTING DRAIN.

- TO USE EXISTING RESTROOM WATER & SEWER CONNECTIONS TO TAP IN NEW PLUMBING

NOTE

CONTRACTOR TO VERIFY IN FIELD OF THE EXACT LOCATION OF MAIN SEWER LINE AND WATER LINES.

MDP SINK

EXISTING 3 COMP. SINK

®

∌Ѿ

TO CITY MAIN

SCOPE OF WORK:

- REMAINING PLUMBING TO REMAIN AS IS.

SHEET: P-1