

MeasPlan.Name	ET6-Teiler
Name	Frei Waldemar

Fahrzeug	ET323
Kilometerstand	2626436

(YKA) CALIPRI

22.04.2026

Name	11L	11R	12L	12R	13L	13R	14L	14R	42L	42R	41L	41R	52L	52R
Spurkranz Sh	29,77	30,00	29,79	29,90	33,09	33,16	33,15	32,83	32,83	32,92	32,81	32,82	32,82	32,95
Spurkranz Sd	31,05	31,34	31,06	31,23	30,52	30,52	30,58	30,27	30,40	30,38	30,33	30,30	30,29	30,33
Spurkranz qR	11,76	11,89	11,72	11,90	11,16	11,29	11,17	11,16	11,05	11,14	10,99	11,13	11,07	11,21
Raddurchmesser Dlk	902,19	901,70	902,01	901,99	698,95	699,03	702,14	702,74	738,82	739,09	738,84	738,72	737,86	737,75
Bremse Innen BH	2,02	1,54	0,87	1,42	1,49	1,55	1,21	1,20	1,12	0,80	0,69	0,96	0,61	0,45
Bremse Innen Bst	2,15	2,36	3,10	4,12	3,26	3,32	2,49	2,69	5,09	5,07	5,20	5,04	5,07	5,01
Bremse Innen WS	0,13	0,82	2,23	2,70	1,77	1,77	1,28	1,49	3,97	4,27	4,52	4,08	4,46	4,53
Bremse Außen BH	0,58	1,15	0,46	0,54	1,88	1,51	1,36	1,24	1,02	0,73	0,99	0,80	0,36	0,60
Bremse Außen Bst	2,18	3,03	3,23	3,91	3,75	4,02	2,42	2,37	4,95	5,60	5,24	5,15	5,16	5,12
Bremse Außen WS	1,60	1,88	2,77	3,37	1,88	2,51	1,06	1,13	3,93	4,66	4,25	4,35	4,73	4,52
Differenz Durchmesser	0,49	0,49	0,01	0,01	0,08	0,08	0,60	0,60	0,27	0,27	0,12	0,12	0,11	0,11
AR-Radinnenabstand	---	---	---	---	---	---	---	---	---	---	---	---	---	---
SR-Spurmaß	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Name	51L	51R	62L	62R	61L	61R	24L	24R	23L	23R	22L	22R	21L	21R
Spurkranz Sh	32,88	32,88	33,00	32,98	32,95	33,11	32,92	33,07	33,04	32,97	29,52	29,84	29,69	29,96
Spurkranz Sd	30,41	30,31	30,46	30,44	30,42	30,56	30,49	30,59	30,46	30,51	30,90	31,26	31,04	31,37
Spurkranz qR	11,01	11,18	11,11	11,24	11,07	11,24	11,24	11,30	11,10	11,20	11,51	11,79	11,62	11,88
Raddurchmesser Dlk	737,75	737,65	706,72	706,51	706,14	706,52	757,78	758,08	757,74	757,70	903,45	903,23	903,06	903,09
Bremse Innen BH	0,68	0,72	1,40	1,52	1,41	1,84	1,21	1,14	1,26	0,85	0,68	0,75	1,57	1,71
Bremse Innen Bst	5,01	5,03	5,05	4,95	4,83	5,03	3,48	3,38	5,05	5,04	4,99	5,02	3,11	3,23
Bremse Innen WS	4,32	4,30	3,66	3,43	3,42	3,19	2,27	2,24	3,79	4,19	4,31	4,27	1,54	1,52
Bremse Außen BH	0,60	0,44	1,07	2,05	0,49	0,46	0,95	1,08	1,41	1,16	0,57	0,51	1,11	1,09
Bremse Außen Bst	5,12	5,21	5,29	4,85	2,57	3,03	3,11	3,33	4,97	5,06	5,04	5,00	3,09	3,69
Bremse Außen WS	4,51	4,77	4,22	2,80	2,08	2,57	2,16	2,25	3,56	3,90	4,47	4,49	1,99	2,61
Differenz Durchmesser	0,10	0,10	0,20	0,20	0,39	0,39	0,30	0,30	0,04	0,04	0,22	0,22	0,03	0,03
AR-Radinnenabstand	---	---	---	---	---	---	---	---	---	---	---	---	---	---
SR-Spurmaß	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Mittlerer Raddurchmesser ² im DG	Gesamte Beilagendicke Kompensation Radverschleiss je DG:
Laufdrehgestell 760 mm - 725 mm (725+5/0 – 690) mm	0 mm 15 mm
Motordrehgestell 920 mm - 885 mm (885+5/0 – 850) mm	0 mm 15 mm

REDBOX:	
Parameter Aw:Achse 1, 2 = Achse 11 (902,19, 901,70) Bw:Achse 1, 2 = Achse 21 (903,06, 903,09)	SCU Konfiguration Aw: RADDM1 = Achse 13 (698,95, 699,03), RADDM2 = Achse 12 (902,01, 901,99) Bw: RADDM1 = Achse 23 (757,74, 757,70), RADDM2 = Achse 22 (903,45, 903,23)
PZB	
Aw:Achse 13 (698,95, 699,03) Bw:Achse 23 (757,74, 757,70)	