



Motivation and Goal

- Quantitatively understand the correspondence of proxy to parent applications with respect to their underlying node and memory hardware behavior.
- Ensure the system co-design and procurement that proxy application are high fidelity models of the target applications
- Find the most efficient similarity measurement.

Methodology

1. Application representation

- A vector with 700 dimensions (features), each of which is an average rank value for one hardware event.

2. Feature set

- Overall (700 features)
- Subset (subgroup features):
 - Cache-related, e.g., longest_lat_cache.miss
 - Instruction mix
 - Pipeline

3. Distance measurement

- Euclidean distance:

- Cosine similarity

$$\cos \theta = \frac{\sum_{i=1}^n x_i y_i}{\|x\| \|y\|}$$

- Statistic distance:

- Kullback–Leibler divergence

$$D_{KL}(P \parallel Q) = \sum_{x \in \mathcal{X}} P(x) \log \left(\frac{P(x)}{Q(x)} \right)$$

- Jensen-Shannon divergence

$$JSD(P \parallel Q) = \frac{1}{2} D(P \parallel M) + \frac{1}{2} D(Q \parallel M)$$

- Wasserstein distance

$$W_2(p, q) = \sqrt{\min_{P_{XY}} E_{P_{XY}} [\|x - y\|_2^2]} \text{ s. t. } P_X \sim p, P_Y \sim q$$


4. Cluster similar applications

- Hierarchical Clustering
 - Get the similarity by tree branch height to rank applications.

5. Evaluation

- Similarity ranking
- Self similarity

ACKNOWLEDGEMENTS



Experiment

Applications

- ECP Applications in scientific domain of cosmology, seismic modeling, molecular dynamics, and thermal transport.
- 16 apps in proxy/parent pairs and 5 unpaired.

System platform




- Intel Skylake
- IBM Power9
- MPI-only mode, 128 ranks, 1 rank/core, on four nodes.

Data collection

- Collection infrastructure: LDMS
- PAPI sampler collect 700 hardware events performance for each application.
- Run same problem for each application:
 - Use the same input problem and/or parameters.

Result

- Overall feature results of three distance methods in the Skylake system look alike.
- Three apps are generally different from the others.
- Three pairs are the most similar proxy/parent pairs.
- Two pairs (nek5000/nekbone and vite/miniVite) show high similar performance in cosine similarity, and relatively high similar performance in other two methods.
- The last five unpaired applications show relative similarity.
- QMCPack and MiniQMC are similar but differ from other applications.



Conclusion

- Overall ranking show similar result for three distance methods.
- Cross platform show different result because of different memory subsystem and SIMD width.
- Subset results: three subgroups contribute most to the overall similarity matrix.
- Most proxies are good representations of their parents, only with few divergences.
- Cosine similarity is simple, quick and interpretable by geometric angle
- Since other distance methods show similar result, cosine similarity is good enough to use for similarity measurement.

Future work

- Include domain expert evaluation for the choice of distance method.
- Calculate self-similarity for time series data with sliding windows to further validate the similarity methods.
- Validate similarity through measures of latency or some other environmental / real metric.