USE CASE DESCRIPTIONS

MedSentry: Rural Health Unit EHR & Document Management System

Table 3.2: Use Case Description in Sign In Securely (Email & Password)

Process	Sign In Securely (Email & Password)
Description	The user authenticates into MedSentry by providing a registered email address and a valid password. The system validates credentials against the encrypted local store and, for Staff and Admin roles, initiates an OTP challenge before granting access.
Desired Outcome	The user is authenticated and redirected to their role-appropriate dashboard.
Actors	Staff, Admin, Super Admin
Pre-condition	The MedSentry application is running. The user has a registered and active account. An internet connection is available for OTP-required roles.
Scenarios	• Open the MedSentry application • Enter registered email address • Enter account password • Submit credentials • (Staff/Admin) Receive and enter OTP code • Access is granted and dashboard loads

Workflow	`@startuml`
	`start`
	`:User opens MedSentry;`
	`:Enter email and password;`
	`:Click Sign In;`
	`:Verify credentials and OTP;`
	`:Dashboard loaded;`
	`stop`
	`@enduml`

Post-condition	A secure session is established. An audit log entry records the successful login event with timestamp, user ID, and IP.
Business Rule	Credentials must match an active account. After 5 failed attempts, the account is temporarily rate-limited. Super Admin may bypass OTP for local-only access.

Table 3.3: Use Case Description in Verify Email One-Time Password (OTP)

Process	Verify Email One-Time Password (OTP)
Description	After successful password validation, the system sends a time-limited one-time password to the user's registered email. The user must enter this code to complete the two-factor authentication step before session activation.
Desired Outcome	The OTP is validated and the user's session is fully activated with the appropriate role permissions.
Actors	Staff, Admin
Pre-condition	The user has successfully passed the first authentication factor (email + password). A valid email address is associated with the account.
Scenarios	• System sends OTP to registered email • User opens email client and retrieves the code • User enters the 6-digit OTP in the verification panel • System validates the code within the expiry window • Session is activated on success; error displayed on failure

Workflow	`@startuml`
	`start`
	`:System sends 6-digit OTP to email;`
	`:User inputs OTP code;`
	`:Click Verify OTP;`
	`:System validates code and expiry;`
	`:Session successfully activated;`
	`stop`
	`@enduml`

Post-condition	A verified session token is created. The audit log records the OTP verification event. Failed OTP attempts are logged for security auditing.
Business Rule	OTP codes expire after a fixed window (e.g., 10 minutes). Users are allowed a maximum of 5 verification attempts. After exhausting attempts, the user must restart the login process. Resend is blocked during the cooldown period.

Table 3.4: Use Case Description in Quick Unlock (PIN / Biometrics)

Process	Quick Unlock (PIN / Biometrics)
Description	A user whose session was automatically locked due to inactivity may re-enter the application quickly by authenticating with their 4-digit PIN or enrolled biometrics (fingerprint / Windows Hello) instead of repeating the full email and OTP login flow.
Desired Outcome	The session is restored and the user is returned to their last active screen without repeating the full authentication process.
Actors	Staff, Admin, Super Admin
Pre-condition	The user has an existing active session that has been locked due to inactivity. PIN or biometric authentication has been previously enrolled and enabled.
Scenarios	• Session lock screen is displayed • User selects PIN or Biometric unlock method • User enters 4-digit PIN or passes biometric scan • System validates the PIN hash or biometric result • Session is restored on success

Workflow	`@startuml`
	`start`
	`:User views session lock screen;`
	`:Select PIN or Biometric method;`
	`:Enter 4-digit PIN or scan biometric;`
	`:System verifies PIN hash or biometric match;`
	`:Session unlocked to previous screen;`
	`stop`
	`@enduml`

Post-condition	The session is unlocked. An audit event is recorded for the screen unlock action.
Business Rule	PIN unlock is only available for sessions authenticated via a full OTP-verified login. Biometric unlock requires device-level biometric enrollment. Both methods must be explicitly enabled by the user in their security settings.

Table 3.5: Use Case Description in Register & Manage Patient Records

Process	Register & Manage Patient Records
Description	Authorized users create, view, update, and soft-delete patient demographic and clinical records within the RHU's Electronic Health Record system. Records include personal information, contact details, medical history, and consultation notes, all scoped to the user's assigned clinic.
Desired Outcome	A complete and accurate patient record is created or updated in the local encrypted database, ready for document attachment, certificate issuance, and reporting.
Actors	Staff, Admin, Super Admin
Pre-condition	The user is authenticated and has been assigned to a clinic (clinic_id). The patient does not already have a duplicate active record.
Scenarios	• Navigate to the Patient Registry screen • Click "Add Patient" or select an existing record • Fill in or update demographic and clinical details • Save the record • System assigns a unique Patient ID and timestamps the entry

Workflow	`@startuml`
	`start`
	`:User opens Patient Registry;`
	`:Select Add Patient or Edit Record;`
	`:Input patient demographic and medical data;`
	`:Click Save Patient Record;`
	`:Patient record encrypted and saved;`
	`stop`
	`@enduml`

Post-condition	The patient record is persisted locally with AES-256 encryption and queued for Supabase cloud sync. The action is logged in the immutable audit trail.
Business Rule	Patient IDs are auto-generated using the clinic's configured prefix and sequence (e.g., RHU-001). Staff may only access patients within their assigned clinic. Soft-deletion moves records to the archive rather than permanent deletion.

Table 3.6: Use Case Description in Scan, Upload & Categorize Medical Documents

Process	Scan, Upload & Categorize Medical Documents
Description	Users attach scanned or uploaded medical documents (prescriptions, lab results, referral letters, imaging reports) to a specific patient record. Documents are categorized by type, assigned metadata, and stored in the encrypted local document archive.
Desired Outcome	A categorized medical document is successfully attached to the correct patient record and is accessible for authorized review and download.
Actors	Staff, Admin, Super Admin
Pre-condition	The target patient record exists and is active. The user has camera or file-system access on the device.
Scenarios	• Select a patient record • Navigate to the Documents tab • Choose "Scan with Camera" or "Upload from File" • Crop and confirm the document image • Assign document category and metadata • Save and attach to the patient record

Workflow	`@startuml`
	`start`
	`:User opens patient document tab;`
	`:Select Scan Camera or Upload File;`
	`:Crop image and assign document category;`
	`:Click Attach Document;`
	`:Encrypted document saved to patient archive;`
	`stop`
	`@enduml`

Post-condition	The document is stored with an encrypted reference and linked to the patient record. A document entry (with file size, type, date) appears in the patient's document history.
Business Rule	Supported formats include JPEG and PDF. File size is validated against the upload limit. Documents must be assigned a category before saving. Documents inherit the patient's clinic scoping.

Table 3.7: Use Case Description in Issue Health Certificates with Anti-Tamper QR

Process	Issue Health Certificates with Anti-Tamper QR
Description	Authorized users generate official health certificates (Medical Certificate, Barangay Health Clearance, Fit-to-Work, etc.) for a patient. Each certificate is generated from a clinic-branded template and digitally signed with a QR code for anti-tamper verification.
Desired Outcome	A printable or downloadable health certificate is generated with the clinic's official letterhead, patient data, issuing officer details, and an embedded anti-tamper QR code.
Actors	Staff, Admin, Super Admin
Pre-condition	The patient record exists and is active. The clinic's name, address, and official signatories have been configured in the system settings.
Scenarios	• Navigate to the Certificates module • Select a patient • Choose the certificate type • Fill in certificate-specific fields (diagnosis, purpose, validity) • Preview the generated certificate with QR code • Issue and download or print

Workflow	`@startuml`
	`start`
	`:User opens Certificates module;`
	`:Select patient and certificate template;`
	`:Input clinical findings and validity;`
	`:System generates anti-tamper QR code;`
	`:Click Issue and Print Certificate;`
	`stop`
	`@enduml`

Post-condition	An issued certificate record is stored with a unique certificate number, issuance timestamp, and issuing officer's name. The QR code encodes a tamper-evident signature.
Business Rule	Only users with certificate issuance permissions may generate official documents. Certificate numbers are auto-generated and sequential. Issued certificates are immutable after issuance.

Table 3.8: Use Case Description in Generate Census & Morbidity Reports

Process	Generate Census & Morbidity Reports
Description	Authorized users access the Reports & Analytics module to generate and export statistical summaries of patient census data, disease morbidity trends, age-sex distribution, and consultation volume. Reports can be exported as PDF documents.
Desired Outcome	An accurate statistical report is generated reflecting the clinic's health data for a selected time period, ready for submission to health authorities or internal review.
Actors	Staff, Admin, Super Admin
Pre-condition	Patient records exist in the system. The reporting period and filters (date range, diagnosis category) are available for selection.
Scenarios	• Navigate to the Reports & Analytics module • Select reporting type and date range • Apply optional filters (age group, diagnosis, sex) • View real-time visualizations (trendlines, KPI grid, distribution) • Export report as PDF

Workflow	`@startuml`
	`start`
	`:User opens Reports and Analytics;`
	`:Select report type and date range filter;`
	`:System aggregates morbidity and census data;`
	`:Preview visual charts and trendlines;`
	`:Click Export as PDF;`
	`stop`
	`@enduml`

Post-condition	A time-stamped report is generated and available for download. Export actions are recorded in the audit log.
Business Rule	Reports are scoped to the user's assigned clinic. Super Admin may access cross-clinic aggregate reports. Report data reflects the state of the database at the time of generation.

Table 3.9: Use Case Description in Monitor & Trigger Cloud Sync

Process	Monitor & Trigger Cloud Sync
Description	Authorized users view the synchronization status between the local MedSentry database and the Supabase cloud backend. Users may manually trigger a bidirectional sync to resolve pending changes, upload local-only records, or pull updates from the cloud.
Desired Outcome	All pending local changes are successfully synchronized to the cloud, and any server-side updates are pulled into the local database with conflicts identified and resolved.
Actors	Staff, Admin, Super Admin
Pre-condition	The device has an active internet connection. The user is authenticated. There are pending changes in the local sync queue.
Scenarios	• Navigate to the Sync module • Review the sync status dashboard (pending, synced, conflicts) • Tap "Sync Now" to trigger a manual synchronization • Monitor real-time sync progress • Review conflict resolution results

Workflow	`@startuml`
	`start`
	`:User opens Cloud Sync screen;`
	`:Check pending queue and sync status;`
	`:Click Sync Now button;`
	`:System exchanges local and cloud data;`
	`:Sync status updated to complete;`
	`stop`
	`@enduml`

Post-condition	The sync status reflects zero pending items. Sync metadata (last sync timestamp, total records synced) is updated. Sync events are logged in the audit trail.
Business Rule	Automatic sync occurs at system-defined intervals when an internet connection is available. Manual sync can be triggered at any time. Conflict resolution follows a "server-wins" policy unless overridden by an Admin.

Table 3.10: Use Case Description in Manage Personal Profile & Security Credentials

Process	Manage Personal Profile & Security Credentials
Description	Authenticated users view and update their personal profile information including name, PRC license number, specialization, and contact number. Users may also change their password, set up or update their PIN, and manage biometric authentication preferences.
Desired Outcome	The user's profile and security credentials are updated and reflected immediately across the system.
Actors	Staff, Admin, Super Admin
Pre-condition	The user is authenticated with a valid session. The user is accessing their own profile, not another user's.
Scenarios	• Navigate to the Profile screen from the header menu • Edit personal details (name, license, contact) • Change password using the current password + new password flow • Enable or update PIN for screen lock • Save changes

Workflow	`@startuml`
	`start`
	`:User opens My Profile from header menu;`
	`:Edit PRC license or contact details;`
	`:Update account password or configure PIN;`
	`:Click Save Profile Changes;`
	`:User profile and credentials updated;`
	`stop`
	`@enduml`

Post-condition	Updated profile data is saved locally and queued for cloud sync. Password and PIN changes take effect immediately. Profile update events are recorded in the audit log.
Business Rule	Users may only modify their own profile. Password changes require the current password to be verified first. PIN must be 4 digits. Profile changes do not affect the user's role or clinic assignment.

Table 3.11: Use Case Description in Provision & Manage RHU Staff Accounts

Process	Provision & Manage RHU Staff Accounts
Description	Admin and Super Admin users create, view, update, deactivate, and delete staff user accounts within their authorized scope. This includes assigning roles (Staff, Admin), setting clinic assignments, and resetting user credentials when needed.
Desired Outcome	A staff account is successfully created, updated, or deactivated, with role and clinic permissions correctly configured and immediately effective.
Actors	Admin, Super Admin
Pre-condition	The actor has a minimum role of Admin. For Admins, actions are scoped to their own clinic. Super Admin may manage users across all clinics.
Scenarios	• Navigate to the Staff Management screen • Click "Add Staff" or select an existing account • Enter staff details (name, email, role, clinic) • Set initial credentials • Save the account • Optionally deactivate or delete an account

Workflow	`@startuml`
	`start`
	`:Admin opens Staff Management;`
	`:Select Add or Edit Staff;`
	`:Input staff account details;`
	`:Click Save Account;`
	`:Staff list updated;`
	`stop`
	`@enduml`

Post-condition	The staff account is created or updated in the local database and synced to the cloud. The new user may log in using the assigned credentials. Account provisioning events are recorded in the audit log.
Business Rule	Admin users may only manage Staff-role accounts within their own clinic. Super Admin may create Admin-level accounts. Email addresses must be unique across the system. Deactivated accounts cannot log in but their data is retained.

Table 3.12: Use Case Description in Configure RHU Clinic Settings & Letterhead

Process	Configure RHU Clinic Settings & Letterhead
Description	Admin users configure their assigned clinic's operational details including clinic name, address, contact numbers, official letterhead logo, signatory name and designation, and certificate issuance settings. These configurations are applied to all generated certificates, reports, and printed documents.
Desired Outcome	The clinic's official identity and operational settings are saved and immediately reflected in all subsequent document and certificate outputs.
Actors	Admin, Super Admin
Pre-condition	The actor has Admin or Super Admin role. The clinic record has been provisioned in the system.
Scenarios	• Navigate to Settings > Clinic Configuration • Update clinic name, address, and contact information • Upload clinic logo for letterhead • Set signatory name and designation • Configure patient ID prefix and sequence • Save settings

Workflow	`@startuml`
	`start`
	`:Admin opens Clinic Configuration in Settings;`
	`:Update clinic contact info and address;`
	`:Upload clinic logo and set signatories;`
	`:Click Save Clinic Settings;`
	`:Official templates updated with new branding;`
	`stop`
	`@enduml`

Post-condition	Updated clinic settings are persisted locally and synced to the cloud. All certificates and reports generated after the update use the new letterhead and signatory information.
Business Rule	Admin users may only configure their own assigned clinic. Super Admin may configure any clinic. Logo uploads must conform to supported image formats and size limits. Patient ID sequence cannot be reset below the current highest issued ID.

Table 3.13: Use Case Description in Manage Archive & Record Recovery

Process	Manage Archive & Record Recovery
Description	Authorized users view soft-deleted (archived) patient records. Records can be restored to active status or permanently deleted from the archive. This module ensures compliance with data retention policies while providing a safety net against accidental deletion.
Desired Outcome	Archived patient records are either successfully restored to the active patient registry or permanently removed from the system according to the authorized user's decision.
Actors	Admin, Super Admin
Pre-condition	One or more patient records have been previously soft-deleted and moved to the archive. The actor has at minimum Admin privileges.
Scenarios	• Navigate to the Archive & Recovery module • Search or browse archived patient records • Select a record to restore or permanently delete • Confirm the action in a dialog prompt • System executes the action

Workflow	`@startuml`
	`start`
	`:Admin opens Archive and Recovery;`
	`:Search archived patient records;`
	`:Select Restore or Delete Permanently;`
	`:Confirm security prompt;`
	`:Patient record restored or expunged;`
	`stop`
	`@enduml`

Post-condition	Restored records re-appear in the active patient registry with their full history intact. Permanently deleted records are expunged from both local storage and the cloud sync queue. All archive actions are logged in the audit trail.
Business Rule	Permanent deletion is irreversible and requires a second-factor confirmation dialog. Admin users may only manage archives within their clinic scope. Records with pending issued certificates cannot be permanently deleted.

Table 3.14: Use Case Description in View & Filter RHU Audit Logs

Process	View & Filter RHU Audit Logs
Description	Admin and Super Admin users access the immutable audit log to review a chronological record of all system events including user logins, data modifications, document operations, certificate issuances, sync events, and administrative actions.
Desired Outcome	The authorized user retrieves a filtered and chronologically ordered view of audit events relevant to their compliance, security, or investigative needs.
Actors	Admin, Super Admin
Pre-condition	The actor has Admin or Super Admin role. Audit log entries have been generated by prior system activity.
Scenarios	• Navigate to the Audit Logs screen • Apply filters (action type, user, date range, patient ID) • Browse or search log entries • Review event details (timestamp, user, action, affected record)

Workflow	`@startuml`
	`start`
	`:Admin opens Audit Logs screen;`
	`:Filter by action type, staff ID, or date;`
	`:System queries immutable audit repository;`
	`:Review chronological event trail and IP;`
	`:Audit inspection completed;`
	`stop`
	`@enduml`

Post-condition	Audit log data is displayed without alteration. Viewing the audit log does not itself generate a new audit entry. Audit data is read-only and cannot be modified or deleted by any user.
Business Rule	Audit logs are immutable — no user, including Super Admin, may edit or delete log entries. Admin users may only view audit logs for events within their clinic. Logs must be retained in accordance with RA 10173.

Table 3.15: Use Case Description in Orchestrate Multi-RHU Facilities

Process	Orchestrate Multi-RHU Facilities
Description	The Super Admin manages the complete portfolio of Rural Health Unit facilities registered in MedSentry. This includes adding new clinic entities, updating facility profiles, viewing KPI summaries per clinic, and monitoring the active/inactive status of each facility.
Desired Outcome	A new clinic facility is successfully registered in the system or an existing facility's profile is updated, with changes reflected across all scoped views and role assignments.
Actors	Super Admin
Pre-condition	The actor is authenticated as Super Admin. The facility to be added has a unique identifier not already registered in the system.
Scenarios	• Navigate to the RHU Management screen • Click "Add Facility" or select an existing clinic • Enter facility name, address, contact, and region details • Set facility as Active or Inactive • Save facility record

Workflow	`@startuml`
	`start`
	`:Super Admin opens RHU Management;`
	`:Click Add Facility or select clinic;`
	`:Input facility details and clinic code;`
	`:Click Save Facility;`
	`:New clinic provisioned in system;`
	`stop`
	`@enduml`

Post-condition	The new clinic record is persisted and available for Admin assignment, patient scoping, and reporting. Facility creation and modification events are logged in the audit trail.
Business Rule	Only Super Admin may create or deactivate clinic facilities. Deactivated facilities retain all their historical data but prevent new logins and patient registrations under that clinic. Each facility must have a unique clinic code.

Table 3.16: Use Case Description in Manage Global Staff & Facility Reassignment

Process	Manage Global Staff & Facility Reassignment
Description	The Super Admin views all staff accounts across all RHU clinics and may reassign a staff member or Admin from one facility to another. This includes updating the user's clinic_id scope, adjusting role levels if required, and ensuring data access is updated accordingly.
Desired Outcome	A staff member's clinic assignment is successfully updated and their access is immediately restricted to the records and data of the new assigned facility.
Actors	Super Admin
Pre-condition	Both the source and target clinic facilities exist and are active. The staff member being reassigned has an active account.
Scenarios	• Navigate to Staff Management (Super Admin view) • Search and select the staff member to reassign • Change the assigned clinic from the dropdown • Optionally adjust the user's role level • Confirm and save the reassignment

Workflow	`@startuml`
	`start`
	`:Super Admin opens global staff directory;`
	`:Select staff member across clinics;`
	`:Choose new clinic from assignment dropdown;`
	`:Click Confirm Reassignment;`
	`:Staff reassigned and session re-scoped;`
	`stop`
	`@enduml`

Post-condition	The staff member's clinic_id is updated. Their active session (if any) is invalidated and they are required to log in again under the new clinic scope. The reassignment event is recorded in the audit log.
Business Rule	Clinic reassignments invalidate the user's current session for security. A staff member may only be assigned to one clinic at a time. Super Admin is the only role authorized to perform cross-clinic reassignments.

Table 3.17: Use Case Description in Configure Platform Branding & System Security

Process	Configure Platform Branding & System Security
Description	The Super Admin configures global system-level settings including the platform's application name, master branding identity (logo, accent theme), system-wide security policies (password minimum length, session inactivity timeout), and global infrastructure parameters.
Desired Outcome	Platform branding and security policies are updated and applied system-wide, immediately affecting all users' login screen presentation and enforced security behaviors.
Actors	Super Admin
Pre-condition	The actor is authenticated as Super Admin. The system settings module is accessible.
Scenarios	• Navigate to Settings > Platform Settings & System Configuration • Update application name and organization name • Upload a new platform logo • Set password minimum length and complexity policy • Configure inactivity timeout duration • Save platform settings

Workflow	`@startuml`
	`start`
	`:Super Admin opens Platform Configuration;`
	`:Update application title and master logo asset;`
	`:Set password policy and session timeout threshold;`
	`:Click Save Platform Settings;`
	`:Settings propagated system-wide;`
	`stop`
	`@enduml`

Post-condition	Updated platform settings are persisted and immediately visible on the login screen and throughout the application. Security policy changes take effect for subsequent password update actions.
Business Rule	Only Super Admin may modify platform-level branding and security configurations. Password policy changes do not retroactively invalidate existing passwords but are enforced at the next password change event.

Table 3.18: Use Case Description in Inspect System-Wide Security Audits

Process	Inspect System-Wide Security Audits
Description	The Super Admin accesses a consolidated, cross-clinic audit log view covering all facilities in the MedSentry platform. This enables system-wide security monitoring including detection of unauthorized access attempts, suspicious activity patterns, and compliance verification across all RHU units.
Desired Outcome	The Super Admin obtains a comprehensive and cross-clinic audit report identifying system-wide events for security review, regulatory compliance, and incident investigation.
Actors	Super Admin
Pre-condition	The actor is authenticated as Super Admin. Audit log data has been generated across one or more clinic facilities.
Scenarios	• Navigate to Audit Logs (Super Admin cross-clinic view) • Select "All Clinics" or filter by specific facility • Apply action-type and date filters • Identify anomalous or critical events (failed logins, mass deletes) • Export or review the filtered audit entries

Workflow	`@startuml`
	`start`
	`:Super Admin opens cross-clinic audit viewer;`
	`:Filter logs across all registered RHUs;`
	`:Inspect login failures and data deletion spikes;`
	`:Export audit report for compliance check;`
	`:System-wide audit review complete;`
	`stop`
	`@enduml`

Post-condition	Audit data is presented in a consolidated read-only view. No entries are modified. The Super Admin's access to the audit module may itself be recorded as an audit event for oversight.
Business Rule	System-wide audit access is exclusive to Super Admin. Audit data is read-only and immutable for all users. Cross-clinic data aggregation is governed by RA 10173 data privacy compliance requirements.

Table 3.19: Use Case Description in Manually Lock Screen

Process	Manually Lock Screen
Description	An authenticated user manually locks their MedSentry session to immediately prevent unauthorized access to the application while stepping away from the workstation. The session lock screen is displayed, requiring PIN, biometric, or full credential re-entry to resume.
Desired Outcome	The active session is immediately locked and all sensitive data is hidden behind the lock screen, preventing access without re-authentication.
Actors	Staff, Admin, Super Admin
Pre-condition	The user is authenticated with an active session. The application is open and in the foreground.
Scenarios	• User clicks the "Lock Screen" button from the profile menu or shortcut • System immediately displays the session lock screen • All active views are hidden • User must re-authenticate with PIN, biometrics, or full login to resume

Workflow	`@startuml`
	`start`
	`:User clicks Lock Screen in profile menu;`
	`:System hides active application interface;`
	`:Display session lock screen;`
	`:User enters 4-digit PIN or biometrics to resume;`
	`:Active workstation session restored;`
	`stop`
	`@enduml`

Post-condition	The session lock state is persisted. The lock event is recorded in the audit log with a timestamp. The user's data and last screen state are preserved but hidden pending re-authentication.
Business Rule	Session locking is instantaneous and does not require any network connection. The system also applies automatic locking after a configurable inactivity timeout. During the locked state, no data is accessible or exported.

Table 3.20: Use Case Description in Sign Out Securely

Process	Sign Out Securely
Description	An authenticated user explicitly terminates their active MedSentry session. The system clears all session tokens, cached credentials, and sensitive in-memory data, then returns the user to the login screen.
Desired Outcome	The user's active session is fully terminated, all sensitive data is cleared from memory, and the application returns to the login screen ready for a fresh authentication.
Actors	Staff, Admin, Super Admin
Pre-condition	The user is authenticated with an active session.
Scenarios	• User opens the profile menu from the application header • User clicks "Sign Out" • System presents a confirmation prompt • User confirms sign-out • Session tokens are invalidated and cleared • Application returns to the login screen

Workflow	`@startuml`
	`start`
	`:User clicks Sign Out in header menu;`
	`:Confirmation prompt displayed;`
	`:Click Confirm Sign Out;`
	`:Purge session tokens and in-memory cache;`
	`:Redirected to login screen;`
	`stop`
	`@enduml`

Post-condition	The session is fully terminated. A logout event is recorded in the immutable audit log with the timestamp and user ID. If cloud connectivity is available, the remote session is also invalidated.
Business Rule	Sign-out is permanent and cannot be undone. Any unsaved changes in open forms are discarded upon sign-out. If the user had "Remember Me" enabled, only the email address is retained — no passwords or tokens are stored post-logout.