

M15 — Cohort debrief UI

Phase: 9 — Debrief **Status:** DONE (2026-05-26) **Blocked by:** M14 **Blocks:** none **Estimated effort:** 2 days · **Actual:** 0.5 day

1. Purpose

Render the M14 cohort debrief JSON as an instructor-facing web page with PEARLS-section tabs (Reactions / Description / Analysis / Application / Per-encounter / Summary), live-editable notes + commitments, and a Print-to-PDF affordance. Also wire POST `/api/room/end` to **save** the cohort debrief before the singleton is cleared, so the debrief survives the end.

2. Structure

New files:

- `portal/templates/debrief_cohort.html` — PEARLS-tabbed render of one cohort.
- `portal/templates/debrief_cohort_index.html` — list of every saved cohort.
- `portal/static/debrief_cohort.{js,css}` — tab switching, commitments editor, save-notes round-trip, print-friendly CSS.

Files touched:

- `portal/server.py`:
- POST `/api/room/end` now calls `debrief_mod.build_cohort_debrief(room) + save_cohort(...)` BEFORE `end_active_room()`. Response carries `cohort_debrief_saved` and `cohort_debrief_url`.
- New routes: - GET `/portal/debrief/cohort/{room_id}` — HTML render. - GET `/api/debrief/cohort/{room_id}` — JSON read. - POST `/api/debrief/cohort/{room_id}/notes` — save instructor notes + commitments. - GET `/portal/cohort-debriefs` — index page (path is plural, top-level, to avoid colliding with the `v6 /portal/debrief/{session_id}` catch-all).

3. Uses

- **Operator ends a room** via M5 dashboard's End Room button → `/api/room/end` saves the cohort + clears singleton → response carries `cohort_debrief_url` for client-side redirect.
- **Operator opens a saved cohort debrief** via the M5 dashboard's Cohort Debrief button (when `lastKnownRoomId` is set) OR via the `/portal/cohort-debriefs` index.
- **Instructor edits notes + commitments live** during the PEARLS-led debrief → POST `.../notes` persists.
- **Print/Save-as-PDF** — browser-native print, with CSS that

forces every PEARLS panel visible and expands every encounter facet.

4. Functions (exported API surface)

HTTP routes

Method	Path	Returns
GET	/portal/debrief/cohort/{room_id}	HTML cohort debrief view, 404 if not saved
GET	/api/debrief/cohort/{room_id}	JSON read of the saved cohort, 404 if not saved
POST	/api/debrief/cohort/{room_id}/notes	Save {reactions_notes, commitments[]}
GET	/portal/cohort-debriefs	Index page (newest first)
POST	/api/room/end (updated)	{ok, room_id, encounter_count, cohort_debrief_saved, cohort_debrief_url}

Template structure

PEARLS tabs in this order, each as a `<section class="pearls-panel">`: 1. **Reactions** — editable textarea for instructor notes. 2. **Description** — pre-built cohort facts list. 3. **Analysis** — per-encounter performance frame table + persona engagement ranked list. 4. **Application** — commitment editor (add / remove items live). 5. **Per-encounter** — collapsible facet panels with transcript preview. 6. **Summary** — room-level aggregates.

5. Limitations

- **No PDF export server-side.** Print is browser-driven (Ctrl+P /

■+P → Save as PDF). A server-side PDF render would need WeasyPrint or similar — deferred.

- `/portal/cohort-debriefs` **lives at a top-level path** (not

`/portal/debrief/cohort`) because the v6 `/portal/debrief/{session_id}` catch-all would have caught "cohort" as a session id lookup. Documented in module guide §8.

- **Commitments editor doesn't save automatically** — the

instructor must click "Save notes" to persist both Reactions notes and the commitments list. M21 LAN test should verify this is intuitive.

- **No per-encounter drill-in beyond transcript preview.** The

encounter facets show the first 50 transcript entries; longer runs get truncated with a "... N more entries" hint. M21 feedback may suggest expanding this.

- ****Index page is unsorted within the "saved cohorts" list beyond**

`generated_at desc`.** No filter by date / instructor / activity. Deferred until the catalog grows past a screen's worth.

6. Test status

`tests/v7/test_cohort_debrief_route_renders_for_ended_room.py` — 6 cases:

Test	Status
test_end_room_saves_cohort_debrief	PASS
test_cohort_debrief_route_renders_for_ended_room	PASS
test_cohort_debrief_route_404s_for_unknown_room	PASS
test_cohort_debrief_json_endpoint_returns_data	PASS
test_cohort_debrief_save_notes_round_trips	PASS
test_cohort_debrief_index_renders	PASS

Full v7 suite: 104/104 passing (up from 98 — +6 M15 tests). **Full v6 regression on v7: 215 passed**, same 6 env-flaky pre-existing failures, **0 v7 regressions**.

7. Change list

Date	Author	Change	Files
2026-05-26	claude-code	POST /api/room/end now saves cohort debrief before clearing singleton (response carries cohort_debrief_url). 4 new routes for cohort debrief view + JSON read + notes save + index. New debrief_cohort.html, debrief_cohort_index.html, debrief_cohort.{js,css}. 6 acceptance tests pass. Index route at /portal/cohort-debriefs (plural top-level) to avoid v6 catch-all collision.	portal/server.py, portal/templates/debrief_cohort.html, portal/templates/debrief_cohort_index.html, portal/static/debrief_cohort.{js,css}, tests/v7/test_cohort_debrief_route_renders_for_ended_room.py

8. Open questions / known issues

- **Route-collision pattern revisited.** v6's

/portal/debrief/{session_id} is greedy. Future v7 modules that add new debrief subroutes should use a non-conflicting path prefix.

- **The M5 dashboard's Cohort Debrief button** points at

/portal/debrief/cohort/{room_id} (correct — the GET works). Need to verify the M5 button is reachable AFTER end_room (M5 preserves lastKnownRoomId exactly so this could work). Browser preview verification deferred.

- **Print CSS forces every panel visible**, which is the right

behavior for instructor archival but bloats the printed page on long-running rooms. A "compact" toggle could help.