

M34 — Per-encounter instructor EHR launch button

Phase: Phase 7 follow-on (post-M33, operator-feedback fix) **Status:** **DONE** **Blocked by:** M2 (Encounter dataclass is a ControlSession), M22 (Per-Patient Console scaffold), M31 (per-encounter ehr_id) **Blocks:** none **Estimated effort:** 0.5 day

1. Purpose

Operator feedback after M33:

"I need to be able to launch and access the medical records from the encounter page as the instructor, and launch the system into a new window."

The Per-Patient Console at `/portal/room/encounter/{id}` had every instructor surface for a bed *except* a direct EHR launch. The existing v6 route `/portal/control/launch_ehr` doesn't work in multi-encounter rooms — it calls `control_session.get_active()` which (per the M2 contract fix) returns `None` whenever the active room has more than one encounter, dropping the instructor back at the wizard.

M34 adds a v7-aware twin keyed to a specific encounter, and a prominent **■ Open EHR ({ehr_id})** button in the console header that opens that route in a new browser tab. A second discovery point lives inside the QR-codes card under the EHR station cell: **■ Open EHR on this device** — for instructors who arrive at the QR card looking for how to get the chart up.

Both links use `target="_blank" rel="noopener"`, so the instructor keeps the Per-Patient Console open on one monitor while the EHR chart opens on another.

2. Structure

Files touched:

- `portal/server.py` — two new routes near the existing

`control_launch_ehr_get/post`: - GET `/portal/room/encounter/{encounter_id}/launch_ehr` — 303 redirect into `/ehr/{join_code}/{station_id}` after registering (or reusing) a control-room EHR station for that encounter. Reuses the existing `_launch_ehr_station(sess)` helper verbatim — the v7 Encounter dataclass *is* a `ControlSession` (M2 rename, not a re-implementation), so the helper accepts it as-is. - POST `/portal/room/encounter/{encounter_id}/launch_ehr` — JSON `{ok, url, ehr_id, station_id, encounter_id, reused}` flavor for programmatic callers.

- `portal/templates/encounter_console.html` —

- Header now carries either a green primary `<a id="btn-launch-ehr">`

action linking to the launch route (with `target="_blank"`), or a disabled `<span>` when the encounter has no EHR configured. - QR card's EHR cell carries a **■ Open EHR on this device** link (`.qr-launch-here`) for inline discovery.

- `portal/static/encounter_console.css` — `.header-action` (green

CTA) + `.header-action-disabled` (muted gray) + `.qr-launch-here` styles.

No schema migration. No dataclass change. The encounter `.ehr_id` field has existed since M2.

3. Uses

3.1 Instructor flow

1. Instructor lands on `/portal/room/encounter/{id}` (the Per-Patient Console for one bed). 2. Header renders a green **■ Open EHR (helix)** anchor (or whichever `ehr_id` is configured) — assuming the row has an EHR picked. Otherwise renders a muted **■ No EHR configured** state with a tooltip pointing back at the wizard. 3. Click → GET `/portal/room/encounter/{id}/launch_ehr` opens in a new tab. 4. Server resolves the encounter from `_require_active_room().encounters`, calls `_launch_ehr_station(enc)`: - First time: creates a new ES-`{token}` station, attaches it to the encounter + writes through `ehr_db.register_station`. - Repeat call: finds the still-online station whose `device_label == "Control room (instructor)"` and reuses it (no station pile-up on repeated clicks). 5. 303 → `/ehr/{join_code}/{station_id}` — the unified EHR bundle loads. Same template + JSX the student-joined EHR stations use (`portal/ehr/_core/index.html + ehr_app.jsx`), themed by the bootstrap JSON's `EHR_ID`.

3.2 Side-by-side workflow

`target="_blank" rel="noopener"` means the EHR opens in its own browser tab; the instructor can drag it to a second monitor and keep the Per-Patient Console + EHR side by side. This was the explicit operator ask — "launch the system into a new window".

3.3 The QR card discovery path

The QR card's EHR cell still shows the student-facing QR + join URL, but adds a green **■ Open EHR on this device** link underneath. So an instructor who walks the QR card looking for "how does the chart open" finds the button right where they're already looking.

4. Functions (exported API surface)

Symbol	Where	Purpose
GET <code>/portal/room/encounter/{id}/launch_ehr</code>	<code>portal/server.py</code>	303 redirect into the EHR bundle for THIS encounter. Falls back to console with <code>?ehr=unconfigured</code> when no EHR is configured.
POST <code>/portal/room/encounter/{id}/launch_ehr</code>	<code>portal/server.py</code>	JSON <code>{ok, url, ehr_id, station_id, encounter_id, reused}</code> . 409 when no EHR; 404 when encounter is unknown.
<code>_launch_ehr_station(sess)</code>	<code>portal/server.py</code>	(existing, M9-era) Register or reuse the control-room EHR station for a given <code>ControlSession/Encounter</code> . Reused verbatim.

5. Limitations

- **Header label hard-codes the `ehr_id` string** (e.g. "Open EHR

(helix)"). The EHR name from the `ehrs` catalog (e.g. "Helix EMR") would read nicer; the encounter dataclass only carries the short id today. A future M35 could pass the catalog entry down.

- **Repeat-launch reuses the station only while it is online.**

If the instructor closes the EHR tab and the heartbeat times out, the next launch will allocate a fresh ES- station instead of reviving the old one. That's the M9 contract — `_launch_ehr_station` scans `sess.ehr_stations.values()` filtering `s.online`. Acceptable for instructor stations; we don't surface

them in the cohort debrief facets anyway.

- **No popup-blocker fallback.** The header button is an `<a>` with

`target="_blank"`, which all major browsers allow as a direct user gesture. We are not using `window.open` from JS, so popup blockers don't see this as a popup. No fallback path needed.

- **Disabled state still shows even when the encounter is frozen.**

If we ever want to grey out the launch action mid-freeze, we'd add an `encounter.state == "frozen"` check in the template. Out of scope today — freezing pauses input but does not lock the chart.

6. Test status

Test file	Asserts	Status	Last run
<code>tests/v7/test_encounter_launch_ehr.py::test_per_encounter_launch_ehr_redirects_to_chart</code>	GET returns 303 → <code>/ehr/{join}</code> / <code><ES-...></code>	PASS	2026-05-27
<code>...::test_per_encounter_launch_ehr_post_returns_url_json</code>	POST returns <code>{ok, url, ehr_id, station_id, encounter_id, reused}</code>	PASS	2026-05-27
<code>...::test_per_encounter_launch_ehr_reuses_station_on_repeat</code>	Second launch returns same <code>station_id</code> + <code>reused=true</code>	PASS	2026-05-27
<code>...::test_per_encounter_launch_ehr_no_ehr_redirects_to_console</code>	GET → 303 back to console with <code>?ehr=unconfigured</code> ; POST → 409	PASS	2026-05-27
<code>...::test_per_encounter_launch_ehr_unknown_encounter_returns_404</code>	Unknown encounter id → 404 on both methods	PASS	2026-05-27
<code>...::test_console_header_renders_open_ehr_button</code>	Header has <code>#btn-launch-ehr</code> linking to the route, <code>target=_blank</code> , label mentions <code>ehr_id</code>	PASS	2026-05-27
<code>...::test_console_header_shows_disabled_state_when_no_ehr</code>	No-EHR encounter → header shows muted "No EHR configured" span instead	PASS	2026-05-27
<code>...::test_qr_card_shows_open_ehr_on_this_device_link</code>	QR card carries the inline <code>.qr-launch-here</code> link	PASS	2026-05-27

Test file	Asserts	Status	Last run
Full v7 suite	217 passed, 1 skipped (M20 Playwright skip — unchanged)	PASS	2026-05-27

7. Change list

Date	Author	Change	Files
2026-05-27	claude-code	Initial M34 implementation: GET+POST per-encounter launch_ehr routes; header button + disabled state; QR-card inline link; CSS; 8 new tests	portal/server.py, portal/templates/encounter_console.html, portal/static/encounter_console.css, tests/v7/test_encounter_launch_ehr.py (new)

8. Open questions / known issues

- **Should the launch route honor `private_clone` chart mode?**

Today it launches the instructor against the template encounter's chart. If the bed is in `private_clone` mode, each student has their own clone — the instructor's launch hits the template, not any one student's chart. That matches the v6 ops-view behavior but may surprise a new instructor. Tracked as a potential M35 follow-up: optionally let the launch button pick a clone.

- **Disabled state copy is operator-friendly but not actionable.**

We could turn the disabled span into a link to the wizard with the encounter id pre-selected — but only if the room is still in setup state, which after `/api/room/start` is never. So a configured-after-start workflow would need a "change EHR for this bed" surface (out of scope).

- **The `?ehr=unconfigured` query hint is set but not consumed.**

The console JS does not display a toast for it today. Adding one is a 10-line change; deferred until an instructor actually trips the case in practice.

Render this guide to PDF with `python docs/module_guides/render_pdfs.py`.