

that patient (back-compat with pre-M55 carts).

- `persona_id` in `active_medications` → cart shows ONLY the meds whose lowercased name is in the list. Empty list = no meds for that patient.
- No schema migration — in-memory only. Dies with the server.

2.3 API

Three new routes under existing instructor / vault guards:

Method	Route	Purpose
GET	<code>/api/encounter/{eid}/medications</code>	List every persona's seed MAR + active flag per med + <code>explicit_active_list</code> flag per persona.
POST	<code>/api/encounter/{eid}/medications/active</code>	Body <code>{persona_id, active_med_names: [...]}</code> — replace ONE persona's active list.
DELETE	<code>/api/encounter/{eid}/medications/active/{persona_id}</code>	Reset one persona to default (every med shows).

POST normalizes the list: `str(n).strip().lower()`. Whitespace and case insensitive on lookup so "Furosemide" matches "furosemide".

2.4 Med-cart bootstrap filter

`portal/devices/routes.py` — the cabinet bootstrap that builds `characters[]` for the cart UI was previously returning every med from `seeds_for_all_personas(enc)`. M55 inserts a filter:

```
for c in per_enc:
    pid = c.get("character_id") or ""
    if pid in active_map:
        active_lower = set(active_map.get(pid) or [])
        c["medications"] = [
            m for m in (c.get("medications") or [])
            if (m.get("name") or "").strip().lower() in active_lower
        ]
    # ... still tag with encounter_id + encounter_label
```

When the persona has no explicit list, the cart sees the full med list. The cart UI doesn't need to change — it just receives a smaller list.

3. Files touched

Modified

- `portal/control_session.py` — `active_medications: dict[str, list[str]] = field(default_factory=dict)` on `ControlSession`.
- `portal/server.py` — 3 new routes (GET `/api/encounter/{eid}/medications`, POST `/api/encounter/{eid}/medications/active`, DELETE `/api/encounter/{eid}/medications/active/{persona_id}`).

- `portal/devices/routes.py` — cabinet bootstrap filter against `enc.active_medications` per persona.
- `portal/templates/encounter_console.html` — new collapsible "■ Medications" card.
- `portal/static/encounter_console.js` — `wireMedsToggle`, `bootMedications`, `renderMedications`, `onMedToggle`, `onMedReset` + `cssEscape` helper.
- `portal/static/encounter_console.css` — `.meds-card` + `.meds-persona` + `.meds-row` + collapsed-state rules.

New

- `tests/v7/test_medications_active.py` — 13 acceptance tests.
- `docs/module_guides/M55_medications_active_at_start.{md,pdf}` — this guide.

4. Acceptance

Source: `tests/v7/test_medications_active.py` (13 tests).

1. **Dataclass** — `ControlSession.active_medications` defaults to `{}`. 2. **GET endpoint** — returns personas + seed MARs; `explicit_active_list=False` until first operator interaction; every med has `active=True` by default. 3. **POST** — sets the explicit list; subsequent GET reports `explicit_active_list=True` and flips the active flag accordingly. Empty list = "no meds active" (different from default-all). 4. **DELETE** — resets one persona to default; subsequent GET reports `explicit_active_list=False` again. 5. **Cart filter** — after POSTing an active list, the M47 cabinet bootstrap returns only the listed med under that patient. Without a POST, every med still appears (back-compat preserved). 6. **Encounter console** — template renders `id="card-medications"` with `meds-collapsed` class, `id="meds-toggle"` with `aria-expanded="false"` + `aria-controls="meds-body"`, caret marker, body section. 7. **JS handlers** — `wireMedsToggle`, `bootMedications`, `renderMedications`, `onMedToggle`, `onMedReset` all present; hit `/medications` + `/medications/active` routes; Enter/Space keyboard accessibility. 8. **CSS** — `.meds-card.meds-collapsed` `.meds-body` hides body; `.meds-persona` + `.meds-row` + `.meds-high-alert` styling.

All 13 pass. Full v7 suite **458 passed, 1 skipped, 0 regressions** (was 445 pre-M55).

5. Operator demo

1. Open a multi-patient room with 2-3 encounters. 2. Drill into one encounter (`/portal/room/encounter/{id}`). 3. The new ■ ■ **Medications** card sits between Devices and Network/QR. Click the header — it expands, listing every persona on this encounter with their full seed MAR. All boxes are ticked (default). 4. Untick a med (say, Atorvastatin). The persona's status badge flips from "default — all active" to "explicit list". 5. Open the M47 med cart (linked to this encounter). Atorvastatin is gone from this patient's section; the other meds remain. 6. Click ■ Reset on the persona. Atorvastatin reappears on the cart on the next refresh.

6. Notes / future hooks

- **No schema migration.** `active_medications` is in-memory only;

dies with the server. Same lifecycle as the M30 `lead_student_id` and M53 `lead_label`. If the operator wants persistence across restarts, a schema-v6 migration would add a JSON column to `control_session` (out of scope here).

- **No bulk-apply UI** like M53's lead-assignments. If the operator needs to mark the same med active across N beds, a bulk endpoint could land later — the route signature would mirror `/api/room/lead_assignments(assignments[] with encounter_ids[])`.
- **Match is by name**, lowercase + stripped. The `med_id` from the seed isn't used (it's not stable across re-seeds; we considered it and rejected). If the seed library ever introduces two meds with the same name on one patient, the filter would treat them as one — the seed builder de-duplicates today so this is fine.
- **MAR display** on the cart is unchanged otherwise — dose, route, frequency, `high_alert`, `current_status`, etc. all flow through from the seed. M55 just filters which rows survive.
- **No chart-event** is written when the operator toggles a med.
This is a configuration step before the scenario starts, not a clinical action. If the operator wants an audit trail (who toggled what when), wrap the POST handler in `ehr_db.append_event(type="meds.active_set", ...)`.

Closes: the operator's M55 ask in full.