Halcyon Product Selection Guide 2025

Halcyon Micro — fictional company, synthetic document

A quick comparison of the Halcyon Micro catalogue. See each part's datasheet for full specifications and conditions.

Selection table

Part	Function	Supply range	Interface	Package	Temperature range
HM3300	3.3 V LDO regulator, 500 mA	2.5 V to 6.0 V	EN pin	SOT-23-5 / DFN-6	–40 °C to 125 °C
HM5V-PD	USB-C PD 3.0 sink controller	VDD 3.0 V to 5.5 V	I²C (0x28 / 0x29)	QFN-24	–40 °C to 105 °C
HT410	Digital temperature sensor, ±0.5 °C	1.7 V to 3.6 V	I²C (0x48–0x4B)	SOT-563	–40 °C to 125 °C
HB7	BLE 5.3 module, +8 dBm	1.8 V to 3.6 V	SPI / I²C / UART	Module 9.5×12.5 mm	–40 °C to 85 °C
HMD12	Dual H-bridge motor driver, 2.5 A	VM 4.5 V to 18 V	SPI	TSSOP-20 (EP)	–40 °C to 125 °C
HIMU6	6-axis IMU	1.71 V to 3.6 V	I²C (0x6A / 0x6B) / SPI	LGA-14	–40 °C to 85 °C
HF16	16 Mbit SPI NOR flash	2.7 V to 3.6 V	SPI / Dual / Quad	WSON-8 / SOIC-8	–40 °C to 85 °C (A grade 105 °C)
HAC24	24-bit 192 kHz audio codec	AVDD 3.0 V to 3.6 V	I²S / TDM, I²C (0x1A / 0x1B)	QFN-32	–40 °C to 85 °C

Reference designs

Wearable sensor node: HB7 + HT410 + HIMU6, powered from a single cell through an HM3300. Dock: HM5V-PD with a 20 V buck stage. Audio: HAC24 with HM3300 on AVDD.