BELLBURN

ELEV 800

FULL NOTAM SERVICE NOT AVBL

WA UTC +8 YBEB

173241S 1281818E VAR 2 DEG E UNCR

AD OPR Department of Environment and Conservation, Ranger in Charge, Purnululu National Park, WA, 6770. Email: calmpurn@wn.com.au. PH AH 08 9168 7300.
Senior Ranger Purnululu 0432 406 643. Fax 08 9168 7326.

REMARKS

1. PPR. Private strip.
2. Permit required for landing from Department of Environment and Conservation - Phone 08 9168 2179 or AD OPR.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 118.2

FLIGHT PROCEDURES

1. Right hand circuits RWY 10.
2. High volume of fixed wing and rotary wing scenic flights operate over the Bungles and in and out of Bellburn, refer to Special Procedures section for Standard Operating Procedures.

CTAF 127.3

ADDITIONAL INFORMATION

1. High frequency HEL traffic OPR in area. HEL based at strip.
2. Animal hazard possible.

CHARTS RELATED TO THE AERODROME

WAC 3222.

BELLEVUE

ELEV 1555

AVFAX CODE 6105



WA UTC +8 YBLU

273646S 1203538E VAR 1 DEG E CERT

AD OPR IGO Limited, PO Box 496, South Perth, WA, 6951.
Email: cosmosaerodrome@igo.com.au. PH AD MGR 0439 765 459.

REMARKS

Restricted OPS - PPR from AD OPR.

HANDLING SERVICES AND FACILITIES

Terminal facilities. No fuel available. Contact ARO.

APRONS AND TAXIWAYS

TWY A - Code C, 15M sealed.

AERODROME OBSTACLES

1. Terrain 1,832FT AMSL BRG 332 DEG MAG APRX 2.8NM FM ARP, penetrates OBST limitation SFC by 82FT.
2. Tower 1,795FT AMSL BRG 297 DEG MAG APRX 1.6NM FM ARP.
3. Cranes:
   a. 1,767FT AMSL BTN BRG 330-340 DEG MAG APRX 1.3NM FM ARP (temporary). Infringes HZS up to 50FT.
   b. 1,763FT AMSL BRG 315 DEG MAG 1.24NM FM ARP. Head frame infringes inner HZS by up to 110FT.
4. Windturbines:
   a. 2,244FT AMSL PSN 273757.6S 1203302.9E. Infringes OLS by 500FT.
   b. 2,270FT AMSL PSN 273811.8S 1203305.3E. Infringes OLS by 514FT.
   c. 2,277FT AMSL PSN 273826.3S 1203303.3E. Infringes OLS by 481FT.
   d. 2,234FT AMSL PSN 273840.2S 1203302.2E. Infringes OLS by 400FT.

PHYSICAL CHARACTERISTICS

01/19	006	66a	Unrated. Sealed.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 01/19	LIRL(3)		SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 01/19	PAPI(1)	3.0 DEG49FT	SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 01/19	PTBL(2)		BY PRIOR ARRANGEMENT

(1) Left side only. Manual activation with 30MIN PN.
(2) EMERG only. 60MIN PN. CTC ARO.
(3) 30MIN PN.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 MIN.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	118.95 Circuit area

LOCAL TRAFFIC REGULATIONS

1. All ACFT to use turn pads, MAX turn radius at MNM speed.
2. All ACFT ABV 5,700KG MTOW must park on marked bays using appropriate lead-in lines.

FLIGHT PROCEDURES

Right hand circuit on RWY 01 due to terrain to the NW of the AD.

CTAF 126.5

AFRU at Leinster. Signal not AVBL on ground Bellevue.

ADDITIONAL INFORMATION

Bird hazard exists (budgies, swallows, parrots and crows) in VCY of AD.

CHARTS RELATED TO THE AERODROME

1. WAC 3345.
2. Also refer to AIP Departure and Approach Procedures.

BELYANDO/LABONA

ELEV 805

FULL NOTAM SERVICE NOT AVBL

QLD UTC +10 YLBA
220016S 1462150E VAR 8 DEG E UNCR

AD OPR Adani Mining Pty Ltd, Level 9, 120 Edward St, Brisbane, QLD, 4000.
Email: rod.ward@sodexo.com: adani.aro@bravus.com.au.
PH Rod Ward 0431 559 986 H24. ARO 0409 531 338 H24.

REMARKS

Private AD. PPR for all OPS. Email AD OPR.

HANDLING SERVICES AND FACILITIES

IOR JET A1 AVBL - IOR account required.

PASSENGER FACILITIES

LG/WC.

AERODROME OBSTACLES

Lit mast 98FT AGL BRG 161 DEG MAG 1.52NM FM ARP.

PHYSICAL CHARACTERISTICS

18/36		36a	Unrated. RWY LEN 1,105M. Slope 0.89% down to N.	WID 18	RWS 80

OTHER LIGHTING

Solar RWY LGT AVBL for emergency services only.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	128.55
UNICOM	BELYANDO-LABONA UNICOM	126.7 (1)

(1) CS "Safety 1".

Information may be continued on the next page: PTO