CENTURY MINE

ELEV 416

AVFAX CODE 4542



QLD UTC +10 YCNY
184512S 1384224E VAR 5 DEG E CERT
AD OPR Century Mining Ltd, LVL 4, 360 Collins Street, Melbourne, VIC, 3000. ARO 0477 347 998.

REMARKS

1. Restricted OPS. PPR for all OPS.
2. Hours of AD operation - HJ only (0600-1800 Local), 60 MIN PN. EMERG use only HN (1800-0600 Local).

APRONS AND TAXIWAYS

TWY A - Code C, WID 17.5M sealed

AERODROME OBSTACLES

1. Terrain penetration of inner HZS to 715FT AMSL BTN BRG 275 MAG to BRG 165 MAG, 1.67NM to 2.26NM FM ARP.
2. Fence 6FT AGL, APRX 75M FM RWY centreline infringes 14.3% TNS to both sides by 6FT.
3. MIOL:
   a. 656FT AMSL, BRG 141 MAG 2.12NM FM ARP. Infringes inner HZS by 93FT.
   b. 735FT AMSL, BRG 142 MAG 2.36NM FM ARP. Infringes inner HZS by 171FT.

METEOROLOGICAL INFORMATION PROVIDED

1. METAR/SPECI.
2. AWIS Phone 07 3564 3709 - Report faults to BoM.
3. AWIS FREQ 135.6 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

14/32	136	57a	PCR 240/F/B/1.20 MPa/U Sealed.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 14/32	LIRL(1)		SDBY PWR AVBL
RWY 14/32	PAPI(2)	3.0 DEG46FT	SDBY PWR AVBL
RWY 14/32	PTBL(3)		BY PRIOR ARRANGEMENT

(1) EMERG only. Manual activation - 60MIN PN.
(2) Left side. Manual activation - 60MIN PN.
(3) EMERG only. 60MIN PN.

1. RWY edge light spacing: 14/32: 90M.
2. Main power supply serviced by Aerodrome generator.

OTHER LIGHTING

1. TWY LGT: Blue edge EMERG only. Manual activation - 60MIN PN.
2. MIOL - Hills on SE approach.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	125.7 9500FT

LOCAL TRAFFIC REGULATIONS

All pilots are requested to make maximum radius turns RWY ends and on apron by following design turn pad guidelines.

FLIGHT PROCEDURES

Right hand circuits when OPR RWY 32.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Bird Hazard (Kites).

CHARTS RELATED TO THE AERODROME

1. WAC 3220.
2. Also refer to AIP Departure and Approach Procedures.