
FITZROY CROSSING

ELEV 368

AVFAX CODE 6906



WA UTC +8 YFTZ
181055S 1253331E VAR 2 DEG E CERT
AD OPR Shire of Derby/ West Kimberley, PO Box 101, Fitzroy Crossing, WA, 6765. Email: sdwk@sdwk.wa.gov.au. PH 08 9191 0999.
ARO H24 0427 915 201: AD MGR 0418 922 415.

HANDLING SERVICES AND FACILITIES

H24 AVGAS and JET A1 via bowser.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT D, METAR/SPECI.
2. AWIS PH 08 6216 2612 - Report faults to BoM.

PHYSICAL CHARACTERISTICS

01/19 015 43a PCR 70/F/C/Y/T Sealed. WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

RWY 01/19 LIRL(2) AFRU+PAL 126.7
RWY 01/19 PTBL(1) BY PRIOR ARRANGEMENT
(1) EMERG only.
(2) Manual activation by prior arrangement with AD OPR 24 HR prior notice required.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 124.8 On Ground

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Animal and Bird hazard exists.

CHARTS RELATED TO THE AERODROME


1. WAC 3223.
2. Also refer to AIP Departure & Approach Procedures.

FLINDERS ISLAND

ELEV 34

AVFAX CODE 7012

TAS UTC +10 YFLI
400529S 1475934E VAR 14 DEG E CERT
AD OPR Flinders Council, PO Box 40, Whitemark, Flinders Island, TAS, 7255.
Email: richard.harley@flinders.tas.gov.au: airport.operations@flinders.tas.gov.au.
PH 03 6359 2144 (BH). ARO H24 0429 813 929. Website: www.flinders.tas.gov.au.



REMARKS

1. This AD is a Security Controlled Airport.
2. AD Charges apply, refer to website.

HANDLING SERVICES AND FACILITIES

World Fuel Services H24 AVGAS and JET A1 bowser. Carnet and credit card (via smartphone APP). PH 0429 813 929 (Telstra is the only mobile phone service provider that works on Flinders Island).

PASSENGER FACILITIES

HC/TX/AC/LG/RF/WC.

APRONS AND TAXIWAYS

TWY B MAX weight - 4,000KG.

SURFACE MOVEMENT GUIDANCE

RWY 32 fixed distance and TDZ markings displayed 20M to N.

AERODROME OBSTACLES

1. RWY 05 - Unlit fence 4.5FT ABV and 11M NE of RWS end.
2. RWY 32 - Unlit fence 5.3FT ABV and 11M NW of RWS end.
3. Group of trees BRG 051 DEG MAG 3,680M FM ARP. Infringes TKOF SFC by 14FT.
4. Lit OBST:
   a. 399FT AMSL, BRG 087 MAG 2NM FM ARP.
   b. 439FT AMSL, BRG 343 MAG 1.1NM FM ARP.
   c. 499FT AMSL, BRG 310 MAG 2.5NM FM ARP.
   d. 552FT AMSL, BRG 108 MAG 2.9NM FM ARP.
   e. 653FT AMSL, BRG 342 MAG 1.7NM FM ARP.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 03 6283 8601 - Report faults to BoM.
3. AWIS FREQ 134.4 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

05/23	047	35c	PCR 55/F/B/0.61 MPa/T Sealed	WID 30	RWS 90
14/32	129	56c	PCR 55/F/B/0.61 MPa/T Sealed	WID 30	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 05/23	LIRL	AFRU+PAL 127.8	SDBY PWR AVBL
RWY 14/32	LIRL	AFRU+PAL 127.8	SDBY PWR AVBL

1. RWY edge light spacing: 05/23: 90M; 14/32: 90M.
2. RWY 23 and RWY 32: AFRU+PAL activation range may be reduced to the N due to high terrain.

OTHER LIGHTING

HBN	FLG 1 R	399FT AMSL BRG 087 MAG 2NM FM ARP.
HBN	FLG 1 R	552FT AMSL BRG 108 MAG 2.9NM FM ARP.
HBN	FLG 1 R	439FT AMSL BRG 343 MAG 1.1NM FM ARP.
HBN	FLG 1 R	653FT AMSL BRG 341 MAG 1.7NM FM ARP.
HBN	FLG 1 R	499FT AMSL BRG 310 MAG 2.5NM FM ARP.

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	126.5 Circuit area

LOCAL TRAFFIC REGULATIONS

1. VHF transmissions of taxiing ACFT are subject to ground shielding. Extreme caution must be exercised.
2. Parking restrictions:
   a. Bay 1 scheduled Air Transport Operation (ATO) only.
   b. Bay 2 shared with RFDS, Air Ambulance and other ATO - contact ARO.
   c. Bay 3 AVBL for itinerant ACFT above 5,700KG - contact ARO.
   d. Light ACFT to park on grass APN adjacent to main APN.
   e. TWY B and grass APN for private hanger ACFT only - contact ARO.
   f. Fuel bay parking not permitted unless ACFT requiring fuel - contact ARO.
3. All ACFT ABV 5,700KG must use RWY end turning node.

Information may be continued on the next page: PTO

FLIGHT PROCEDURES
1. Right hand circuits RQ when OPR on RWY 05 and 14.
2. Night landings not permitted RWY 23. Night takeoffs not permitted RWY 05.


CTAF - AFRU 127.8

ADDITIONAL INFORMATION
Bird and wallaby hazard exists.

CHARTS RELATED TO THE AERODROME
1. WAC 3556.
2. Also refer to AIP Departure and Approach Procedures.

FORBES **ELEV 760**

AVFAX CODE 2201
NSW UTC +10 YFBS
332149S 1475606E VAR 11 DEG E CERT
AD OPR Forbes Shire Council, PO Box 333, Forbes, NSW, 2871. PH 02 6850 2874 (BH) or 0447 487 726 (AH).



REMARKS
Landing charges: nil.

HANDLING SERVICES AND FACILITIES
AVGAS and JET A1 AVBL. H24, self-service bowser accepts all credit cards.

PASSENGER FACILITIES
WC

METEOROLOGICAL INFORMATION PROVIDED
1. METAR/SPECI.
2. AWIS PH 02 9353 6420 - Report faults to BoM.

PHYSICAL CHARACTERISTICS
09/27 088 40a Unrated. WID 18 RWS 90

AERODROME AND APPROACH LIGHTING
RWY 09/27 LIRL PAL 122.4

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 135.25 Circuit area

LOCAL TRAFFIC REGULATIONS
1. RWS 09L/27R: grass strip parallel to sealed RWY. Marked by orange gable markers and available for use by hang gliders, tugs and tail skid aircraft.
2. RWY 09R/27L: for use by aircraft other than hang gliders, tugs and tail skid aircraft.

FLIGHT PROCEDURES
1. Simultaneous contra circuit operations daily HJ.
2. Hang glider/tug/tail-skid circuits to north using RWS 09L/27R.
3. Other aircraft circuits to the south using RWY 09R/27L.
4. There is no dead side with contra circuits.
5. Aircraft must not infringe hang gliders, tugs and tail-skid aircraft circuit below 1,500FT AGL.
6. Join circuit downwind or upwind over RWY 09R/27L.
7. RWY 27R: Right hand circuits.
8. RWY 09R: Right hand circuits HJ. Left hand circuits permitted HN.

CTAF 126.7