ADDITIONAL INFORMATION

1. Blasting HJ DLY BRG 028 DEG MAG 3.6NM FM ARP. Dust plumes may occur following blasting, ACFT are requested to avoid flying over mine pit.
2. UAV OPR HJ daily BRG 037DEG MAG 3.7NM FM ARP. SFC to 400FT AGL.

CHARTS RELATED TO THE AERODROME

1. WAC 3352.
2. Also refer to AIP Departure and Approach Procedures.

GUDAI-DARRI MINE — ELEV 1473

AVFAX CODE 6838

WA		UTC +8	YKDD
223019S	1190434E	VAR 1 DEG E	CERT

AD OPR Mount Bruce Mining Pty Ltd, Level 18, 152-158 St Georges Terrace, Perth, WA, 6000. Email: gudaidarri.airport@amsaustralia.com. PH 08 9327 2000. ARO AH 0428 868 947.



REMARKS

1. Restricted OPS: 24 HR PPR FM AD OPR (AD MGR).
2. All OPS – Advise AD OPR at least 20 MINS prior ETA on 127.925. CS “Gudai-Darri Base”.

HANDLING SERVICES AND FACILITIES

Viva Energy Aviation: 2230-1000 UTC DLY, AH with 2HR PN. PH 0448 680 573. JET A1 - Fuel2Sky Carnet Cards, V or MC.
Marshalling, parking allocation and ground handling services by prior arrangement with AD OPR.

PASSENGER FACILITIES

WC, LG, RF, Telstra 4G mobile reception.

APRONS AND TAXIWAYS

TWY A, Code C WID 18M bitumen seal.

AERODROME OBSTACLES

There are a large number of obstacles in the VCY of the AD. CTC ARO for details.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS FREQ 133.350 (requires three one-second pulses to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

12/30	115	72a	PCR 450/F/B/X/T Sealed.	WID 45	RWS 300

AERODROME AND APPROACH LIGHTING

RWY 12/30	LIRL(3)	PAL+AA 119.6		
RWY 12/30	PAPI(1)	PAL+AA 119.6	3.0 DEG54FT	SDBY PWR AVBL
RWY 12/30	PTBL(2)			BY PRIOR ARRANGEMENT

(1) Left side. PAL+AA requires three three-second pulses to activate.
(2) EMERG (mercy flights) only. 2HR PN.
(3) PAL+AA requires three three-second pulses to activate.
RWY edge light spacing: 59.5M.

OTHER LIGHTING

1. SDBY PWR switchover time: 20 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	128.15 Circuit area

Information may be continued on the next page: PTO

LOCAL TRAFFIC REGULATIONS

1. RWY 12/30: All fixed wing ACFT ABV 5,700KG must make MAX RAD turns at MNM speed at turning nodes to avoid SFC damage.
2. All ACFT 5,700KG and BLW are permitted to perform MAX RAD mid RWY turns.
3. All ACFT are required to backtrack on RWY centreline.
4. All ACFT to follow APN markings.
5. All jet ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi.

FLIGHT PROCEDURES

Right hand circuit on RWY 30 due to high terrain to the S of the AD.

CTAF - AFRU 127.05

1. AFRU not AVBL on ground.
2. AFRU at Fortescue Dave Forrest (YFDF).

ADDITIONAL INFORMATION

Blasting occurs BTN BRG 209 MAG and BRG 248 MAG, 2.0NM to 4.2NM FM ARP.
CTC ARO for blasting times.

CHARTS RELATED TO THE AERODROME

1. WAC 3229.
2. Also refer to AIP Departure and Approach Procedures.

GUNBOWER

ELEV 290

FULL NOTAM SERVICE NOT AVBL



VIC UTC +10 YGBW
355759S 1442252E VAR 11 DEG E UNCR
AD OPR Brohden Elliott, 34 Pavone Rd, Gunbower, VIC, 3566.
Email: brohdenelliott@icloud.com. PH 03 5487 1517. Mobile 0438 368 088.

REMARKS

PPR.

AERODROME OBSTACLES

Powerlines prior to RWY 31 THR.

PHYSICAL CHARACTERISTICS

13/31	23c	Unrated. Grass. RWY LEN 700M.	WID 30

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	118.6

CTAF 126.7

ADDITIONAL INFORMATION

1. White painted tyres around RWY edges and windsock.
2. Strip becomes unserviceable after moderate rain.
3. Bird and animal hazard may exist.

CHARTS RELATED TO THE AERODROME

WAC 3457, 3469, 3470.