FLIGHT PROCEDURES

1. Outside TWR HR, fixed wing ACFT should remain S of RWY 08/26 on base circuit.
2. Circuit Direction:
   Outside TWR HR, RWY 08 Right Hand circuits; RWY 26 Left Hand Circuits.
3. Extensive Helicopter OPS conducted to N of AD.
4. ACFT BAE-146 and above, when joining downwind for RWY 26 are REQ to join the circuit South of the town site to avoid overflying residential areas.
5. Low visibility operations not AVBL.
6. ATC may process SIMUL same direction independent OPS on RWY 08/26 and TWY F as a HLS, with the following conditions:
   a. In VMC, by day.
   b. Between HEL and single/twin engined propeller ACFT.
   c. RWY centre line and TWY centre are spaced at 200M.
   d. Pertinent traffic will be issued.
   e. Both ACFT will be on the same FREQ.

CTAF - AFRU 127.35

ADDITIONAL INFORMATION

1. Bird and animal hazard exists.
2. Unannounced high velocity gas discharge may occur within D150 (APRX 002DEG MAG/7.5NM ARP).
3. D157 Karratha Dampier Firing Range may be in use without promulgation of NOTAM as indicated by flags lining the range.
4. HEL OPS WI 40NM of YPKA using night vision goggles primarily BTN the area bounded by YSBY, YCLN, YCPL, YPKA over water for maritime transfer OPS may not be displaying external LGT.

CHARTS RELATED TO THE AERODROME

1. WAC 3229.
2. Refer to AIP Departure and Approach Procedures.
3. Aerodrome Obstacle Chart Type A: May 2022 AVBL from AD OPR.

KARUMBA — ELEV 18

AVFAX CODE 4524



QLD UTC +10 YKMB
172717S 1404949E VAR 5 DEG E CERT
AD OPR Shire of Carpentaria, PO Box 31, Normanton, QLD, 4890.
PH 07 4745 2200. ARO 0427 117 765 H24. Fax 4745 1340.

REMARKS

1. AD Charges: All ACFT.
2. This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES

World Fuel Services (WFS): H24 AVGAS bowser WFS cardswipe and credit card (via smartphone APP). PH: 07 4745 1615 or 0474 073 734 (H24). Email: wfsnormanton@gmail.com.

PASSENGER FACILITIES

HJ - TX/AC/RF/WC/PT/HC

PHYSICAL CHARACTERISTICS

03/21 032 45a PCR 88/F/B/0.90 MPa/U Sealed. WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

RWY 03/21 LIRL(1) PAL 120.05 SDBY PWR AVBL
RWY 03/21 PTBL(2) BY PRIOR ARRANGEMENT

(1) PAL requires three one-second pulses to activate.
(2) 60 MIN PN.
RWY edge light spacing: 60M.

Information may be continued on the next page: PTO

OTHER LIGHTING
1. Secondary PWR switchover time: 70 SEC.
2. TWY LGT: Blue Edge.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA BRISBANE CENTRE 118.6 Circuit Area

CTAF 126.7

ADDITIONAL INFORMATION
Bird hazard exists particularly early morning and late afternoon.

CHARTS RELATED TO THE AERODROME
WAC 3220.

KATANNING — ELEV 936

AVFAX CODE 6309



WA UTC +8 YKNG
334201S 1173912E VAR 2 DEG W CERT
AD OPR Shire of Katanning, PO Box 130, Katanning, WA, 6317.
Email: admin@katanning.wa.gov.au. PH 08 9821 9999. ARO 0438 582 732.

REMARKS
CTC ARO for security gate code.

PHYSICAL CHARACTERISTICS

07/25	067	49a	5700 kg/0.80 MPa Sealed	WID 23	RWS 90
13/31	132	33c	5700 kg/0.80 MPa Gravel	WID 18	RWS 60

AERODROME AND APPROACH LIGHTING
RWY 07/25 LIRL PAL+AA 119.6 SDBY PWR AVBL
SDBY PWR manually activated, 30MIN PN. PH 0409 891 645.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 125.4

CTAF 126.7

CHARTS RELATED TO THE AERODROME
1. WAC 3642.
2. Also refer to AIP Departure & Approach Procedures.

KEITH — ELEV 92

FULL NOTAM SERVICE NOT AVBL

SA UTC +9:30 YKTH
360651S 1401508E VAR 9 DEG E UNCR
AD OPR Tatiara District Council, 43 Woolshed St, Bordertown, SA, 5268.
Email: office@tatiara.sa.gov.au. PH 08 8752 1044. Website: www.tatiara.sa.gov.au.



PHYSICAL CHARACTERISTICS

17/35		38c	Unrated. Gravel.	WID 15	RWS 77