PHYSICAL CHARACTERISTICS

01/19	006	66a	Unrated. Sealed.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 01/19	LIRL(3)		SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 01/19	PAPI(1)	3.0 DEG49FT	SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 01/19	PTBL(2)		BY PRIOR ARRANGEMENT

(1) Left side only. Manual activation with 30MIN PN.
(2) EMERG only. 60MIN PN. CTC ARO.
(3) 30MIN PN.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 MIN.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	118.95 Circuit area

LOCAL TRAFFIC REGULATIONS

1. All ACFT to use turn pads, MAX turn radius at MNM speed.
2. All ACFT ABV 5,700KG MTOW must park on marked bays using appropriate lead-in lines.

FLIGHT PROCEDURES

Right hand circuit on RWY 01 due to terrain to the NW of the AD.

CTAF 126.5

AFRU at Leinster. Signal not AVBL on ground Bellevue.

ADDITIONAL INFORMATION

Bird hazard exists (budgies, swallows, parrots and crows) in VCY of AD.

CHARTS RELATED TO THE AERODROME

1. WAC 3345.
2. Also refer to AIP Departure and Approach Procedures.

BELYANDO/LABONA

ELEV 805

FULL NOTAM SERVICE NOT AVBL



QLD UTC +10 YLBA
220016S 1462150E VAR 8 DEG E UNCR

AD OPR Adani Mining Pty Ltd, Level 9, 120 Edward St, Brisbane, QLD, 4000.
Email: rod.ward@sodexo.com: adani.aro@bravus.com.au.
PH Rod Ward 0431 559 986 H24. ARO 0409 531 338 H24.

REMARKS

Private AD. PPR for all OPS. Email AD OPR.

HANDLING SERVICES AND FACILITIES

IOR JET A1 AVBL - IOR account required.

PASSENGER FACILITIES

LG/WC.

AERODROME OBSTACLES

Lit mast 98FT AGL BRG 161 DEG MAG 1.52NM FM ARP.

PHYSICAL CHARACTERISTICS

18/36		36a	Unrated. RWY LEN 1,105M. Slope 0.89% down to N.	WID 18	RWS 80

OTHER LIGHTING

Solar RWY LGT AVBL for emergency services only.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	128.55
UNICOM	BELYANDO-LABONA UNICOM	126.7 (1)

(1) CS "Safety 1".

Information may be continued on the next page: PTO

LOCAL TRAFFIC REGULATIONS

1. PRKG bays unmarked. Follow ARO directions.
2. Make a 'Rolling' call when lined up and prior to take-off due to line of sight limitations.

FLIGHT PROCEDURES

Right hand CCTS RQ when OPR on RWY 18.

CTAF 126.7

ADDITIONAL INFORMATION

Bird and wildlife hazard exists:

a. Galahs and black kites in VCY of AD.
b. Rabbits may be on airfield.
c. Increased bird activity early morning and late afternoon.
d. ARO will advise inbound aircraft via CTAF for increased bird activity.

CHARTS RELATED TO THE AERODROME


WAC 3234.

BENALLA ELEV 569

AVFAX CODE 3030

VIC		UTC +10	YBLA
363315S	1460033E	VAR 12 DEG E	CERT

AD OPR Benalla Rural City Council, PO Box 227, Benalla, VIC, 3672.
Email: council@benalla.vic.gov.au. PH 03 5760 2600.



REMARKS

AD Charges: All AVTUR ACFT.

HANDLING SERVICES AND FACILITIES

Aero Refuellers: H24 card swipe. AVGAS and JET A1 bowsers. Accepts Aero Refuellers cards, V and MC.

PHYSICAL CHARACTERISTICS

08/26	083	34a	Unrated. Sealed.	WID 18	RWS 90
17/35	163	24c	5700 kg/0.45 MPa Grass silt clay.	WID 30	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 08/26 LIRL PAL 123.4

OTHER LIGHTING

TWY LGT: Green CL.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.2 Circuit area

FLIGHT PROCEDURES

1. CONTRA CIRCUITS IN OPERATION - **THERE IS NO DEAD SIDE WITH CONTRA CIRCUITS.**
2. Gliders and tugs use separate glider strips 08/26 and 17/35, marked by orange gable markers. Also AVBL for tailskid equipped ACFT.
3. Glider/tug circuits to N or E, other ACFT circuits to S or W. Other ACFT must not infringe glider circuit BLW 2,000FT AGL. Right hand circuits RWY 08 and 17. Gliders/tugs right hand circuits glider strip RWY 26 and 35.