METEOROLOGICAL INFORMATION PROVIDED
1. TAF CAT D, METAR/SPECI.
2. AWIS PH 08 8150 3807 - Report faults to BoM.

PHYSICAL CHARACTERISTICS
02/20	023	40a	Unrated. Sealed	WID 18	RWS 90
11/29	114	56a	PCR 68/F/A/0.70 MPa/U Sealed	WID 30	RWS 90

AERODROME AND APPROACH LIGHTING
RWY 11/29	LIRL	PAL+AA 120.6		SDBY PWR AVBL
RWY 11/29	PAPI(1)	PAL+AA 120.6	3.0 DEG42FT	SDBY PWR AVBL

(1) Left side.
RWY edge light spacing: 11/29: 90M.

OTHER LIGHTING
ABN FLG 6 W
1. TWY LGT: Blue edge on A.
2. Automatic standby generator AVBL. Switchover time: 45 SEC.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 121.2 On Ground

RADIO NAVIGATION AND LANDING AIDS
NDB LEC 287 303555.4S 1382632.1E Range 150 (HN 85) (1)
(1) 125/1.6 to ARP.

FLIGHT PROCEDURES
1. Right Hand circuits RQ when OPR on RWY 02 and RWY 29.
2. RWY 02/20 - Night TKOF and LDG are not permitted.
3. Night VFR OPS approved under the FLW mandatory conditions:
   WX COND at the time must meet the night VMC requirements. Circuit ALT must not be less than 2,050FT. OPS under night VFR COND are only permitted on RWY 11/29. Circling and circuits must be kept WI 3NM of either THR. DEP ACFT must FLW the circuit direction and remain WI 3NM until reaching LSALT for the first TR. DEP ACFT must use full length of the RWY - INT DEP are not permitted for night OPS. ARR ACFT must MNTN LSALT until positively established WI 3NM and then descend to not less than 2,050FT until turning base for LDG. This base position must be kept WI 3NM of the THR.
4. RWY 11/29 - IFR CAT ACFT LDG HN are not to descend BLW 1,950FT unless established on PAPI, or on final approach.

CTAF 126.7

ADDITIONAL INFORMATION
Animal proof fence installed.

CHARTS RELATED TO THE AERODROME
1. WAC 3355.
2. Also refer to AIP Departure and Approach Procedures.

LEINSTER **ELEV 1631**

AVFAX CODE 6106



WA UTC +8 YLST
275036S 1204212E VAR 1 DEG E CERT
AD OPR BHP Nickel West Pty Ltd, LNO, PO Box 22, Leinster, WA, 6437.
Email: leinsteraerodrome@bhp.com. PH AD MGR 0450 031 931.
Email: joseph.buchanan@bhp.com. ARO PH 08 9026 5068:
0460 024 827 (H24).

REMARKS
1. AD Charges: All ACFT.
2. PPR for all OPS. CTC ARO via email.

HANDLING SERVICES AND FACILITIES
JET A1 by prior arrangement with BHP Nickel West, account required. CTC AD MGR to set up account. AD not manned H24. Contact ARO (H24) for refuelling.

Information may be continued on the next page: PTO

PASSENGER FACILITIES
LG/RF/WC.

AERODROME OBSTACLES
1. Lit tower:
   a. Frame 1,871FT AMSL PSN 274855.42S 1204207.04E. Infringes inner HZS by 96FT.
   b. Stack 1,786FT AMSL PSN 274854.11S 1204154.72E. Infringes inner HZS by 11FT.
2. Unlit site (dump) 1,833FT AMSL PSN 274910.13S 1204235.77E. Infringes inner HZS by 59FT.
3. Unlit terrain:
   a. 1,797FT AMSL PSN 274829.72S 1204049.11E. Infringes COS by 9FT.
   b. 1,783FT AMSL PSN 274841.42S 1204112.79E. Infringes inner HZS by 8FT.

METEOROLOGICAL INFORMATION PROVIDED
1. TAF CAT C, METAR/SPECI.
2. AWIS PH 08 6216 2624 - Report faults to BoM.
3. AWIS FREQ 124.0 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS
10/28 099 59a PCR 210/F/A/Y/T Sealed WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 10/28	LIRL(1)	PAL+AA 119.6		SDBY PWR AVBL
RWY 10	PAPI(2)	PAL+AA 119.6	3.0 DEG44FT	SDBY PWR AVBL
RWY 28	PAPI(2)	PAL+AA 119.6	3.0 DEG43FT	SDBY PWR AVBL

(1) HN
(2) Left side.

OTHER LIGHTING
1. SDBY PWR switchover time: 8 SEC. Automatic activation.
2. TWY LGT: Blue edge.
3. TWY holding point LGT: 2 x yellow.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 118.95 Circuit Area

RADIO NAVIGATION AND LANDING AIDS
NDB LST 230 275026.3S 1204201.0E Range 70 (HN 70) (1)
(1) Pilot monitored.

LOCAL TRAFFIC REGULATIONS
1. All ACFT performing 180 DEG turns on RWY must be at MNM speed and MAX RAD WI the RWY turning nodes.
2. ACFT must be at taxiing speed when turning into and out of TWY/RWY.
3. ACFT must follow lead in lines:
   a. DH8D/E190/F100 - Use lead in/out line A.
   b. B190/DH8C/F70/PC24/SW4 - Use lead in/out line B.
4. Refuelling only AVBL on Bay 1.

FLIGHT PROCEDURES
Right hand circuits required RWY 10.

CTAF - AFRU 126.5

ADDITIONAL INFORMATION
1. Blasting occurs at Harmony Pit (BRG 350 DEG MAG 4.09NM FM ARP) and Camelot Pit (BRG 343 DEG MAG 9.56NM FM ARP). Pilots are requested to avoid overflying these mining sites.
2. Increased bird activity post rainfall events (typically between January and June). NOTAM will be issued during periods of increased wildlife.

CHARTS RELATED TO THE AERODROME
1. WAC 3345.
2. Also refer to AIP Departure and Approach Procedures.