FLIGHT PROCEDURES

1. Pilots are reminded that NZ altimetry setting PROC are applicable when OPR into and out of Norfolk Island.
2. NZ regulations require aircraft flying within the Auckland Oceanic FIR to maintain vertical position with reference to standard pressure 1,013 HPA, with the exception that within proximity to the Norfolk Island AD aircraft must maintain altitude with reference to aerodrome QNH.
3. Right hand CCTS RQ when OPR on RWY 04 and 11 due to high terrain and obstacles to the north of the ARP.

CTAF 118.1

ADDITIONAL INFORMATION

1. Significant bird hazard at Philip Island (160DEG/5NM from AD, ELEV 913FT AMSL), and Nepean Island (131DEG/2.5NM from AD, ELEV 108FT AMSL).
2. Weather balloon launch APRX 2315 UTC FM 420M SW ARP. Launches may occur at other times.
3. SARWATCH: The responsibility of SAR for ACFT movements at Norfolk Island belongs with New Zealand.
4. Actual weather conditions can change rapidly and vary from forecasts.

CHARTS RELATED TO THE AERODROME

1. WAC 3359.
2. Aerodrome Obstruction Chart Type A: RWY11/29, 3rd Edition (August 2025).
3. Also refer to AIP Departure and Approach Procedures.

NORMANTON — ELEV 73

AVFAX CODE 4517



QLD		UTC +10	YNTN
174106S	1410413E	VAR 5 DEG E	CERT

AD OPR Shire of Carpentaria, PO Box 31, Normanton, QLD, 4890. PH 07 4745 2200: AH 0429 303 112. ARO 0429 303 112 H24. Fax 4745 1340.

REMARKS

1. AD Charges: All ACFT
2. This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES

World Fuel Services (WFS): H24 AVGAS bowser WFS cardswipe and credit card (via smartphone APP). AVGAS and JET A1 tankers. WFS Carnet card, EFTPOS and cash. 0800-1700 Local MON-FRI AH by arrangement. Call-out fee applies. 90MIN PN. PH: 07 4745 1615 or 0474 073 734 (H24). Email: wfsnormanton@gmail.com.

PASSENGER FACILITIES

PT/TX/AC/WC/RF/HC and airport shuttle.

AERODROME OBSTACLES

Unlit TWR 198FT AMSL BRG 022 DEG MAG 2,010M FM ARP. Infringes inner HZS by 5FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS Phone 07 3564 3730 - Report faults to BoM.
3. AWIS FREQ 133.1 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

14/32 141 55a PCR 89/F/A/0.85 MPa/U WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 14/32 LIRL AFRU+PAL 126.7 SDBY PWR AVBL

RWY 14/32 edge light spacing: 60M.

OTHER LIGHTING
1. TWY LGT blue edge.
2. ABN not AVBL.
3. Secondary PWR switchover time: 30 SEC.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA BRISBANE CENTRE 118.6 On Ground

RADIO NAVIGATION AND LANDING AIDS
NDB NTN 311 174144.7S 1410422.9E Range 120 (HN 85) OW 180 (OW HN120) (1)

(1) 344/0.8 to ARP.

LOCAL TRAFFIC REGULATIONS
Parking of non-RPT ACFT ABV 5,700KG is AVBL after prior approval from AD OPR. All other ACFT, except RPT ACFT, must park in light ACFT area to N of main apron.

CTAF - AFRU 126.7

CHARTS RELATED TO THE AERODROME
1. WAC 3220.
2. Also refer to AIP Departure and Approach Procedures.

NORMANTON HELIPAD

ELEV 70

FULL NOTAM SERVICE NOT AVBL

QLD UTC +10 YNTH
174039S 1410406E VAR 5 DEG E UNCR

AD OPR Kristen Kuskopf, PO Box 487, Normanton, QLD, 4890.
Email: gulflandmotel@bigpond.com. PH 07 4745 1290. ARO AH 0417 482 692.
Mobile 0448 543 239.

REMARKS
PPR CTC AD OPR - day use only.

PASSENGER FACILITIES
WC/RF/TX/HC/AC. Transfers to and from Normanton Airport AVBL upon request.

PHYSICAL CHARACTERISTICS
Helipad - 30M x 30M. Hard gravel.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA BRISBANE CENTRE 118.6
UNICOM NORMANTON HELIPAD UNICOM 126.7 (1)

(1) CS "Normanton UNICOM".

CTAF 126.7

CHARTS RELATED TO THE AERODROME
WAC 3220.

Information may be continued on the next page: PTO