MONTO

ELEV 757

FULL NOTAM SERVICE NOT AVBL



QLD UTC +10 YMTO
245332S 1510607E VAR 10 DEG E UNCR
AD OPR North Burnett Regional Council, PO Box 390, Gayndah, QLD, 4625.
Email: admin@northburnett.qld.gov.au. Council PH 1300 696 272.
Fax 07 4161 1425.

PASSENGER FACILITIES

PT/WC/LG/TX (07 4166 1124, AH 4166 1254)/HC (4166 1755)/AC (4166 1377, 4166 1777)/ Terminal shelter.

APRONS AND TAXIWAYS

Sealed TWY and APN.

AERODROME OBSTACLES

Assume APCH OLS and transition OLS infringements exist.

PHYSICAL CHARACTERISTICS

16/34	43a	Unrated. Sealed. RWY LEN 1,310M. Slope 0.3% down to N.	WID 30	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 16/34 LIRL AFRU+PAL 126.7

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 124.1 3000FT

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

1. Assume bird and animal hazards exist.
2. Model ACFT OPR WI 1,000M RAD FM ARP. OPR will monitor CTAF.

CHARTS RELATED TO THE AERODROME

WAC 3340.

MOOMBA

ELEV 143

AVFAX CODE 5204



SA UTC +9:30 YOOM
280558S 1401149E VAR 7 DEG E CERT
AD OPR Santos Ltd, PO Box 2319, Adelaide, SA, 5001.
PH 08 8116 5213. ARO 0419 847 168 (H24). Fax 08 8116 5057.

REMARKS

1. PPR.
2. AD charges to all unauthorised ACFT.
3. All OPS: advise AD OPR at least 20MIN prior to ETA on 126.4. CS “Moomba Base”.

HANDLING SERVICES AND FACILITIES

Sodexo refuelling: Phone 0491 970 912. AVBL HJ. JET A1 only.
Refuelling: PH 08 8678 4107 AVBL H24. Account holders only.

AERODROME OBSTACLES

1. Lit masts infringe inner horizontal surface:
   a. 315FT AMSL, APRX 1.38NM 152 DEG MAG FM ARP.
   b. 315FT AMSL, APRX 1.47NM 154 DEG MAG FM ARP.
2. Apron flood lights infringe transitional surface:
   a. 181FT AMSL, APRX 0.15NM 151 DEG MAG FM ARP.
   b. 181FT AMSL, APRX 0.18NM 149 DEG MAG FM ARP.
3. COM TWR 313FT AMSL BRG 138 DEG MAG 2,502M FM ARP. Infringes horizontal surface by 25FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS Phone 08 8150 3808 - Report faults to AD OPR.
3. AWIS FREQ 128.55 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

12/30 120 56a PCR 232/F/B/1.03 MPa/U Graded. WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 12/30	LIRL(1)	PAL+AA 120.6		SDBY PWR AVBL
RWY 12/30	PAPI(2)	PAL+AA 120.6	3.0 DEG52FT	SDBY PWR AVBL
RWY 12/30	PTBL(3)			BY PRIOR ARRANGEMENT

(1) PAL will not ACT RWY lighting by day in good VIS.
(2) Left side.
(3) EMERG only. 60MIN PN.
RWY edge light spacing: 12/30: 60M.

OTHER LIGHTING

1. Secondary PWR switchover time: 9 SEC.
2. TWY LGT: Blue edge on A and B.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 119.5 On Ground

RADIO NAVIGATION AND LANDING AIDS

DME	OOM	112.0/ 57X	280615.4S	1401158.8E		(1)
NDB	OOM	227	280615.6S	1401156.9E	Range 75 (HN 75)	(2)

(1) 120/1.7 to ARP. Antenna ELEV 142FT.
(2) 120/1.7 to ARP.

LOCAL TRAFFIC REGULATIONS

ACFT ABV 5,700KG must use nodes for 180 turns.

FLIGHT PROCEDURES

1. RWY 30 right hand circuits required.
2. ACFT are to avoid overflying the gas treatment plant 800M S RWY 30 THR.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

1. Gas vent 600M S RWY 30 THR. Operational use advised by NOTAM.
2. Increased wildlife activity will be communicated via NOTAM as required. Pilots are encouraged as part of flight planning to REQ current information from AD safety personnel on 08 8678 4513.

CHARTS RELATED TO THE AERODROME

1. WAC 3355.
2. Also refer to AIP Departure and Approach Procedures.

Information may be continued on the next page: PTO