ROYAL NORTH SHORE HOSPITAL

ELEV 363

FULL NOTAM SERVICE NOT AVBL

NSW UTC +10 YXNS
334916S 1511131E VAR 13 DEG E UNCR
AD OPR Royal North Shore Hospital, Pacific Highway, St Leonards, NSW, 2065.
PH Hospital Switch 02 9926 7111: Security 02 9926 7190: 02 9926 7724.

REMARKS

1. MAX size/Mass - BH412 or equivalent (5,400KG).
2. Medical EMERG OPS only.

HANDLING SERVICES AND FACILITIES

Medical EMERG only.

AERODROME OBSTACLES

1. Three large television towers in close proximity.
2. Plant room at E end of HLS.
3. Taller buildings to the N, E and SE.

PHYSICAL CHARACTERISTICS

HELIPAD - 26M x 40M Rooftop HLS with 2 9M x 9M concrete LLAs.

AERODROME AND APPROACH LIGHTING

Pilot Actuated Airport Lighting Control (PAALC) - 120.05 - Yellow perimeter lights, Hospital HLS markings.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA SYDNEY CENTRE 124.55
Operations are within NORTH SHORE LANE - FREQ 120.8

LOCAL TRAFFIC REGULATIONS

1. Notify details of inbound patients to emergency department on 02 9436 1863.
2. Skid under carriage HEL on LLA.

FLIGHT PROCEDURES

APPROACH/DEPARTURE PATHS

a. Over Gore Hill cemetery (Inbound - 083DEG MAG; Outbound - 263DEG MAG)
b. Over Gore Hill oval (Inbound - 290DEG MAG; Outbound - 110DEG MAG)

CTAF 120.8

CHARTS RELATED TO THE AERODROME

WAC 3456.

ROYAL PRINCE ALFRED HOSPITAL

ELEV 96

FULL NOTAM SERVICE NOT AVBL

NSW UTC +10 YRPA
335322S 1511102E VAR 13 DEG E UNCR
AD OPR Royal Prince Alfred Hospital, Missenden Road, Camperdown, NSW, 2050.

REMARKS

1. Location: UBD City Link Map 14D3
2. 1:25K Map 9130 grid 319485

PHYSICAL CHARACTERISTICS

1. 26M Rooftop Helipad atop new wing (Level 11).
2. Maximum design weight 5,400KG.
3. 19M Dashed white circle.
4. Standard Hospital HLS Symbol.
5. 12 x white omnidirectional perimeter lights.
6. 2 x white, illuminated flight path arrows.
7. Manually-activated flood light on request.
8. Lighted windsock with beacon.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA SYDNEY CENTRE 124.55

LOCAL TRAFFIC REGULATIONS

1. Lee-side turbulence in west wind due to building alongside.
2. Possible turbulence due low velocity air discharge from plant rooms immediately below northern flight path.
3. Magnetic Resonance Imaging Unit (MRI) bearing 290DEG 70M.

FLIGHT PROCEDURES

1. PREFERRED FLIGHT PATHS:

a. 165DEG M in/345DEG M out.
b. 330DEG M in/320DEG M out.

2. Minimise ground running.

CTAF 126.7

ADDITIONAL INFORMATION

1. Buildings below 8:1 flight path gradient about 600M South.
2. Emergency equipment stored adjacent to HLS.
3. CO2 & Dry Chemical Fire Extinguishers.
4. Fire Hose Reel with “chrome foam”.
5. Chem-spill Bucket.
6. Fire Blanket.
7. “Hot Line” to NSWFB.
8. Video Surveillance.
9. Push-button to open access doors & prioritise lifts.

CHARTS RELATED TO THE AERODROME

WAC 3456.

RUTLAND PLAINS

ELEV 50

FULL NOTAM SERVICE NOT AVBL



QLD UTC +10 YRTP
153836S 1415036E VAR 5 DEG E UNCR
AD OPR M.D.H. Pty Ltd, Rutland Plains Station, via Normanton, QLD, 4890.
PH 07 4060 5215. Fax 07 4060 5196.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	118.6 9500FT

CTAF 126.7

CHARTS RELATED TO THE AERODROME

WAC 3112.

Information may be continued on the next page: PTO