
ST ARNAUD

ELEV 640

AVFAX CODE 3038

VIC UTC +10 YSTA
363812S 1431109E VAR 11 DEG E CERT
AD OPR Northern Grampian Shire Council, PO Box 580, Stawell, VIC, 3380. ARO 03 5358 8700 (H24).



PHYSICAL CHARACTERISTICS

09/27	087	18c	5700 kg/0.45 MPa Gravel. Loose stones.	WID 18	RWS 80
18/36	177	33c	5700 kg/0.45 MPa Sealed	WID 18	RWS 80

AERODROME AND APPROACH LIGHTING

RWY 18/36 PTBL(1) BY PRIOR ARRANGEMENT
(1) EMERG use only can be activated on PAL 120.55.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	125.8 to W - On Ground (125.8)
FIA	MELBOURNE CENTRE	126.8 to E

CTAF 119.1

CHARTS RELATED TO THE AERODROME


WAC 3469.

STANTHORPE

ELEV 2934

AVFAX CODE 2088

QLD UTC +10 YSPE
283713S 1515926E VAR 11 DEG E CERT
AD OPR Southern Downs Regional Council, PO Box 26, Warwick, QLD, 4380.
Email: mail@sdrc.qld.gov.au. Council PH 1300 697 372.



REMARKS

AD charges apply. See Council *Fees and Charges* document at www.sdrc.qld.gov.au.

APRONS AND TAXIWAYS

1. TWY A - Code C, WID 15M, bitumen sealed.
2. TWY B - Code B, WID 15M, bitumen sealed.

AERODROME OBSTACLES

Hill APRX 3,090FT AMSL LOC 2.03NM W FM W RWS 08 end infringes COS by 41FT.

PHYSICAL CHARACTERISTICS

08/26	080	56a	Unrated.	WID 30	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 08/26 LIRL PAL+AA 120.05
RWY edge light spacing: 08/26: 60M.

Information may be continued on the next page: PTO

OTHER LIGHTING
1. TWY LGT: Blue edge.
2. APN LGT AVBL for EMERG use only with PN.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA BRISBANE CENTRE 121.2 Circuit Area


CTAF 126.7

ADDITIONAL INFORMATION
Animal hazard (eastern grey kangaroo) exists WI VCY of AD. Recommend ACFT overfly RWY before landing and conduct a full-length backtrack before departure.

CHARTS RELATED TO THE AERODROME
1. WAC 3357.
2. Also refer to AIP Departures and Approach Procedures.

STAWELL ELEV 807

AVFAX CODE 3041



VIC UTC +10 YSWL
370418S 1424425E VAR 11 DEG E CERT
AD OPR Northern Grampians Shire Council, Town Hall, Stawell, VIC, 3380.
ARO 03 5358 8700 H24.

HANDLING SERVICES AND FACILITIES
Aero Refuellers: JET A1 and AVGAS H24 self-serve bowsers. Accepts Aero Refuellers cards, V and MC. PH 02 6540 1850.

PASSENGER FACILITIES
LG/RF/WC.

AERODROME OBSTACLES
Unlit TWR 1,109FT AMSL PSN 370315.9S 1424719.0E. Infringes COS by 96FT.

METEOROLOGICAL INFORMATION PROVIDED
1. METAR/SPECI.
2. AWIS PH 03 8470 3220 - Report faults to AD OPR.
3. AWIS FREQ 122.575 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS
11/29	104	46c	PCR 60/F/D/0.65 MPa/T Centre 23 sealed.	WID 30	RWS 90
18/36	175	28a	5700 kg/0.45 MPa Sealed.	WID 18	RWS 90

AERODROME AND APPROACH LIGHTING
RWY 11/29 LIRL AFRU+PAL 119.1 SDBY PWR AVBL
RWY edge light spacing: 11/29: 58M.

OTHER LIGHTING
1. Secondary PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge on A and B.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 125.8 On Ground

LOCAL TRAFFIC REGULATIONS
1. For all ACFT, casual and short term PRKG use TWY A to the terminal.
2. ACFT below 5,700KG, for longer term PRKG, tie-down area & fuel use TWY B to the APN.

FLIGHT PROCEDURES
1. Right hand CCTS RQ on RWY 18 HJ and RWY 29 HN.
2. Night OPS are prohibited on RWYs 18 and 36.
3. RWY 18 TKOF: At RWY head turn Right to MNTN TR not less than 190DEG MAG.
4. RWY 36 LDG: Base leg must be no further than 2000 FM THR.

CTAF - AFRU 119.1