TROPICANA ELEV 1104

AVFAX CODE 6403

WA UTC +8 YTRA
291112S 1243301E VAR 2 DEG E CERT

AD OPR Anglogold Ashanti Australia Ltd - GPO Box B91, Perth, WA, 6838. PH 08 9265 2000: AD Manager 08 9265 2300, 08 9265 2345. ARO 08 9265 2321, 0409 310 718.



REMARKS

1. Restricted OPS. PPR from AD OPR.
2. PRI source of PWR is derived from a generator.

HANDLING SERVICES AND FACILITIES

JET A1 private installation. AVBL to scheduled and emergency ACFT only.

APRONS AND TAXIWAYS

TWY A: Unrated, sealed, WID 15M.

AERODROME OBSTACLES

1. Lit mast 1,464FT PSN 291246.10S 1243058.34E.
2. Lit weather station tower 33FT AGL PSN 291113.00S 1243301.00E 105M south of RWY centre line infringes transitional SFC.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 08 6216 2639 - Report faults to BoM.
3. AWIS FREQ 133.0 - (requires three one-second pulses to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

09/27 087 69a PCR 201/F/A/1.04 MPa/U WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 09/27	LIRL	AFRU+PAL 126.7		SDBY PWR AVBL
RWY 09/27	PAPI(1)	AFRU+PAL 126.7	3.0 DEG41.3FT	SDBY PWR AVBL
RWY 09/27	PTBL(2)			BY PRIOR ARRANGEMENT

(1) Left side.
(2) EMERG only. 90MIN PN.
RWY edge light spacing: 09/27: 60M.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.75

LOCAL TRAFFIC REGULATIONS

1. All ACFT ABV 5,700KG must use turning nodes for 180DEG turns.
2. All ACFT to make MAX RAD turns at MNM speed to avoid SFC damage.

FLIGHT PROCEDURES

Right hand CCTS RWY 27.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Potential blasting at 1300 or 1800 WST at mine site 3.8NM south of AD.

CHARTS RELATED TO THE AERODROME

1. WAC 3352.
2. Also refer to AIP Departure and Approach Procedures.

TROUGHTON ISLAND — ELEV 27

AVFAX CODE 8607



WA UTC +8 YTTI
134506S 1260854E VAR 2 DEG E CERT
AD OPR Mungalalu North Kimberley Airport Pty Ltd, 1202 Hay Street, West Perth, WA, 6005. Email: gm@mnkairport.com.au.
ARO 08 9161 4235. Website: www.mnkairport.com.au.

REMARKS

Restricted OPS: PPR

METEOROLOGICAL INFORMATION PROVIDED

METAR/SPECI.

PHYSICAL CHARACTERISTICS

14/32 146 32c 5700 kg/0.73 MPa Gravel. WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

RWY 14/32 LIRL(1)
RWY 14/32 PTBL(2) BY PRIOR ARRANGEMENT
(1) EMERG only.
(2) 1HR PN.
RWY end lighting marks the extremities of the RWY strip.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 120.75 5000FT

LOCAL TRAFFIC REGULATIONS

ACFT PRKG will be on the concrete APN unless advised otherwise on arrival.

CTAF 128.0

ADDITIONAL INFORMATION

Significant bird hazard present at all times. Seagulls, terns and assorted migratory seabirds may be present on all areas of the RWY at any time of day. Significant increase in bird activity FM late afternoon to early morning.

CHARTS RELATED TO THE AERODROME

1. WAC 3108.
2. Also refer to AIP Departure & Approach Procedures.

Information may be continued on the next page: PTO