CTAF 127.3

CHARTS RELATED TO THE AERODROME
WAC 3456.

WONDAI

ELEV 1050
FULL NOTAM SERVICE NOT AVBL

QLD UTC +10 YWND
261703S 1515141E VAR 10 DEG E UNCR
AD OPR South Burnett Regional Council, PO Box 336, Kingaroy, QLD, 4610.
PH 07 4189 9100: ALA 0448 184 992. Mobile 0488 911 187.

PASSENGER FACILITIES
PT (EMERG use only).

AERODROME AND APPROACH LIGHTING
PAL 122.3 (PAL is activated using three times two to four SEC pulses WI a 24SEC period).

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	124.6 4000FT

CTAF 126.7

CHARTS RELATED TO THE AERODROME
WAC 3340.

WONDOOLA

ELEV 190
FULL NOTAM SERVICE NOT AVBL

QLD UTC +10 YWDL
183430S 1405330E VAR 6 DEG E UNCR
AD OPR Wondoola Station, via Mt Isa, QLD, 4825. PH 07 4745 3441.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	118.6 Circuit Area

CTAF 126.7

CHARTS RELATED TO THE AERODROME
WAC 3220.

WOODIE WOODIE

ELEV 889

AVFAX CODE 6823



WA UTC +8 YWWI
213843S 1211130E VAR 1 DEG E CERT
AD OPR Pilbara Manganese Pty Ltd, PO Box 1220, West Perth, WA, 6872.
Email: woodienpisupervisors@consminerals.com.au. PH On site
08 9460 7095. ARO 08 9460 7037. ARO AH Emergency 08 9460 7068.

REMARKS
1. Restricted OPS: PPR from AD OPR.
2. Day OPS only.
3. No mobile coverage on site.

HANDLING SERVICES AND FACILITIES
Ground handling agents. Contact ARO.
Fuel facilities: Limited JET A1. Private installation. Contact ARO.

PASSENGER FACILITIES
LG/WC.

AERODROME OBSTACLES
Lit mast 1,042FT AMSL BRG 103 DEG MAG 3,329M FM ARP. Infringes inner HZS by 7FT.

PHYSICAL CHARACTERISTICS

14/32 139 66a PCR 250/F/B/Y/T WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 14/32 PAPI(1) 3.0 DEG48FT
RWY 14/32 PTBL(2) BY PRIOR ARRANGEMENT

(1) Left hand side. 30MIN PN to ARO.
(2) EMERG only 90MIN PN to ARO.

1. RWY edge light spacing: RWY 14/32: 90M apart (PTBL).
2. RWY 14 PAPI units located 430M from RWY 14 THR due 1.47% downward slope - reduced landing distance may be applicable.
3. No mains power AVBL - power supply via on site generator.

OTHER LIGHTING

TWY LGT: Nil.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	134.5 Not AVBL on Ground
UNICOM	WOODIE WOODIE UNICOM	128.9

LOCAL TRAFFIC REGULATIONS

1. All ACFT ABV 5,700KG MTOW must use turning nodes for 180DEG turns at MAX radius, MNM speed.
2. ACFT must follow lead-in lines.
3. RWY 32: all ACFT ABV 5,700KG MTOW must run-out to turning node when landing.
4. RWS not maintained for ACFT OPS.

CTAF 126.7

ADDITIONAL INFORMATION

Blasting scheduled daily however occurs intermittently. Approval must be obtained from ARO or airport manager prior to blasting.

CHARTS RELATED TO THE AERODROME

1. WAC 3230.
2. Also refer to AIP Departure and Approach Procedures.

Information may be continued on the next page: PTO