BALLARAT

ELEV 1433

AVFAX CODE 3011



VIC UTC +10 YBLT
373042S 1434728E VAR 11 DEG E CERT
AD OPR City of Ballarat, Sturt Street, Ballarat, VIC, 3350. PH 03 5320 5500.

REMARKS

1. AD restricted to ACFT BLW 5,700KG.
2. ACFT ABV 5,700KG and/or 450kPa tyre pressure must contact AD OPR for approval - Phone 0437 771 644 or 0418 137 784.
3. Ballarat is a high density Training Aerodrome.
4. AD fees apply - refer to City of Ballarat website for details.

HANDLING SERVICES AND FACILITIES

BP: Ballarat Aviation Group: 2300-0730 UTC DLY. 2 HR PN, Phone 0438 508 576. Call-out fee $40. Credit cards and BP Carnet (H24) AVBL. AVGAS, O125.
Field Air: Phone 03 5330 9330, AH 0437 348 124. Credit card (MC and VISA only) AVBL (H24). JET A1 facility located W of TWY B.

APRONS AND TAXIWAYS

TWY D MAX wing span 15M (Code A).

AERODROME OBSTACLES

1. Towers 1,675FT AMSL, 3,450M SSW of ARP.
2. RWY 05 S side transitional SFC infringed by tower and aerial.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS Phone 03 8470 3202 - Report faults to BoM.
3. AWIS FREQ 134.05 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

05/23	051	42a	PCR 50/F/C/0.45 MPa/T	WID 30	RWS 90
13/31	123	19c	Unrated. Grass	WID 30	RWS 90
18/36	178	59a	PCR 50/F/C/0.45 MPa/T	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 18/36	LIRL(1)	AFRU+PAL 127.75	
RWY 18	PAPI(2)	AFRU+PAL 127.75	3.0 DEG29.5FT
RWY 36	PAPI(3)	AFRU+PAL 127.75	3.0 DEG29.5FT

(1) HN.
(2) Right side.
(3) Left side.
RWY edge light spacing: 18/36: 60M.

OTHER LIGHTING

TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	126.8 2000FT

LOCAL TRAFFIC REGULATIONS

1. Circuit training not permitted BTN 2300-0600 Local.
2. RWY gradients may inhibit visibility from all thresholds and pilots must confirm that both RWYs are clear before landing or takeoff.
3. Visiting ACFT are not to conduct circuit training at any time.

Information may be continued on the next page: PTO

FLIGHT PROCEDURES

1. Right hand CCTS RQ when OPR on RWY 18 or RWY 13.
2. Training flights conducting practice instrument approach should add 1,000FT to all the ALT prescribed in the approach to reduce noise nuisance and interference with circuit traffic. Such flights should BCST their intentions, including ALT limit of OPS when turning inbound. IMC flights should remain as high as practicable when encountering VMC and join the circuit in the standard manner.

CTAF - AFRU 127.75

ADDITIONAL INFORMATION

1. Bird hazard exists.
2. Possible high ab initio training 0700-2300 Local.
3. Model ACFT OPR HJ WI 1,000M RAD of Burrumbeet Racecourse PSN 372944S 1434014E BRG 269 MAG 5.85NM FM ARP SFC to 3,000FT AMSL.

CHARTS RELATED TO THE AERODROME

1. WAC 3469.
2. Also refer to AIP Departure and Approach Procedures.

BALLERA — ELEV 385

AVFAX CODE 4135



QLD UTC +10 YLLE
272430S 1414830E VAR 8 DEG E CERT
AD OPR Santos Ltd, PO Box 2319, Adelaide, SA, 5001. PH 08 8116 5213. ARO 07 4646 8103.

REMARKS

1. Restricted OPS. PPR for all OPS.
2. All OPS: advise AD OPR at least 20MIN prior to ETA on 126.4. CS 'Ballera Base'.
3. AD Charges: Non-company aircraft.
4. Bay 2 for all jet refuelling.

HANDLING SERVICES AND FACILITIES

Private terminal facilities. JET A1 private facility.
Refuelling PH: 08 8678 4107 AVBL H24.

AERODROME OBSTACLES

1. Chimneys:
   a. 573FT AMSL PSN 272322.9S 1414819.9E. Infringes HZS by 50FT.
   b. 568FT AMSL PSN 272325.7S 1414822.1E. Infringes HZS by 45FT.
2. Lit COM TWR, 694FT AMSL PSN 272321.3S 1414836.3E. Infringes HZS by 170FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 07 3564 3702 - Report faults to BoM.
3. AWIS FREQ 128.65 - Report faults to Santos Limited.

PHYSICAL CHARACTERISTICS

03/21	032	59a	PCR 90/F/D/X/T Sealed.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 03/21	LIRL	PAL+AA 120.05		SDBY PWR AVBL
RWY 03/21	PAPI(1)	PAL+AA 120.05	3.0 DEG48FT	SDBY PWR AVBL
RWY 03/21	PTBL(2)			BY PRIOR ARRANGEMENT

(1) Left side.
(2) EMERG only. 60MIN PN.

1. Secondary PWR MAN activated - 45 MIN PN.
2. RWY 03/21 edge light spacing: 60M.

OTHER LIGHTING

TWY LGT: Blue edge.