
BACCHUS MARSH

ELEV 520

FULL NOTAM SERVICE NOT AVBL



VIC UTC +10 YBSS
374400S 1442520E VAR 12 DEG E UNCR
AD OPR Bacchus Marsh Aerodrome Management Inc, PO Box 375, Bacchus Marsh, VIC, 3340. ARO 0439 391 257 or 0407 539 041. Website: www.ybss.com.au.

REMARKS

1. PPR all ACFT - Phone ARO.
2. All ACFT - Refer website for charges and conditions of use.

HANDLING SERVICES AND FACILITIES

IOR Aviation Pty Ltd. JET A1 and AVGAS 100LL AVBL H24 self-serve bowser. Payment via IOR tag or Fuelcharge APP.
TVSA pilot training: AVGAS 100LL 24HR credit card swipe facility. Phone 03 5369 5162.

PHYSICAL CHARACTERISTICS

01/19	51a	Unrated. RWY LEN 1,554M.	WID 18	RWS 150
09/27	50a	Unrated. RWY LEN 1,525M.	WID 18	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 01/19 LIRL PAL 120.0
RWY edge light spacing: 01/19: 60M.

OTHER LIGHTING

TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 135.7

LOCAL TRAFFIC REGULATIONS

1. Carriage and use of radio is required by AD OPR.
2. Non-Bacchus Marsh operators require approval for night training on each occasion.

FLIGHT PROCEDURES

1. Right hand circuits required when operating on RWY 01 HN, due to terrain to the west affecting night circuit operations.
2. Circuit operations not permitted between 2230–0700 Local.
3. Maximum of four aircraft permitted to conduct night circuits simultaneously.
4. All powered ACFT and gliders should broadcast when turning onto base leg.
5. If wind is BLW 5KT and variable, RWY 19 or 27 must be used by all ACFT. Wind ABV 5KT, operate on the most into wind RWY.
6. The following also apply when gliding operations are in progress:
   a. The duty RWY is the RWY in use by the gliding operation.
   b. Gliders and tugs operate from the grass on side of the duty RWY short of the displaced threshold. Other ACFT should land beyond the displaced threshold.
   c. All powered ACFT except tugs should commence take-off from the displaced threshold unless operationally required.
   d. If use of the full runway length is required, the pilot must coordinate with the gliding operation on the CTAF prior to take-off.
   e. Helicopters must follow the standard aeroplane circuit pattern and operate to or beyond the displaced threshold.
   f. Straight-in approaches or joining circuit on base leg are NOT recommended.
   g. Overflying the AD should be avoided. If operationally necessary, overfly as high as practicable.

CTAF 132.25


ADDITIONAL INFORMATION

1. Gliding OPS HJ - Aerotow and winch launched. Gliders and tugs normally operate inside and below standard 1,000FT circuit.
2. Wildlife hazard (kangaroos) exists at various times, mostly dawn and dusk.

Information may be continued on the next page: PTO

CHARTS RELATED TO THE AERODROME
WAC 3469, 3470.

BADU ISLAND
ELEV 45
FULL NOTAM SERVICE NOT AVBL



QLD UTC +10 YBAU
100900S 1421027E VAR 4 DEG E UNCR
AD OPR Torres Strait Island Regional Council, PO Box 7336, Cairns, QLD, 4870. PH 07 4034 5700. ARO 0429 537 202 (H24).

REMARKS
RESTRICTED OPS: PPR from AD OPR.

AERODROME OBSTACLES
1. RWY 12/30 transitional SFC infringed by trees on both side of RWY.
2. Inner HZS infringed by hill W of AD. OBST light not provided.

PHYSICAL CHARACTERISTICS
12/30 Unrated. Sealed.

AERODROME AND APPROACH LIGHTING
RWY 12/30 LIRL(1) PAL 120.6
(1) AD Lighting for EMERG Helicopter OPS only.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA BRISBANE CENTRE 120.3 Circuit area

FLIGHT PROCEDURES
For special procedures which apply to Torres Strait biosecurity requirements, see ERSA GEN - SPECIAL PROCEDURES.

CTAF 126.5

CHARTS RELATED TO THE AERODROME
WAC 3097.

BAIRNSDALE
ELEV 165

AVFAX CODE 3019

VIC UTC +10 YBNS
375315S 1473404E VAR 13 DEG E CERT
AD OPR East Gippsland Shire Council, PO Box 1618, Bairnsdale, VIC, 3875. ARO 0472 796 779: Backup 0438 497 697: Backup (AH) 0447 132 980.
Website: www.eastgippsland.vic.gov.au/building-and-development/aerodromes.

