CTAF - AFRU 126.8

AFRU signal not AVBL on ground Laverton, Murrin Murrin or Sunrise Dam. AFRU located at Leonora.

ADDITIONAL INFORMATION

1. Bird Hazard in VCY of AD (falcons or hawks).
2. Animal hazard (kangaroos). ARO will conduct additional RWY inspection prior to scheduled ACFT OPS.
3. Seasonal wetlands may be present at western end of RWY, ducks, swans and birds of prey maybe in VCY.

CHARTS RELATED TO THE AERODROME


1. WAC 3352.
2. Also refer to AIP Departure and Approach Procedures.

SUNSHINE COAST — ELEV 15

AVFAX CODE 4005

QLD		UTC +10	YBSU
263612S	1530528E	VAR 11 DEG E	CERT

AD OPR Sunshine Coast Airport Pty Ltd, PO Box 9535, Pacific Paradise, QLD, 4564.
PH 1300 993 543. ARO 0419 658 272. PH AH 07 3830 5251.
Website: www.sunshinecoastairport.com.au.



REMARKS

1. AD Charges and Conditions of Use apply to any use of the AD - see website or contact AD OPR for details.
2. Airside access AH requires a call-out (fees apply).
3. This AD is a security controlled airport. All pilots and operators must possess and display a current Aviation Security Identification Card (ASIC) whilst airside unless under escort.
4. GA pilot and pedestrian access/egress via Gate 4 only, 30M north of the fuel bowser. Access to terminal not permitted via Regular Public Transport (RPT) Apron.
5. Limited PRKG for overnight GA ACFT, CTC ARO for PRKG approval.

Information may be continued on the next page: PTO

HANDLING SERVICES AND FACILITIES

Viva Energy Australia (Airport Refuelling Services): DLY 1900-1000 UTC. JET A1 30 MIN PN. PH 0408 711 968 AH surcharges apply. AVGAS 24HR via outdoor payment terminal bowser. Carnet, V and MC.
MACHJET - FBO H24 DLY. PH 0447 182 351 or 07 5457 0778. Email: fbo@machjet.com.au. Full FBO services.
SWISSPORT - FBO email: charters@swissport.com.au or info@skycare.co.nz. PH 0403 455 443.
FLIGHT OPTIONS – FBO PH +61 488 603 132 H24. Email: fbo@flightoptions.com.au.

General

AD OPR does not provide marshalling services.

PASSENGER FACILITIES

PT/TX/HC/BU/LG/RF/WC/ME

RESCUE AND FIREFIGHTING SERVICES

1. CAT 7:
   a. MON 2045-1320 UTC.
   b. TUE-SUN 2045-1155 UTC.
2. 131.0 MHz AVBL HO.
3. Water Rescue Service AVBL.

AERODROME OBSTACLES

1. Mt Coolum lit 710FT AMSL BRG 340 DEG MAG 2.53NM FM ARP. Infringes inner HZS by 551FT.
2. TWR:
   a. Lit 834FT AMSL BRG 258 DEG MAG 5.38NM FM ARP.
   b. Lit communications 212FT AMSL BRG 324 DEG MAG 2.52NM FM ARP. Infringes inner HZS by 49FT.
3. B737/A321 ACFT tail when positioned at TWY F holding point RWY 13/31. Infringes RWY 31 APCH SFC by 14.7FT.
4. Roof unlit 36FT AMSL BRG 084 DEG MAG 240M FM ARP. Infringes RWY 13 TKOF SFC by 4FT.
5. Tree (lit) 257FT AMSL PSN 263541.1S 1530301.5E. Infringes inner HZS by 95FT.
6. Trees (unlit):
   a. 563FT AMSL PSN 263125.6S 1530204.2E. Infringes horizontal section RWY 13 APCH SFC BY 50FT.
   b. 179FT AMSL PSN 263617.3S 1530240.1E. Infringes inner HZS by 17FT.
   c. 51FT AMSL PSN 263613.7S 1530540.5E. Infringes RWY 31 APCH SFC by 2FT.
   d. 57FT AMSL PSN 263611.8S 1530540.1E. Infringes TNS by 10FT.
   e. 81FT AMSL PSN 263436.5S 1530412.6E. Infringes RWY 13 APCH SFC by 16FT.
   f. 86FT AMSL PSN 263431.8S 1530415.1E. Infringes RWY 13 APCH SFC by 16FT.
   g. 74FT AMSL PSN 263439.2S 1530413.1E. Infringes RWY 13 APCH SFC by 14FT.
   h. 60FT AMSL PSN 263446.3S 1530414.4E. Infringes RWY 13 APCH SFC by 12FT.
   i. 54FT AMSL PSN 263448.6S 1530416.3E. Infringes RWY 13 APCH SFC by 12FT.
   j. 62FT AMSL PSN 263447.2S 1530413.1E. Infringes RWY 13 APCH SFC by 14FT.
   k. 49FT AMSL PSN 263455.3S 1530415.3E. Infringes TNS by 6FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT A, METAR/SPECI, AD WRNG.
2. AWIS PH 07 3564 3738 - Report faults to BoM.
3. AWIS FREQ 119.8 AVBL outside TWR HR - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

13/31	131	92a	PCR 690/F/B/X/T Grooved	WID 45	RWS 300

AERODROME AND APPROACH LIGHTING

RWY 13/31	MIRL	AFRU+PAL 124.4		SDBY PWR AVBL
RWY 13/31	PAPI	AFRU+PAL 124.4	3.0 DEG67FT	SDBY PWR AVBL
RWY 13/31	RTIL	AFRU+PAL 124.4		SDBY PWR AVBL

1. RWY edge light spacing: 13/31: 58M.
2. RGL at all RWY/TWY intersections.

OTHER LIGHTING

1. Secondary PWR switchover time: 15 SEC. Does not support TKOF BLW 800M.
2. TWY LGT: Green CL on TWY A, A1, A2, B, B1, B2, J, M, F BTN TWY B1 and RWY 13/31 and Western GA Taxilane.
3. RWY guard LGT
4. Blue edge LGT at RWY 13 turn node.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE		129.0 CCT area - on GND COM CTC 135.2 (outside TWR HR)
ATIS	SUNSHINE COAST	(3)	114.2 (1) 119.8 (2)
SMC	SUNSHINE COAST GROUND		121.1
TWR	SUNSHINE COAST TOWER		124.4

(1) H24.
(2) TWR HR only.
(3) Also AVBL on PH 07 5458 2955.

1. TWR HR:
   2100-0940 UTC DLY. Phone: 07 5458 2953^.
   Note: TWR HR may change at short notice, check status of airspace with ATS or Sunshine Coast ATIS.
2. Sunshine Coast TWR provides combined TWR and APP CTL services within Class D airspace 4,500FT AMSL and BLW DRG TWR HR. CTC TWR for a clearance.
3. Outside TWR HR, Sunshine Coast Class D airspace 4,500FT AMSL and BLW becomes Class G.
4. Brisbane Centre operates Sunshine Coast Class C airspace H24.
5. FIA on ground COMS may be AVBL with ATS dependent on ACFT location and building shielding.

RADIO NAVIGATION AND LANDING AIDS

DME	SU	114.2/ 89X	263551.7S	1530525.1E		(2)
NDB	SU	380	263531.9S	1530530.2E	Range 50 (HN 50)	(3)
VOR	SU	114.2	263551.7S	1530525.1E		(1)

(1) Coverage reduced in minor arc 169 to 340 due terrain shielding. Radial 169 not to be used outside 40NM. DME ARR is not AVBL on SU VOR 340 radial. Bending and scalloping on 224 radial at low altitudes.
(2) Antenna ELEV 36FT.
(3) 172/0.67 to ARP.

LOCAL TRAFFIC REGULATIONS

1. RWY 31: ACFT ABV 80,000KG MTOW to make 180DEG MAX RAD turns following yellow line at RWY end turning node.
2. ACFT ABV 5,700KG RQ prior approval from the AD OPR to OPR BTN HR of 2300 and 0530 Local. PN for HEL OPS RQ (non EMERG).
3. MAX Code C ACFT to occupy TWY F RWY hold point when ACFT on APCH to RWY 31.
4. Code D and E ACFT to hold short at INT hold PSN located on APN TWY B south of TWY B1 to inform ATC ready when RWY 31 duty RWY.
5. TWY F RWY holding PSN not AVBL during low VIS OPS.
6. ACFT Holding Bay AVBL to ACFT MAX wingspan 24M (e.g. E35L), located northern side TWY A2.
7. Pilots to exercise caution on TWY E, BTN TWY M and TWY J due to lack of VIS FM control TWR.
8. Southern PRKG APN Bays 30 and 31 and GA Southern Apron HJ only.
9. Ground Running of engines for maintenance purposes RQ prior approval FM ARO.
10. **TRAINING FLIGHTS**
    a. All ACFT planning practice instrument APCH and NAVAID training require ATC approval, pilots must book a slot online at www.bookawk.com.
    b. Circuit training requires ATC approval, pilots must book a slot online at www.bookawk.com. Circuit training permitted only BTN HR of 2100 and 1200 UTC.

Information may be continued on the next page: PTO

11. **APN AND TWY AVAILABILITY AND RESTRICTIONS**
    a. TWY A BTN TWY A1 and TWY A2, and TWY A2 restricted to MAX wingspan 36M
    b. TWY B2 and APN TWY B BTN TWY B1 and TWY B3: restricted to MAX B737/A321.
    c. TWY B3: restricted to MAX 24M wingspan and 10,000KG.
    d. TWY F south of TWY B1: restricted to MAX 26M wingspan (B737/A320).
    e. TWY M and TWY J: restricted to MAX 20M wingspan and 10,000KG.
    f. TXL D, TXL G and TXL H: restricted to MAX wingspan 15M and 5,700KG (EXCL Cessna 208).
    g. GA PRKG APN, TWY F BTN TWY B1 and TXL C, TXL D, TXL H, TXL G and TWY B3 unlit and restricted to HJ OPS only.
    h. Code D and Code E ACFT restricted to TWY A1, TWY A BTN TWY A1 and TWY F, TWY B1, APN TWY B BTN TWY B1 and TWY G, TWY F north of TWY B1.
    i. TWY E restricted to helicopter OPS. Access to western TXL is via TWY M or J unless otherwise instructed by ATC.

12. **PARKING**
    a. Bay 19A and 20A: restricted to ACFT MAX 32M wingspan.
    b. Bay 19, 19A, 20 and 20A not AVBL to ACFT without prior approval from the AD OPR.
    c. Bays 30 and 31 (Southern PRKG APN) access via TWY F and TXL C
    d. Due to security requirements, all ACFT ABV 5,700KG and are not RPT must obtain prior approval FM AD OPR if they are programmed to stage through or remain at Sunshine Coast. To obtain such approval 48HR notice is required; PH ARO.
    e. GA ACFT BLW 5,700KG not permitted on Air Transport (RPT) APN without prior approval from AD OPR. Access to the Southern GA APN is via TXL C or TXL G. Access to the western TXL is via TWY J, TWY B3 or TWY M.
    f. For any itinerant/GA ACFT requiring to park on the Air Transport (RPT) APN, a ground handler/FBO is required to be engaged by the ACFT operator prior to ACFT parking being allocated by AD OPR (exceptions: RFDS/medical/emergency operations).

13. **START AND PUSHBACK**
    a. Air Transport (RPT) APN Bays pushback RQ.
    b. CTAF pushback procedures:
        (i) During CTAF, all ACFT on RPT APN Bays RQ to pushback.
        (ii) Additional mandatory CTAF ACFT broadcast. ACFT shall broadcast intention to pushback to nominated disconnect point prior to pushback, followed by TAX broadcast when ready as per *AIP GEN*.

14. **HEL OPS**
    a. Southern GA APN – APCH and depart via TWY F or as directed by ATC.
    b. Western GA precinct – to avoid construction zone, APCH and depart via TWY A or as directed by ATC.

FLIGHT PROCEDURES

1. **ATC TRAFFIC MANAGEMENT SPEED**
   When **not** on a SID or STAR (including vectoring) - ACFT ARR or DEP SU via Class C airspace must not exceed 250KT IAS when BLW 10,000FT AMSL. Advise ATC if a higher speed is operationally required.
   Note: Pilots must also comply with Class D airspace speed limits. Cancellation of ATC traffic management speeds does not cancel Class D airspace speed limits.
2. Outside TWR HR - ALL ACFT OPR in circuit area are to BCST position and RWY being used when an inbound call is received FM an ACFT joining the circuit or a call is received FM an ACFT about to taxi.
3. Right hand circuits required when OPR RWY 13 except as directed by ATC.
4. **LOW VISIBILITY OPERATIONS**
    a. LVO AVBL during TWR HR.
    b. Transmissometers not installed. RVR not AVBL.
    c. RWY VIS assessment measurements AVBL.
    d. RWY 13/31 not capable of supporting TKOF when RWY VIS is less than 800M.
    e. Preparations for LVP activation commence when VIS is likely to reduce below 2,750M.
    f. LVP in force when VIS is 800M or less, or cloud base is 200FT or BLW. ATC will limit vehicle movements on the manoeuvring area to Airport Safety Officer, ARFFS and other EMERG vehicles.
    g. TWY F RWY holding point not used when LVP in force.

CTAF - AFRU 124.4
Outside TWR HR.


NOISE ABATEMENT PROCEDURES
Noise Abatement Procedures (NAP) apply. Refer AIP DAP.

ADDITIONAL INFORMATION
1. TWY F RWY holding position located 145M from start of take-off RWY 31.
2. Class D airspace is in close proximity to aerodromes in Class G airspace.
3. Fuel/oil clean-up/disposal are chargeable and must meet Government Environmental standards.
4. Bird and animal hazard exists:
   a. Flying fox transiting south to north - HN only.
   b. Nankeen kestrel (birds of prey) present on airfield.
   c. Australian white ibis flocking on airfield HJ.
   d. Increased ducks in VCY of AD, HN.
   e. Increased Fairy martins and Welcome swallows in VCY of RWY 13/31 strip early morning and late afternoon.
5. PJE OPS:
   a. Occasional operations HJ within 1NM of Maroochydore Sporting Complex Oval BRG 194 DEG MAG 3.3NM from ARP, up to FL150.
   b. DLY HJ at Coolum Beach located BRG 351 DEG MAG 4.0NM from ARP, up to FL150.
6. Model ACFT OPR WI 300M radius of PSN 264005.61S 1530048.34E, BRG 216 DEG MAG 5.7NM FM ARP, SFC to 1,000FT AGL. OPS not ABV 400FT AGL WI Sunshine Coast CTR.

CHARTS RELATED TO THE AERODROME
1. WAC 3340.
2. Also refer to AIP Departure and Approach Procedures.
3. Aerodrome Obstruction Chart Type A: October 2025.

SURAT

ELEV 837
FULL NOTAM SERVICE NOT AVBL



QLD		UTC +10	YSRT
270934S	1490434E	VAR 10 DEG E	UNCR

AD OPR Maranoa Regional Council, PO Box 620, Roma, QLD, 4455.
Email: airport@maranoa.qld.gov.au. PH 1300 007 662.
ARO 0407 730 531. Fax 07 4624 6990.
Website: www.maranoa.qld.gov.au.

REMARKS
1. PPR FM AD OPR.
2. AD Charges: For current fees and charges refer to website.

AERODROME AND APPROACH LIGHTING
PAL+AA 120.05.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	126.0 4000FT

CTAF 126.7

CHARTS RELATED TO THE AERODROME
WAC 3340, 3341.

Information may be continued on the next page: PTO