NOISE ABATEMENT PROCEDURES

1. Pilots are encouraged to adopt the fly neighbourly procedures that are designed to minimise ACFT noise impacts on residential areas. View the document at www.bunbury.wa.gov.au
2. Circuit training is permitted only BTN the FLW HR:
   a. MON-FRI 0700 – 2200 Local
   b. SAT-SUN 0800 – 1800 Local
   c. No circuit training:
      (i) Good Friday
      (ii) Easter Monday
      (iii) ANZAC Day
      (iv) Christmas Day
      (v) New Year's Day
3. ACFT below 600KG and flying below 55KT (microlights/ultralights) permitted to fly 500FT circuits MON-SUN: 0600 - Sunset (Local).

ADDITIONAL INFORMATION


1. Searchlight display OPR FM PSN BRG 327 MAG 3.8NM FM ARP.
2. Model ACFT OPR WI 500M RAD of PSN 333048.00S 1153642.00E BRG 203 MAG 8.8NM FM Bunbury AD (YBUN) SFC to 1,000FT AGL.
3. Bird hazard exists in the vicinity of RWY 07/25.

CHARTS RELATED TO THE AERODROME

1. WAC 3462.
2. Also refer to AIP Departure and Approach Procedures.

BUNDABERG ELEV 107

AVFAX CODE 4022



QLD UTC +10 YBUD
245414S 1521907E VAR 10 DEG E CERT
AD OPR Bundaberg Regional Council, PO Box 3130, Bundaberg, QLD, 4670. Email: airport@bundaberg.qld.gov.au. PH 1300 883 699.
ARO 0418 796 991 (H24).

REMARKS

1. AD Charges: All ACFT.
2. This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES

Air BP - Bundaberg Aviation Fuel; MON-SUN 0730-1700 Local. AH refuelling fee $160 plus GST/ $176 plus GST. Phone H24 07 4155 1061, 0468 425 130. Email: bdbavfuel@gmail.com. H24 Air BP carnet card swipe AVGAS 100LL bowser. JET A1 truck. O117, O125, other 24HR PN. Credit cards office hours only.
IOR Aviation Pty Ltd - JET A1 AVBL truck O/W and U/W MON-SUN 0800-1700 Local. AH call-out available, fees apply, $250.00 plus GST - payment method via IOR Aviation account holders, credit card or EFTPOS. CTC 0484 690 921.

PASSENGER FACILITIES

LG/WC/TX/HC/AC/RF

AERODROME OBSTACLES

1. Lit mast APRX 259FT AMSL BRG 008 DEG MAG 1,957M FM ARP. Infringes inner HZS by 12FT.
2. LIOL on APN light:
   a. APRX 182FT AMSL BRG 017 DEG MAG 585M FM ARP. Infringes TNS by 8FT.
   b. APRX 180FT AMSL BRG 012 DEG MAG 620M FM ARP. Infringes TNS by 6FT.
3. Tree 157FT AMSL BRG 338 DEG MAG 1,312M FM ARP. Infringes VSS by 5FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT B, METAR/SPECI.
2. AWIS Phone 07 3564 3706 - Report faults to BoM.
3. AWIS FREQ 135.45 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

07/25	059	37c	Unrated. Grassed grey silt clay	WID 30	RWS 90
14/32	138	66a	PCR 450/F/C/1.40 MPa/U Grooved. Sealed shoulders 7.5 M wide (old RWY), 3M wide on SE extension.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 14/32	LIRL(1)	AFRU+PAL 126.9		SDBY PWR AVBL
RWY 14	PAPI	AFRU+PAL 126.9	3.0 DEG55FT	SDBY PWR AVBL
RWY 32	PAPI	AFRU+PAL 126.9	3.0 DEG53FT	SDBY PWR AVBL

(1) HN only.

1. RWY edge lighting spacing: 14/32: 60M.
2. PAL only activates PAPI HJ.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Green CL.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	124.1 On ground

RADIO NAVIGATION AND LANDING AIDS

NDB	BUD	302	245423.7S	1521913.1E	Range 65 (HN 60)	(1)

(1) 149DEG MAG 363M FM ARP

LOCAL TRAFFIC REGULATIONS

1. ACFT ABV 23,000KG to execute 180DEG turns at RWY ends.
2. TWY D MAX 5,700KG.
3. RPT APN limited to RPT ACFT and other ACFT approved by the AD OPR with 24HR PN for bay allocation.
4. RPT APN PRKG restrictions apply - not AVBL for GA, helicopters or itinerant ACFT PRKG except for RAAF and government ACFT with PN. Other requests considered with 24HR PN. Email approval for ACFT that require RPT APN due to mass or wingspan limitations. ACFT PRKG and passenger fees apply.
5. GA ACFT engine runs to be conducted in GA area, clear of RPT APN. CTC ARO for other location REQ.
6. Light ACFT with tail skids to confine OPS to RWY 07/25.
7. **HELICOPTER PARKING**
   a. PSN H1 and H2 MAX rotor DIA 13M.
   b. PSN H3 MAX rotor DIA 15M.
   c. Large wheeled HEL park on RPT APN Bay 1 with PN.

CTAF - AFRU 126.9

NOISE ABATEMENT PROCEDURES

1. Preferred RWY 32 for ARR, RWY 14 for DEP.
2. If DEP RWY 32 RQ, full length of RWY to be used.
3. Circuit training permitted 2000-0900 UTC.
4. Night circuit training permitted 0900-1200 UTC for local ACFT. Other ACFT PPR.

ADDITIONAL INFORMATION

1. Ultralight OPS take place WI 1NM RAD Booyan ALA (14NM NW Bundaberg) not above 1,000FT AGL.
2. Winch (rope) launched GFY to A030 at Elliott Field 200DEG/10NM YBUD ARP. Gliders OPR on YBUD CTAF.
3. Access to aprons via pedestrian gates. Code AVBL to bona fide aircrew by contacting the ARO.
4. Pilots, crew and operators must display a current ASIC when airside and have a bona fide reason to be in the Security Restricted Area.
5. Increased flying fox activity in vicinity during twilight periods.


Information may be continued on the next page: PTO

CHARTS RELATED TO THE AERODROME

1. WAC 3340.
2. Also refer to AIP Departure and Approach Procedures.

BURKETOWN ELEV 21

AVFAX CODE 4519



QLD UTC +10 YBKT
174455S 1393204E VAR 5 DEG E CERT
AD OPR Burke Shire Council, Musgrave Street, Burketown, QLD, 4830. Email: office@burke.qld.gov.au. PH 07 4745 5100. ARO 0419 396 224: 0458 004 131. Fax 07 4745 5181.

REMARKS

1. This AD is a Security Controlled Airport.
2. AD Charges: All ACFT
3. Landing Charges $5.50/tonne - MNM $11.
4. Parking: $5.50/overnight. $330/annum.
5. Parking without approval in a no standing area incurs a fine of $27.50.

HANDLING SERVICES AND FACILITIES

Fuel not AVBL whilst RPT ACFT on APN.
Nowland: DLY H24. Phone 07 4745 5107, AH 0427 455 107. AVGAS, JET A1, O125. Credit card self-service bowser (not AMEX or DC).

AERODROME OBSTACLES

1. Marked unlit mast 185FT AMSL BRG 029 MAG 1.30NM FM ARP. Infringes HZS by 20FT.
2. LGT TWR APN 55FT AMSL 114M and 133M FM RWY CL. Infringes TNS by 17FT.
3. Tree 44FT AMSL 84M NW of RWY CL at THR RWY 21. Infringes TNS by 21FT.
4. Fence post 27FT AMSL 78M NW of RWY CL at THR RWY 21. Infringes TNS by 7FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT D, METAR/SPECI.
2. AWIS PH 07 3564 3707 - Report faults to BoM.
3. AWIS FREQ 123.05 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

03/21 037 45a PCR 69/F/C/0.85 MPa/U WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 03/21 LIRL AFRU+PAL 126.7 SDBY PWR AVBL

OTHER LIGHTING

1. Secondary PWR switchover time: 30 SEC.
2. TWY LGT: Blue edge.
3. RWY edge light spacing 60M.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 125.7 3000FT

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

1. Animal activity (wallabies).
2. Gliding OPS HJ during the dry season - winch or towed to 3,000FT.
3. Manned balloon activities to NE of AD may occur morning and afternoon BTN June and September.

CHARTS RELATED TO THE AERODROME

1. WAC 3220.
2. Also refer to AIP Departure and Approach Procedures.