
KAMILEROI

ELEV 300

FULL NOTAM SERVICE NOT AVBL



QLD UTC +10 YKML
192229S 1400322E VAR 5 DEG E UNCR
AD OPR Stanbroke Pastoral Company, PMB 33, Cloncurry, QLD, 4825.
PH 07 4742 5977.

PHYSICAL CHARACTERISTICS

14/32 52c Unrated. Gravel. RWY LEN 1,600M. WID 8

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 122.4 4500FT

CTAF 126.7

ADDITIONAL INFORMATION

Possibility of feral animals on AD.


CHARTS RELATED TO THE AERODROME

WAC 3220.

KARARA

ELEV 1019

AVFAX CODE 6013



WA UTC +8 YKAR
291258S 1164112E VAR 1 DEG W CERT
AD OPR Karara Mining Ltd, Level 2, 216 St Georges Tce, Perth, WA, 6000.
Email: aro@kararamining.com.au. PH 08 6298 1888. ARO 0438 926 212:
MESO 0488 078 025.

REMARKS

Restricted OPS. PPR from AD OPR.

AERODROME OBSTACLES

1. Numerous OBST penetrate inner HZS and conical SFC.
   a. Terrain - LCA BTN 085 DEG MAG and 095 DEG MAG 4,037M to 4,907M FM ARP 1,198FT.
   b. Terrain - LCA BTN 098 DEG MAG and 115 DEG MAG 4,846M to 5,420M FM ARP 1,198FT.
   c. Power poles BTN 319 DEG MAG and 008 DEG MAG 1.6NM FM ARP, up to 100FT.
2. Lit mast - LCA 024 DEG MAG 4,223M FM ARP 1,312 FT AMSL.
3. Perimeter fence unmarked and unlit, north side of entire length of RWY 12/30 and south of SOT RWY 30, 82M FM RWY 12/30 CL. Infringes transitional SFC by 4FT.

PHYSICAL CHARACTERISTICS

12/30 117 46a PCR 130/F/A/Y/T Sealed WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 12/30 PAPI(2) AFRU+PAL 126.9 3.0 DEG41.5FT
RWY 12/30 PTBL(1) BY PRIOR ARRANGEMENT

(1) EMERG only. 2HR PN.
(2) Left side only.
1. PAPI power supplied by generators.
2. Allow 15 seconds for generators to start up and positive confirmation of AD LGT activation communicated through CTAF.
3. PAPI intensity HN manually controlled by ARO via CTAF 126.9.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 124.8 Circuit area
UNICOM KARARA UNICOM 126.9 (1)

(1) Operating when ARO in attendance.

Information may be continued on the next page: PTO

LOCAL TRAFFIC REGULATIONS
All ACFT ABV 5,700KG MTOW to make MAX RAD, MNM speed turns at turning nodes only.

CTAF - AFRU 126.9

ADDITIONAL INFORMATION
Caution: intermittent blasting and associated potential fly-rock at Karara mine site located approximately 5-8NM ENE of ARP.

CHARTS RELATED TO THE AERODROME
1. WAC 3351.
2. Also refer AIP Departure and Approach Procedures.

KARLAWINDA MINE — ELEV 1928

AVFAX CODE 6840



WA UTC +8 YKWA
234652S 1200806E VAR 1 DEG E CERT
AD OPR Greenmount Resources Pty Ltd, Level 1, 28 Ord Street, West Perth, WA, 6005. Email: nmitchell@capmet.com.au. PH 08 9212 4600: AD MGR 0437 830 900 (H24). Fax 08 9212 4699. Website: www.capmetals.com.au.

REMARKS
1. PPR.
2. AD AVBL HJ only.

HANDLING SERVICES AND FACILITIES
Marshalling, parking allocation and ground handling services by prior arrangement with AD MGR.

PHYSICAL CHARACTERISTICS
01/19 007 66a PCR 210/F/A/Y/T WID 30 RWS 280

AERODROME AND APPROACH LIGHTING
RWY 01/19 PAPI(2) 3.0 DEG51FT BY PRIOR ARRANGEMENT
RWY 01/19 PTBL(1) BY PRIOR ARRANGEMENT
(1) EMERG only. 90MIN PN.
(2) Left side. Manually activated 2HR PN. PAPI intensity is manually controlled. CTC ARO via CTAF 122.0

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 123.4

LOCAL TRAFFIC REGULATIONS
1. All fixed wing ACFT ABV 5,700KG must make MAX RAD turns at MNM speed at turn pads to avoid SFC damage.
2. All ACFT to follow APN markings.
3. All jet ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi.
4. RWS not available for flight operations.

CTAF 122.0

ADDITIONAL INFORMATION
1. Blasting at APRX 0500 and 0830 UTC on intermittent days - CTC Blast Controller 0433 050 874:
   a. BRG 293 DEG MAG 2.43NM FM ARP
   b. BRG 293 DEG MAG 960M FM ARP.
2. Caution: Newman (YNWN) AD 28NM to NW. YNWN PROCS overlay and ADJ to PROCS at YKWA.

CHARTS RELATED TO THE AERODROME
1. WAC 3230.
2. Also refer to AIP Departure and Approach Procedures.