KONDININ

ELEV 965

FULL NOTAM SERVICE NOT AVBL

18

36

WA		UTC +8	YKDN
322803S	1181611E	VAR 1 DEG W	UNCR

AD OPR Shire of Kondinin, 11 Gordon Street, (PO Box 7), Kondinin, WA, 6367.
Email: cso@kondinin.wa.gov.au. ARO 08 9889 1006. Mobile 0429 891 006.
Website: www.kondinin.wa.gov.au.

REMARKS

1. OPS allowed include RFDS, private pilots including cropdusters and occasional flight training. ACFT ABV 5,700KG MTOW not permitted.
2. OPR 24HR in case of RFDS.

PASSENGER FACILITIES

Kondinin Roadhouse PH 08 9889 1190.

AERODROME OBSTACLES

Telstra communication mast 1,108FT AMSL BRG 191 MAG 1.54NM FM ARP.

PHYSICAL CHARACTERISTICS

18/36	42c	5700 kg Unrated. Sealed. RWY LEN 1,275M, HN RWY LEN 1,075M.	WID 30

AERODROME AND APPROACH LIGHTING

RWY 18/36 LIRL PAL+AA 120.35

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.4

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Kangaroo hazard exists.

CHARTS RELATED TO THE AERODROME

WAC 3462.

KOOLAN ISLAND/KOOLAN CENTRAL

ELEV 540

AVFAX CODE 6918

WA		UTC +8	YKLC
160733S	1234405E	VAR 2 DEG E	CERT

AD OPR MGX Resources Limited, Level 1, 2 Kings Park Road, West Perth, WA, 6005.
Email: ki.aerodrome@mgx.com.au. PH 08 9426 7500; Site: 08 9423 0858. ARO 0435 009 670.



REMARKS

1. AD is a private installation - PPR FM AD OPR 24HR.
2. PRI and SDBY source of PWR is derived FM generators.

HANDLING SERVICES AND FACILITIES
Air BP - JET A1 via arrangement. CTC ARO.

General
Marshalling provided for all ACFT ABV 5,700KG.

PASSENGER FACILITIES
LG/RF/WC. Telephone facilities AVBL and Telstra 4G mobile reception.

APRONS AND TAXIWAYS
TWY A - Code C, 15M bitumen.

AERODROME OBSTACLES
Lit mast 571FT AMSL BRG 048 MAG 240M FM ARP. Infringes transitional SFC by 3FT.

METEOROLOGICAL INFORMATION PROVIDED
1. TAF CAT C, METAR/SPECI.
2. AWIS FREQ 122.250 (requires three one-second pulses to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS
11/29	113	69a	PCR 342/F/A/1.40 MPa/T Sealed.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING
RWY 11/29	LIRL	AFRU+PAL 127.2		SDBY PWR AVBL
RWY 11/29	PAPI(1)	AFRU+PAL 127.2	3.0 DEG53FT	SDBY PWR AVBL

(1) Left side.

RWY edge light spacing: 60M.

OTHER LIGHTING
1. TWY LGT: Blue edge.
2. SDBY PWR - automatically activated, switchover time: 8 SEC.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA	BRISBANE CENTRE	122.1
UNICOM	KOOLAN ISLAND/KOOLAN BASE UNICOM	129.35 (1)

(1) All OPS advise AD OPR at least 20MIN prior to ETA.

LOCAL TRAFFIC REGULATIONS
1. RWY 11/29: All fixed wing ACFT ABV 5,700KG must make MAX RAD turns at MNM speed at all turn pads to avoid SFC damage.
2. All ACFT to follow APN markings as required.
3. All jet ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi. ACFT that cannot comply with this restriction must advise the AD OPR prior to departure.
4. Pilots are advised that tie-downs in GA parking are untested, and use is at own risk.

FLIGHT PROCEDURES
For special procedures which apply to the Horizontal Falls, see entry under ERSA GEN - SPECIAL PROCEDURES.

CTAF - AFRU 127.2

ADDITIONAL INFORMATION
1. Blasting 0.2NM south FM ARP. Contact ARO for blasting times.
2. Secondary WDI 180M N of RWY 11 THR.

CHARTS RELATED TO THE AERODROME
1. WAC 3223.
2. Also refer to AIP Departure and Approach Procedures.

Information may be continued on the next page: PTO