LEINSTER

ELEV 1631

AVFAX CODE 6106



WA UTC +8 YLST
275036S 1204212E VAR 1 DEG E CERT
AD OPR BHP Nickel West Pty Ltd, LNO, PO Box 22, Leinster, WA, 6437.
Email: leinsteraerodrome@bhp.com. PH AD MGR 0450 031 931.
Email: joseph.buchanan@bhp.com. ARO PH 08 9026 5068:
0460 024 827 (H24).

REMARKS

1. AD Charges: All ACFT.
2. PPR for all OPS. CTC ARO via email.

HANDLING SERVICES AND FACILITIES

JET A1 by prior arrangement with BHP Nickel West, account required. CTC AD MGR to set up account. AD not manned H24. Contact ARO (H24) for refuelling.

PASSENGER FACILITIES

LG/RF/WC.

AERODROME OBSTACLES

1. Lit tower:
   a. Frame 1,871FT AMSL PSN 274855.42S 1204207.04E. Infringes inner HZS by 96FT.
   b. Stack 1,786FT AMSL PSN 274854.11S 1204154.72E. Infringes inner HZS by 11FT.
2. Unlit site (dump) 1,833FT AMSL PSN 274910.13S 1204235.77E. Infringes inner HZS by 59FT.
3. Unlit terrain:
   a. 1,797FT AMSL PSN 274829.72S 1204049.11E. Infringes COS by 9FT.
   b. 1,783FT AMSL PSN 274841.42S 1204112.79E. Infringes inner HZS by 8FT.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 08 6216 2624 - Report faults to BoM.
3. AWIS FREQ 124.0 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

10/28	099	59a	PCR 210/F/A/Y/T Sealed	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 10/28	LIRL(1)	PAL+AA 119.6		SDBY PWR AVBL
RWY 10	PAPI(2)	PAL+AA 119.6	3.0 DEG44FT	SDBY PWR AVBL
RWY 28	PAPI(2)	PAL+AA 119.6	3.0 DEG43FT	SDBY PWR AVBL

(1) HN
(2) Left side.

OTHER LIGHTING

1. SDBY PWR switchover time: 8 SEC. Automatic activation.
2. TWY LGT: Blue edge.
3. TWY holding point LGT: 2 x yellow.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	118.95 Circuit Area

RADIO NAVIGATION AND LANDING AIDS

NDB	LST	230	275026.3S	1204201.0E	Range 70 (HN 70)	(1)

(1) Pilot monitored.

LOCAL TRAFFIC REGULATIONS

1. All ACFT performing 180 DEG turns on RWY must be at MNM speed and MAX RAD WI the RWY turning nodes.
2. ACFT must be at taxiing speed when turning into and out of TWY/RWY.
3. ACFT must follow lead in lines:
   a. DH8D/E190/F100 - Use lead in/out line A.
   b. B190/DH8C/F70/PC24/SW4 - Use lead in/out line B.
4. Refuelling only AVBL on Bay 1.

FLIGHT PROCEDURES
Right hand circuits required RWY 10.

CTAF - AFRU 126.5

ADDITIONAL INFORMATION
1. Blasting occurs at Harmony Pit (BRG 350 DEG MAG 4.09NM FM ARP) and Camelot Pit (BRG 343 DEG MAG 9.56NM FM ARP). Pilots are requested to avoid overflying these mining sites.
2. Increased bird activity post rainfall events (typically between January and June). NOTAM will be issued during periods of increased wildlife.

CHARTS RELATED TO THE AERODROME
1. WAC 3345.
2. Also refer to AIP Departure and Approach Procedures.

LEONGATHA

ELEV 263

FULL NOTAM SERVICE NOT AVBL



068° 3.5NM
Leongatha

VIC UTC +10 YLEG
382944S 1455135E VAR 13 DEG E UNCR
AD OPR Leongatha Aerodrome Users Pty Ltd, PO Box 310, Leongatha, VIC, 3953. PH 03 5664 3288: 0408 515 475.

REMARKS
1. AD Charges: $10/engine.
2. PPR for visiting ACFT

HANDLING SERVICES AND FACILITIES
Fuel supplied by IOR Aviation Pty Ltd. JET A1 and AVGAS AVBL H24 self-serve bowsers. Payment method via IOR Aviation tag for account holders or via the Fuelcharge APP. PH 1300 457 467.

PASSENGER FACILITIES
WC

PHYSICAL CHARACTERISTICS

04/22	30a	5700 kg/0.45 MPa Sealed. RWY LEN 924M.	WID 18	RWS 90
18/36	22a	5700 kg/0.45 MPa Sealed. RWY LEN 669M.	WID 18	RWS 90

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	123.35 Circuit Area

FLIGHT PROCEDURES
1. Right hand circuits RQ when OPR on RWY 04 and RWY 36.
2. OPS to N of AD to be by day and VMC only.

CTAF 127.55

ADDITIONAL INFORMATION
1. Gliding OPS HJ. Gliders OPR WI RWS. Wire launching.
2. Intensive low level agricultural training within 5NM RAD.

CHARTS RELATED TO THE AERODROME
WAC 3470.

Information may be continued on the next page: PTO