METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 07 3564 3727 - Report faults to BoM.
3. AWIS FREQ 122.075 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

16/34	163	50a	PCR 240/F/D/Y/U Sealed.	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 16/34	LIRL(2)	AFRU+PAL 127.5		SDBY PWR AVBL
RWY 16/34	PAPI(3)	AFRU+PAL 127.5	3.0 DEG48FT	SDBY PWR AVBL
RWY 16/34	RTIL(1)	AFRU+PAL 127.5		SDBY PWR AVBL

(1) H24
(2) HN and low LGT conditions only.
(3) H24. PAPI left side.
RWY edge light spacing: 16/34: 60M.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	BRISBANE CENTRE	128.55 Circuit area (On ground COM contact 118.45)

LOCAL TRAFFIC REGULATIONS

1. All ACFT performing 180 DEG turns on RWY must be at MNM speed and MAX RAD WI the RWY turning nodes.
2. All ACFT entering or vacating TWY must be at MNM speed.

FLIGHT PROCEDURES

1. RWY 34 right hand CCTS HJ and HN.
2. Mandatory final APCH call.
3. Due to RWY profile causing possible obstructed VHF COM, ACFT must BCST intentions on CTAF before operating on RWY.

CTAF - AFRU 127.5

ADDITIONAL INFORMATION

1. Blasting may take place 5NM S through to SW WI the open cut mine site (CTC 0439 668 368 for INFO).
2. Bird and animal hazard exists year round with risk species varying depending on weather conditions. Pilots should CTC ARO for real time wildlife hazard report.
   a. Black kite, magpie, bustard, galah and crows are present all year round.
   b. Flying foxes are a seasonal risk at dawn and dusk in VCY of RWY 16/34 APCH and DEP tracks. Peak risk period is DEC-FEB, although potential exists year round.

CHARTS RELATED TO THE AERODROME

1. WAC 3234, 3235.
2. Also refer to AIP Departure and Approach Procedures.

MORAWA — ELEV 902

AVFAX CODE 6032



WA		UTC +8	YMRW
291205S	1160119E	VAR 1 DEG W	CERT

AD OPR Shire of Morawa, PO Box 14, Morawa, WA, 6623.
Email: admin@morawa.wa.gov.au. PH 08 9971 1204.
ARO 0499 829 302 (H24).

METEOROLOGICAL INFORMATION PROVIDED

METAR/SPECI.

PHYSICAL CHARACTERISTICS

09/27	090	32c	5700 kg/0.55 MPa Sand/Gravel.	WID 18	RWS 60
15/33	150	44c	PCR 40/F/A/Y/U Sand/Gravel.	WID 30	RWS 80

Information may be continued on the next page: PTO

AERODROME AND APPROACH LIGHTING
RWY 15/33 PTBL(1)
(1) EMERG only. Solar lighting. Automatic activation HN.

ATS AND AERODROME COMMUNICATION FACILITIES
FIA MELBOURNE CENTRE 124.8

LOCAL TRAFFIC REGULATIONS
Prior permission required for overnight parking. Contact AD OPR.

CTAF 126.7

CHARTS RELATED TO THE AERODROME
1. WAC 3351.
2. Also refer to AIP Departure and Approach Procedures.

MOREE **ELEV 701**

AVFAX CODE 2057



NSW UTC +10 YMOR
292956S 1495041E VAR 11 DEG E CERT
AD OPR Moree Plains Shire Council, PO Box 420, Moree, NSW, 2400. PH 02 6757 3222. ARO 24HR 0428 681 319. Fax 02 6752 6030.

REMARKS
1. AD Charges: All ACFT.
2. YMOR is a Security Controlled Airport. ASIC/VIC regulations apply.
3. RWY 01/19 AVBL H24.
4. Terminal opening hours (Local):
   MON and TUES 0730-1530
   WED - FRI 0730-2000
   SAT 0730-1230
   SUN 1700-2000

HANDLING SERVICES AND FACILITIES
AIR BP - Austrek Aviation Pty Ltd: AVGAS H24 cardswipe bowser (BP Carnet, V, MC, AMEX and EFTPOS). JET A1 tanker, overwing and pressure refuelling. 1HR PN required for all ACFT. No call-out fee. TEL 0418 651 081. Email: admin@austrekair.com.au.

PASSENGER FACILITIES
TX/LG/WC/HC/RF/ME

AERODROME OBSTACLES
1. LIOL - TWR 916FT/356DEG MAG, 3,550M FM RWY 23 RWS end.
2. Aerials on silo 920FT/084DEG MAG, 730M FM RWY 23 RWS end.
3. Flour Mill lit 855FT/347DEG MAG 3,020M FM SOT RWY 01.
4. Transient heavy vehicles 713FT AMSL PSN 292929.1S 1495054.0E. Infringes RWY 19 APCH SFC by 6FT.

METEOROLOGICAL INFORMATION PROVIDED
1. TAF CAT C, METAR/SPECI, AD WRNG.
2. AWIS Phone 02 9353 6435 - Report faults to BoM.
3. AWIS FREQ 129.2 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

01/19	006	53a	PCR 360/F/D/1.00 MPa/T	WID 30	RWS 150
05/23	047	32c	Unrated. Gravel. Central 10M sealed	WID 23	RWS 90

AERODROME AND APPROACH LIGHTING

RWY 01/19	LIRL	AFRU+PAL 126.7		SDBY PWR AVBL
RWY 01/19	PAPI(1)	AFRU+PAL 126.7	3.0 DEG51FT	SDBY PWR AVBL

(1) Left side only.
RWY edge light spacing: 60M.