LOCAL TRAFFIC REGULATIONS
1. ACFT ABV 5,700KG MTOW use RWY ends only for 180DEG turns.
2. Limited Itinerant PRKG to NE edge of APN. CTC AD Manager.
3. APN PRKG Position 3 for Dash 8 OPS only (HJ).
4. ACFT PRKG Position 1 Night OPS only for F100 and below.

FLIGHT PROCEDURES
1. Due terrain no circling to the north of RWY 09/27.
2. LEFT hand CCTS ONLY RWY 27.
3. DEP RWY 27 left hand turn as soon as practicable after TKOF. North bound TFC to intercept track overhead YCHK.
4. RIGHT hand CCTS ONLY RWY 09.
5. DEP ACFT to use RWY 09 in calm wind conditions.
6. All ACFT to call airborne on CTAF FREQ as soon as practicable after TKOF.

CTAF - AFRU 127.05
1. AFRU not AVBL on ground.
2. FREQ confirmation by (YCHK) UNICOM on receipt of taxi departure call (YCHK UNICOM confirm 127.05).

ADDITIONAL INFORMATION
1. Blasting occurs in the following:
   a. E and SE quadrants outside 6,000M from ARP.
   b. SW and SSE quadrants outside 5,000M from ARP.
   c. SW quadrants outside 2,000M from ARP.
2. Dust plumes may occur following blasting.
3. YFDF is in close proximity and the APCH/DEP tracks cross close to the ground. Due to terrain shielding, VHF contact with ACFT on or close to the ground at YFDF is not possible.

CHARTS RELATED TO THE AERODROME
1. WAC 3229.
2. Also refer to AIP Departure and Approach Procedures.

CHRISTMAS ISLAND — ELEV 913

AVFAX CODE 9807

OTH		UTC +7	YPXM
102702S	1054125E	VAR 0 DEG E	CERT

AD OPR Toll Remote Logistics - Locked Bag 860, Christmas Island, Indian Ocean, WA, 6798. Email: christmas.airport@tollgroup.com.
PH Airport OPS +61 8 9164 8498. Mobile AH Duty Officer 0447 109 143.

REMARKS
1. AD Charges apply to all ACFT. Contact AD Manager for charges.
2. PPR for all non RPT flights by fax or email to AD Manager at least 24HR prior to arrival.
3. All ACFT arrivals at Christmas Island are treated as International arriving ACFT regardless of last port (including arrivals from Australian mainland) and are subject to Customs and Quarantine declaration.
4. Due limited space, operators should notify AD OPR of EST time of ARR.
5. This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES
AIR BP: JET A1. HO by arrangement. Phone 0419 644 277 H24.
Altitude: FBO services. VIP services. H24. WC and watering services AVBL. Facilitation of Customs/Quarantine/Airport permits. Email: operations@ciremovals.com.au.
Phone 0407 474 968. VHF 129.25 Callsign ‘Christmas Operations’.

PASSENGER FACILITIES
TX/HC/LG/WC (by prior arrangement).

AERODROME OBSTACLES

1. OLS extensively infringed to west of RWY and extended centre line - confine manoeuvring in IMC or night to east of RWY.
2. Transitional SFC infringed both sides of RWY.
3. Terrain hazard beacon 994FT AMSL BRG 352 DEG MAG 1,979M FM ARP.
4. Lit DVOR lightning rod 997FT AMSL BRG 358 DEG MAG 2,255M FM ARP.
5. DVOR hazard LGT 994FT AMSL BRG 357 DEG MAG 2,246M FM ARP.
6. DME hazard LGT 992FT AMSL BRG 359 DEG MAG 2,261M FM ARP.
7. Lit lighting towers 1,120FT AMSL BRG 333 DEG MAG 1,195M FM ARP.
8. Masts (lit for NGT OPS):
   a. 1,185FT BRG 300 DEG MAG 2,110M FM ARP.
   b. 1,045FT BRG 017 DEG MAG 1,893M FM ARP.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT A, METAR/SPECI.
2. AWIS PH 08 6216 2606 - Report faults to BoM.
3. AWIS FREQ 126.25 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

18/36 175 69a PCR 350/F/A/X/T WID 45 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 18/36	LIRL	AFRU+PAL 132.2		SDBY PWR AVBL
RWY 18/36	PTBL(2)			BY PRIOR ARRANGEMENT
RWY 18	PAPI(1)	AFRU+PAL 132.2	3.2 DEG51FT	SDBY PWR AVBL
RWY 36	PAPI(1)	AFRU+PAL 132.2	3.0 DEG53FT	SDBY PWR AVBL

(1) Both sides - Intensity automatic
(2) EMERG only. 90MIN PN.
RWY edge light spacing: 18/36: 60M.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIS	BRISBANE INO-1 INTL HF WI SELCAL	(1)	3476 5634 8879 13306 17961
FIS	JAKARTA SEA 3 INTL HF WI SELCAL	(2)	3470 6556 11396 13318 17907

(1) For flights departing to or arriving from Australian mainland and territories.
(2) Flights departing to and arriving from the N.

RADIO NAVIGATION AND LANDING AIDS

DME	XMX	112.4/ 71X	102548.5S	1054124.0E	(1)
VOR	XMX	112.4	102548.8S	1054121.6E	

(1) Antenna ELEV 988FT.
All NAVAIDS Privately operated/Pilot Monitored.

LOCAL TRAFFIC REGULATIONS

1. All ACFT ABV 36,000KG MTOW to use RWY ends for 180DEG turns.
2. APN not AVBL to other ACFT during C17 OPS.

FLIGHT PROCEDURES

1. Right hand circuits required on RWY 36.
2. Straight-in approaches permitted at night. Recommended that ACFT arriving at night establish on final of instrument approach procedure.
3. Approach slope guidance (PAPI) REQ for all high capacity ACFT OPS.

CTAF - AFRU 132.2

Information may be continued on the next page: PTO

ADDITIONAL INFORMATION

1. Bird hazard exists.
2. No RFFS provided.
3. Expect moderate turbulence on late final approach when surface wind velocity above 15KT - especially from easterly direction.
4. Hazardous conditions may exist for ACFT when departing on RWY 18 with a E/SE cross-wind ABV 10KT. Due to close proximity of small hill NE of RWS, ACFT are shielded until APRX 800M FM SOT RWY 18.

CHARTS RELATED TO THE AERODROME

1. WAC 3103.
2. Aerodrome Obstruction Chart Type A: July 2026.
3. Also refer to AIP Departure and Approach Procedures (DAP West).

CLARE VALLEY

ELEV 1120

FULL NOTAM SERVICE NOT AVBL



SA UTC +9:30 YCVA

334230S 1383500E VAR 8 DEG E UNCR

AD OPR Clare Valley Flying Group Inc, PO Box 1502, Clare, SA, 5453.
Email: cvfg@clarevalleyaerodrome.com.au. PH Chairman - 0418 891 205.
Mobile Secretary - 0407 829 584. Website: www.clarevalleyaerodrome.com.au.

REMARKS

Donations for use appreciated.

HANDLING SERVICES AND FACILITIES

AVGAS AVBL H24. Use Compac Pay mobile APP. Organisation code for site: 389KP4
PH: 0412 602 447.

PASSENGER FACILITIES

LG/WC/TX/RF. Courtesy car AVBL at AD. Further information and bookings AVBL online: www.clarevalleydownwind.com.au.

PHYSICAL CHARACTERISTICS

09/27	20c	Unrated. Grass. RWY LEN 600M.	WID 30	
17/35	41a	Unrated. Sealed. RWY LEN 1,250M.	WID 18	RWS 22

AERODROME AND APPROACH LIGHTING

RWY 17/35 LIRL PAL 120.05

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 118.95

CTAF 126.7

NOISE ABATEMENT PROCEDURES

1. All ACFT to avoid overflying Bungaree Station 1.3NM SW THR RWY 35 BLW 2,300FT AMSL.
2. ACFT to track close downwind when using RWY 35 to avoid Bungaree Station.
3. TRNG ACFT inbound from S to track via overhead Clare township not below 2,600FT AMSL.

ADDITIONAL INFORMATION

Kangaroo and deer hazard may exist.

CHARTS RELATED TO THE AERODROME

WAC 3458, 3459.