
NOWRA

ELEV 399

AVFAX CODE 2122

NSW UTC +10 YSNW
345656S 1503213E VAR 13 DEG E MIL
AD OPR NAVY, Naval Air Station Nowra, NSW, 2540.
Email: albatross.airoperations@defence.gov.au. PH Airfield Coordination Centre: 02 4449 2161: AH Duty Officer 0411 127 367.



REMARKS

1. **MIL OPS ONLY.** NAVAID training for CIV ACFT AVBL outside of ATS hours.
2. Visiting MIL ACFT 24HR PN to Airfield Coordination Centre. All visiting MIL aircrew conducting flying activities at Nowra (YSNW) and Jervis Bay Airfield (YJBY) are to read and comply with FIHA AD2 supplement Nowra.
3. Due to proximity of Navy SUA, NWX and TSX should be included when checking NOTAM.

HANDLING SERVICES AND FACILITIES

Fuel not AVBL for visiting civil ACFT.
F44, O147, H576, H515, E10, E13.
Aircraft PIC should be prepared to refuel aircraft as only tanker driver provided.

General

MARSHALLING Provided - 24HR PN.
ACFT wash FAC on the FLW FREQ:
WASH 1 - EC135 size ACFT - 376.75;
WASH 2 - H60 size ACFT - 377.75;
WASH 3 - C130 size ACFT - 378.75.

RESCUE AND FIREFIGHTING SERVICES

1. CAT 5 AVBL 2300-1300 UTC MON-THU and 2300-0600 UTC FRI EXC PH.
2. During HDS CAT 5 2200-1300 UTC MON-THU and 2200-0500 UTC FRI EXC PH.
3. CAT 4 OT.
4. CAT 6 AVBL 72HR PN.
5. CAT 5 or CAT 6 outside published HR will be at cost to user.
6. RFFS MNT 118.85MHz outside AD HR.

APRONS AND TAXIWAYS

1. Low strength bitumen areas outside TWY sidelines not AVBL for taxi.
2. TWY G and Civil APN PCR 120/D.
3. TWY J, H and Romeo APN PCR 180/D.
4. Central and Hot Refuel APN PCR 80/D.
5. TWY B and C infringe RWS. MNM 41M wing tip CLR BTN C17 on RWY 03/21 and C17 on TWY B. MNM 11M wing tip CLR BTN C17 on RWY 08/26 and C17 on TWY C. ACFT with a wing span of 36M or greater can perform LDG or TKOF OPS to the RWY with the respective parallel TWY being occupied provided that:
   a. conditions are VMC;
   b. neither ACFT is subject to an emergency;
   c. the RWY is dry or wet but not contaminated;
   d. the parallel TWY is occupied by an ACFT with a wingspan less than 36M.
6. TWY A2 Inverts 1 and 2 are 14M wide, fixed wing ACFT to exercise caution when using these inverts. Inverts 3 to 6 are 6.6M wide, AVBL MIL HELO only. Invert 7 is 19M wide.
7. TWY E2 and J2 helicopters only. Fixed wing approved on REQ.
8. TWY A1, C and F shoulders 1-2M WID.
9. TWY A, B, C, D, E, F and Hot Refuel APN inverts 15M WID 10. TWY G and H 9M WID 11. TWY J 10.5M WID.

SURFACE MOVEMENT GUIDANCE

1. Distance to run markers (lit) located both sides of all runways.
2. RWY 21 aiming point markers aligned with PAPI.
3. TWY A RWY 26 holding point located at non-standard position on TWY A2 prior to TWY A1. Holding point marked by pavement marking, lights and MAG sign.

AERODROME OBSTACLES

1. Lit OBST. MET sensor masts 43FT AGL outside RWS as follows:
   a. Mast S ABM RWY 26 PAPI, N ABM HP C/RWY 03, W RWY 21 ABM ILS;
   b. Masts at FLT deck PROC trainer helipad 0.37NM S THR RWY 03.
2. RWY 21 2% APCH SFC infringed by:
   a. Trees both sides of RCL WI 493M FM THR up to 63FT ABV THR ELEV.
   b. Fence Along Road on RCL WI 422M FM THR 25FT ABV THR ELEV.
   c. Transient OBST on Road 177M FM THR along RCL up to 18FT ABV THR ELEV.
   d. Transient OBST on Road 435M FM THR along RCL up to 36FT ABV THR ELEV.
3. Lit OBST radar 45FT AGL BRG 327 MAG 0.2NM FM ARP.
4. TACAN 51FT AGL BRG 240 MAG 350M FM ARP. Infringes RWY 03/21 TKOF/APCH SFC by 42FT.
5. Trees:
   a. Up to 436FT AMSL WI 60M radius of PSN 345558.8S 1503328.1E.
   b. Up to 433FT AMSL WI 140M radius of PSN 345558.8S 1503328.1E.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT B, METAR/SPECI, TAF3 issued hourly AVBL during MO HR (2100-1000 UTC MON-THU, 2100-0500 UTC FRI, EXC PH, OT by TAF RMK/NOTAM).
2. AWIS Phone 02 9353 6444 - Report faults to BoM.
3. AWIS FREQ 125.65, 280.4, 359 - Report faults to 02 4424 1269.
4. MET INFO AVBL FM Airservices Pilot Briefing. Elaborative briefing FM RAN MO 02 4424 1269 when staffed. AH AVBL FM MWO 02 9296 1527.

PHYSICAL CHARACTERISTICS

03/21	031	67a	PCR 360/F/C/2.00 MPa/T Grooved.	WID 45	RWS 230
08/26	081	69a	PCR 360/F/C/2.00 MPa/T	WID 45	RWS 150

RWY 03/21 and 08/26 shoulders 1-2M WID.

Information may be continued on the next page: PTO

AERODROME AND APPROACH LIGHTING

RWY 03/21	HIRL	PAL+AA 122.2		SDBY PWR AVBL
RWY 03/21	PTBL(2)			
RWY 03	PAPI(1)		3.0 DEG52FT	SDBY PWR AVBL
RWY 21	HIAL-CAT I			SDBY PWR AVBL
RWY 21	PAPI(3)		3.0 DEG50FT	SDBY PWR AVBL
RWY 08/26	HIRL	PAL+AA 122.2		SDBY PWR AVBL
RWY 08/26	PTBL(2)			
RWY 08	PAPI(4)		3.0 DEG57FT	SDBY PWR AVBL
RWY 26	PAPI		3.0 DEG52FT	SDBY PWR AVBL
RWY 26	SALS			SDBY PWR AVBL

(1) Left side.
(2) 30MIN PN
(3) Right side only. Aligned with ILS GP.
(4) Right side
1. **ALS type and length**
   a. RWY 21 - distance coded CL: 724M.
   b. RWY 26 - distance coded CL: 240M.
2. Rising terrain APP RWY 08/TKOF RWY 26. Marked by bi-directional red LGT.
3. Caution: some obstruction LGT not Light Enhancement device (NVG) compatible.
4. SDBY PWR AVBL. 15SEC nominal interruption.

OTHER LIGHTING

ABN	ALTN 10 WG	ELEV 681FT. Co-located with radar antennae BRG 055 DEG MAG 1.86NM FM ARP.

1. TWY light: Green CL.
2. TWY G lighting activated by PAL+AA 120.45.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	121.2 Circuit Area (Outside APP/TWR HR)
ACC	NOWRA CENTRE	132.3 325.8
ACD	NOWRA DELIVERY	128.35 (3)
AFIS	NOWRA INFORMATION	118.85
APP	NOWRA APPROACH	123.5 243.0 352.15
ATIS	NOWRA	125.65 280.4 359 (2)
SMC	NOWRA GROUND	135.85
SMCV	NOWRA GROUND	122.05
TWR	NOWRA TOWER	118.85 243.0 (1) 267.2 359 (2)

(1) Guarded ATS HR. Test transmissions on 243.0 not exceeding 10 SEC 2115-2130 on the first working day of each week.
(2) Transmits voice to ACFT with COM failure.
(3) Start Clearance not RQ unless specified by NOTAM or ATIS.
1. ATS hours notified by R421A/B NOTAM (refer NWX). Outside ATS hours CTAF procedures apply. ATS may be ACT at short notice, check YSNW ATIS for status.
2. Automatic retransmit FAC exists BTN FLW FREQ: 123.5/352.15/118.35, 118.85/267.2.
3. Nowra Approach FREQ 118.35: Jervis Bay (Bhewerre Ridge Repeater) - Use only when directed by ATC or when poor COM with APP BTN YJBY S to UDA.
4. NWA ATC do not control adjacent and overlapping MOA (TSX Airspace Group: M440, M441 and M444), including portions of M441 and M440AB overlapping R421A. Clearance to enter active MOA not AVBL through NWA ATC. Requests for access to be directed to the Controlling Authority.

RADIO NAVIGATION AND LANDING AIDS

DME	INA	108.5/ 22X (RWY21)	345613.6S	1503253.3E		(4)
GP	INA	329.9 (RWY21)	345613.6S	1503253.2E		(3)
ILS	INA	108.5 (RWY21)	345706.0S	1503159.1E		(2)
LOC	INA	108.5 (RWY21)	345706.0S	1503159.1E		
NDB	NWA	359	345704.4S	1503147.2E	Range 90	(1)
TAC	NWR	112.4/ 71X	345703.8S	1503216.8E		(5)

(1) Limitations:
a. Unreliable at MSA in sector 170DEG through north to 030DEG beyond 10NM. Voice AVBL to ACFT with COM failure.
b. Limited coverage to 72NM on 245 RAD at all levels.
(2) ILS Critical Area not protected outside ATS HR.
(3) GP not to be used outside 6 DEG right of centreline.
(4) Antenna ELEV 118FT.
(5) Terrain shielding BLW 4,300FT beyond 25NM BTN 090DEG to 095DEG and 240DEG to 249DEG.

All NAV AIDS Pilot MNT outside ATS HR.

LOCAL TRAFFIC REGULATIONS

1. Start CLR not RQ unless specified by NOTAM or ATIS. When specified by NOTAM or ATIS, start CLR RQMNTS shall apply to all ACFT WI 5NM of AD due PJE OPS.

2. TRAINING FLIGHTS

a. 24HR PPR for all visiting ACFT intending to conduct an INSTR APCH FM Airfield Coordination Centre and a PLN must be submitted for NAVAID training.
b. Visiting ACFT conducting practice INSTR APCH may be instructed to go-around by TWR or delayed by APP to afford LCA RAN circuit/TRNG ACFT priority.
c. Reciprocal IFR INSTR APCH training to duty circuit RWY not permitted.
d. Low overshoot or go-around subject to ATC approval when no conflicting circuit ACFT.
e. IFR practice INSTR APCH BLW 3,000FT AMSL may not be AVBL to visiting ACFT.
f. In VMC delays may be avoided or reduced by operating VFR
g. Prior approval does not guarantee use of the aid.
h. NAV and LDG LGT are to be on prior to intercepting final.
i. 24HR PN for Flight Deck PROC Trainer. Email: ta-avn.fdtu@defence.gov.au.

3. HOT LANE - MILITARY

Upon declaration of hot lane, airborne MIL ACFT are to initiate a go-around, maintain circuit ALT or proceed as directed by ATC. ACFT on the RWY are to immediately position:
a. Left side of the RWY on 21/08;
b. Right side of the RWY on 03/26, and
c. ACFT beyond the 1,000FT DIST to run marker board are to expedite TAX.

4. No overflight of hot refuel facility (ADJ TWY B4) BLW 200FT AGL.
5. Emergency Services/MED ACFT to meet Ambulance for transfer are to use the APN in front of fire station located east of TWY E1.

FLIGHT PROCEDURES

1. AIR TRAFFIC SERVICES

1.1. Class D ATS provided WI R421 to all ACFT.

2. FLIGHT PLANNING

2.1. All FLT planned to take place in R421 RQ submission of FLT details – excluding Circuit Area (CIRA) OPS and Mercy flights.
2.2. FLT notification acceptance by radio is subject to ATS workload. VFR OPS in R421 should PLN prior to DEP. Failure to do so may result in DLA.
2.3. YSNW is in close proximity to multiple MOA (M440, M441, M442, M444). Active MOA are not AVBL for use without Controlling Authority approval, including the portions of M440AB and M441 overlapping R421A. NWA ATC do not control these MOA and cannot provide clearance through these areas. Brief TSX airspace group NOTAM for activation status.
2.4. Survey flights WI R421 SUBJ MIL traffic and ATC workload. Details of proposed survey flights, including maps, aircraft details and timings, must be provided to ATC with 48HR PN by email to 453sqnnwaflt@defence.gov.au. Approval of survey operations may be SUBJ delay or cancellation to afford MIL priority.

Information may be continued on the next page: PTO

3. CIRCUIT PROCEDURES

3.1. All ACFT TAX for OPS confined to the CIRA shall CTC Nowra SMC to pass FLT details and obtain AWY CLR. Circuit OPS at Nowra occur WI the CIRA, a 5NM radius of Nowra ARP, SFC to 2,000FT.

3.2. Unless ATC direct otherwise, CCTS will be conducted as follows:

a. RWY 08 - Right;
b. RWY 21 - Right;
c. Fixed wing circuit ALT is 2,000FT AMSL;
d. Rotary wing circuit ALT is 1,200FT AMSL.
e. MIL HEL OPR CCTS to W Pad, S Pad and Flight Deck PROC Trainer not ABV 1,500FT AMSL.

3.3. Continuous IFR CCTS not permitted.

3.4. Mixed rotary wing and fixed wing CCTS subject to ATC approval and LCA MIL priority.

4. DEPARTURE PROCEDURES

Unless otherwise directed, DEP local ACFT transfer automatically FM TWR to APP WI 1NM of upwind THR EXC for local HEL with transfer WI 1NM of AD BDRY.


5. VFR ENTRY AND TRANSIT PROCEDURES

5.1. VFR ACFT should submit FPL to reduce delay in processing clearance. Airborne VFR ACFT with FPL may contact APP on 123.5MHz directly for airways clearance. VFR ACFT without FPL to contact ACD on 128.35MHz to provide flight details.

5.2. VFR aircraft transiting R421A by day below 3,500FT AMSL expect clearance via STD VFR transit routes as below. ACFT requesting DCT or other tracking expect clearance at or above 3,500FT AMSL, except during poor weather.

5.3. STD VFR routes are established for low level transit of R421A. Route dependent on status of M440AB/M441 (check TSX airspace group NOTAM). Expect FISHO ROUTE when M440AB/M441 ACT BLW 2,000FT AMSL, otherwise expect WOOLY ROUTE:

a. Expect clearance via WOOLY/FISHO ROUTE either SOUTHBOUND or NORTHBOUND, not above 2,000FT AMSL.
b. **WOOLY ROUTE**:
   (i) Southbound: KMA - CONG - WOI - WDN - UDA.
   (ii) Northbound: UDA - WDN - WOI - CONG - KMA.
c. **FISHO ROUTE**:
   (i) Southbound: KMA - CONG - WDN - FSHR - UDA.
   (ii) Northbound: UDA - FSHR - WDN - CONG - KMA.
d. Caution: VTC/VNC/TAC display WOOLY ROUTE only. FISHO route not shown on AIP Charts.



6. INITIAL AND PITCH

a. IP is 5NM on final for the assigned RWY, displaced 800M to the dead side. Left/ Straight/Right Initial are 30 SEC flying time prior to IP. ACFT are to establish not below 2,000FT AMSL prior to IP.

b. ATC may vertically restrict conflicting ACFT. ACFT will receive relevant traffic by the IP; ACFT are to pitch into the circuit from the dead side and may be subject to positive control and sequencing.

c. Subject to ATC approval, low breaks may occur not below 900FT AMSL (APRX 500FT AGL).

7. **REMOTELY PILOTED AIRCRAFT SYSTEM (RPAS)**

7.1. The FLW permanent small RPAS (less than 25KG) areas exist:

a. Thurgate Oval, Bomaderry PSN 345124S 1503618E (BRG 016 MAG 6.5NM FM ARP) and Bomaderry Oval, Bomaderry PSN 345124S 1503624E (BRG 019 MAG 6.5NM FM ARP). OPR BTN 2130-1100 UTC (2030-1000 UTC HDS) DLY, WI 0.5NM up to 200FT AGL.

b. Model ACFT OPR SAT/SUN/PH HJ TWY A up to 400FT AGL (will land on receipt of CTAF broadcast),

c. Model ACFT OPR HJ WI 500M RAD OF PSN 345413.31S 1503521.69E (Archer Racecourse) BRG 030MAG 3.9NM FM ARP. OPR will MNT CTAF. SFC TO 400FT AGL when R421A/B ACT (up to 1,000FT with ATC approval). SFC to 1,000FT AGL when R421A/B deactivated.

d. Model ACFT OPR HJ WI 500M RAD of PSN 344955.80S 1503719.70E (Fletcher's Lane) (BRG 018MAG 8.1NM FM ARP). OPR will MNT CTAF, SFC to 400FT AGL when R421A/B ACT (Up to 1,000FT with ATC approval), SFC to 1,000FT AGL when R421A/B deactivated.

7.2. RPAS requests and enquires are to be sent to: nowra.rpas@defence.gov.au with at least 10 business days PN. RPAS approval is subject to all MIL OPS and status of active restricted/military operating areas may have additional restrictions imposed or be cancelled at short notice.

7.3. When activated by NOTAM requests for RPAS OPS WI M441 and M440A/B will not be available.

8. **OUTSIDE TWR HR**

a. MIL HEL OPR CCTS to W Pad, S Pad and Flight Deck PROC Trainer not ABV 1,500FT AMSL. Other HEL CCTS 1,200FT AMSL.

b. In the event of an EMERG, ACFT OPR at YSNW on an unattended airfield basis are to declare the EMERG on Melbourne Centre, FREQ 121.2. Additionally when WI 10NM of YSNW, MIL ACFT are to advise details to RFFS watch attendant CS "Base Fire" on FREQ 118.85.

c. When other ACFT are OPR in the circuit, pilots conducting a practice IAP and not intending to land must not descend BLW 1,900FT. At MAPT, conduct the published missed approach procedure.

CTAF - AFRU 118.85

Outside ATS HR.

NOISE ABATEMENT PROCEDURES

1. Fast jet/turboprop departures RWY 21:
For noise abatement climb to 1,500FT on RWY HDG before commencing a turn onto track.

2. Noise sensitive area SFC-900FT AMSL S of AD WI RWY 08/26 circuit area:
345744.82S 1503109.72E
345821.60S 1503106.24E
345813.56S 1503138.34E
345751.18S 1503154.30E

Information may be continued on the next page: PTO

ADDITIONAL INFORMATION

1. SEV downdraft may be experienced WI 1NM on final RWY 26 during W wind ABV 7KT.
2. Rifle range 060/4.2NM ARP. ACT is indicated by R flags.
3. 23M pistol firing range 323/1.4NM ARP. ACT is indicated by R flags.
4. MIL ACFT may conduct OPS WI 50NM of YSNW using Light Enhancement devices and may not display external lighting. SFC-1,500FT AGL. Outside ATS HR ACFT will display external lighting on receipt of CTAF call FM other ACFT.
5. High density MIL OPS take place WI R421. Night vision device aided and unaided. MON-THU 2200-1500 UTC, FRI 2200-0700 UTC.
6. Bird hazard exists.
7. All ACFT OPR IN M440, M441 and M444 when ACT are not SUBJ to an ATS from Nowra ATC and OPR SUBJ to the COND imposed by Navy Fleet HQ Potts Point NSW.
8. PJE HX.
9. Non RDO equipped hang gliders OPR in VCY of Mount Cambewarra.
10. Model ACFT OPR WI VCY of AD, see *Flight Procedures*.
11. Caution: Outside TWR HR non RDO equipped AD support vehicles OPR on APN and TWY.


CHARTS RELATED TO THE AERODROME

1. WAC 3456.
2. MIL Aerodrome Obstruction Chart Type A: FEB 2025.
3. Also refer to AIP Departure and Approach Procedures.

NULLAGINE

ELEV 1251

FULL NOTAM SERVICE NOT AVBL



WA		UTC +8	YNUL
215446S	1201155E	VAR 1 DEG E	UNCR

AD OPR Shire of East Pilbara, PMB 22, Newman, WA, 6753.
ARO 08 9177 8964: 0409 483 651. Council PH 08 9177 8964.
Fax 08 9177 8965.

PASSENGER FACILITIES

AC/LG/WC.

PHYSICAL CHARACTERISTICS

RWY 14/32 1,620M. Unsealed natural/sand. WID 30M.

AERODROME AND APPROACH LIGHTING

1. Solar lighting HN. RWY 14/32 white on sides, green APCH, red at ends. IWI.
2. RWY 14/32 edge light spacing: 60M.

OTHER LIGHTING

TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA	MELBOURNE CENTRE	128.15 5500FT

CTAF 126.7

ADDITIONAL INFORMATION

Wildlife hazard exists. Cattle, kangaroos, dingoes, birds and other feral animals.

CHARTS RELATED TO THE AERODROME

WAC 3230.