LOCAL TRAFFIC REGULATIONS

1. RWY 12/30: all fixed wing ACFT must make MAX RAD turns at MNM speed at all RWY ends to avoid SFC damage.
2. AFRU signal NOT AVBL at Yamarna. AFRU located at Tropicana.
3. PRKG by prior arrangement with AD OPR.
4. APN and TWY AVBL to single ACFT ABV 5,700KG MTOW when no other ACFT present.
5. No other ACFT allowed in ACFT ABV 5,700KG MTOW occupying APN or TWY.
6. ACFT ABV 5,700KG MTOW to use primary or secondary lead in lines partially marked on concrete pad.
7. All fixed wing ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi. ACFT that cannot comply with this restriction must advise the AD OPR prior to departure.
8. Day VMC OPS only.


CTAF 126.7

CHARTS RELATED TO THE AERODROME

WAC 3352.

YARRAM — ELEV 60

AVFAX CODE 3046



VIC UTC +10 YYRM
383403S 1464516E VAR 13 DEG E CERT
AD OPR Wellington Shire Council, PO Box 506, Sale, VIC, 3850.
PH 1300 366 244. ARO 0429 825 266: 03 5182 5266.
Website: www.wellington.vic.gov.au/development/airports.

REMARKS

AD Charges: Current fees and conditions of use can be obtained FM AD OPR or website.

HANDLING SERVICES AND FACILITIES

AVGAS AVBL 24HR. Payment via IOR QuickPay app only. Contact IOR Aviation, phone 1800 414 012.

METEOROLOGICAL INFORMATION PROVIDED

1. METAR/SPECI.
2. AWIS PH 03 8470 3225 - Report faults to BoM.
3. AWIS FREQ 134.7 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

05/23	049	36c	5700 kg/0.65 MPa Grass.	WID 18	RWS 60
09/27	086	25c	5700 kg/0.65 MPa Gravel.	WID 23	RWS 80

AERODROME AND APPROACH LIGHTING

RWY 09/27 LIRL PAL 119.65 SDBY PWR AVBL
RWY edge light spacing: 09/27: 90M.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 124.0 On Ground

LOCAL TRAFFIC REGULATIONS

ACFT at opposite ends of RWY 05/23 may not be visible to each other.

FLIGHT PROCEDURES

Right hand circuits required for night OPS RWY 09.

CTAF 126.7

ADDITIONAL INFORMATION

1. Ultra light ACFT movements at AD.
2. Bird hazard exists.
3. Turbulence and windshear hazard exists:
   a. RWY 09 - when NE wind ABV 10KT;
   b. RWY 27 - when NW wind ABV 10KT.

CHARTS RELATED TO THE AERODROME


1. WAC 3470.
2. Also refer to AIP Departure and Approach Procedures.

YARRAWONGA — ELEV 424

AVFAX CODE 3005

VIC		UTC +10	YYWG
360150S	1460140E	VAR 12 DEG E	CERT

AD OPR Moira Shire Council, PO Box 578, Cobram, VIC, 3644.
PH AD Manager/ARO 0428 752 274. Council PH 1300 369 966. Fax 03 5872 1567.



HANDLING SERVICES AND FACILITIES

Fuel supplied by IOR Aviation Pty Ltd. JET A1 and AVGAS 100LL AVBL H24. Payment method via IOR Aviation tag for account holders or via the Fuelcharge APP. PH 1300 457 467.

PASSENGER FACILITIES

1. WC/TX (03 5743 2111)/ME (0418 125 164, 0408 547 104).
2. The Terminal Building is available to pilots. To book this facility PH 03 5871 9222.

AERODROME OBSTACLES

1. Transient vehicles on road 15FT AGL BRG 015 DEG MAG 560M FM ARP (160M N of THR RWY 19).
2. Fence 426.4FT AMSL APRX BRG 242 DEG MAG 487M FM ARP. Infringes RWY 05/23 OLS take-off/approach gradient of 5% by 0.2M.
3. Towers:
   a. 475FT AMSL BRG 270 DEG MAG 467M FM ARP. Unlit.
   b. 560FT AMSL BRG 359 DEG MAG 2,000M FM ARP. Lit.
   c. 559FT AMSL BRG 229 DEG MAG 3,440M FM ARP. Lit.

METEOROLOGICAL INFORMATION PROVIDED

METAR/SPECI.

PHYSICAL CHARACTERISTICS

01/19	011	39a	PCR 90/F/B/0.70 MPa/T Sealed	WID 18	RWS 90
05/23	053	15c	Unrated. Natural surface	WID 18	RWS 60

AERODROME AND APPROACH LIGHTING

RWY 01/19 LIRL AFRU+PAL 126.7
RWY 01/19 edge light spacing: 60M.

Information may be continued on the next page: PTO