

TCL COMMANDS – COMMIT, SAVEPOINT, ROLLBACK

```
MySQL 8.0 Command Line Cli × + ∨

mysql> CREATE DATABASE TCLDemo;
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> USE TCLDemo;
Database changed
mysql>
mysql> CREATE TABLE Student (
  ->     ID INT,
  ->     Name VARCHAR(30)
  -> );
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> INSERT INTO Student VALUES (1, 'Arun');
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO Student VALUES (2, 'Bala');
Query OK, 1 row affected (0.00 sec)

mysql>
mysql> COMMIT;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> INSERT INTO Student VALUES (3, 'Charan');
Query OK, 1 row affected (0.00 sec)

mysql>
mysql> SAVEPOINT sp1;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> INSERT INTO Student VALUES (4, 'Divya');
Query OK, 1 row affected (0.00 sec)

mysql>
mysql> SELECT * FROM Student;
+-----+-----+
| ID    | Name  |
+-----+-----+
| 1     | Arun  |
| 2     | Bala  |
| 3     | Charan|
| 4     | Divya |
+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql>
mysql> ROLLBACK TO sp1;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM Student;
```

ID	Name
1	Arun
2	Bala
3	Charan

```
3 rows in set (0.00 sec)
```

```
mysql>
mysql> COMMIT;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM Student;
```

ID	Name
1	Arun
2	Bala
3	Charan

```
3 rows in set (0.00 sec)
```

```
mysql> |
```