

DCL COMMANDS– GRANT, REVOKE

```
MySQL 8.0 Command Line Cli × + v

mysql> CREATE DATABASE StringDemo;
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> USE StringDemo;
Database changed
mysql>
mysql> CREATE TABLE Student (
    ->     Name VARCHAR(30)
    -> );
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> INSERT INTO Student VALUES
    -> ('Arun Kumar'),
    -> ('Bala Kumar'),
    -> ('Charan');
Query OK, 3 rows affected (0.00 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql>
mysql> SELECT REPLACE(Name, 'Kumar', 'Raj') AS Replace_Name
    -> FROM Student;
+-----+
| Replace_Name |
+-----+
| Arun Raj    |
| Bala Raj    |
| Charan      |
+-----+
3 rows in set (0.00 sec)

mysql>
mysql> SELECT REPEAT(Name, 2) AS Repeat_Name
    -> FROM Student;
+-----+
| Repeat_Name |
+-----+
| Arun KumarArun Kumar |
| Bala KumarBala Kumar |
| CharanCharan         |
+-----+
3 rows in set (0.00 sec)
```

3 rows in set (0.00 sec)

```
mysql>
mysql> SELECT REVERSE(Name) AS Reverse_Name
       -> FROM Student;
```

Reverse_Name
ramuK nurA
ramuK alaB
narahC

3 rows in set (0.00 sec)

```
mysql>
mysql> SELECT RIGHT(Name, 3) AS Right_Name
       -> FROM Student;
```

Right_Name
mar
mar
ran

3 rows in set (0.00 sec)

```
mysql>
mysql> SELECT LEFT(Name, 3) AS Left_Name
       -> FROM Student;
```

Left_Name
Aru
Bal
Cha

3 rows in set (0.00 sec)

```
mysql>
mysql> SELECT RPAD(Name, 15, '*') AS RPad_Name
       -> FROM Student;
```

RPad_Name
Arun Kumar*****
Bala Kumar*****
Charan*****

3 rows in set (0.00 sec)

```
mysql>
mysql> SELECT LPAD(Name, 15, '*') AS LPad_Name
       -> FROM Student;
```

LPad_Name
*****Arun Kumar
*****Bala Kumar
*****Charan

3 rows in set (0.00 sec)

```
mysql> |
```