

PROCEDURES

```
MySQL 8.0 Command Line Cli  x  +  v

Database changed
mysql> CREATE TABLE student_info (
-> id INT PRIMARY KEY,
-> name VARCHAR(50),
-> age INT,
-> city VARCHAR(50)
-> );
Query OK, 0 rows affected (0.05 sec)

mysql> INSERT INTO student_info VALUES
-> (1, 'Ravi', 20, 'Chennai'),
-> (2, 'Priya', 21, 'Hyderabad'),
-> (3, 'Arun', 20, 'Bangalore');
Query OK, 3 rows affected (0.01 sec)
Records: 3 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM student_info;
+----+-----+-----+-----+
| id | name  | age  | city  |
+----+-----+-----+-----+
| 1  | Ravi  | 20   | Chennai |
| 2  | Priya | 21   | Hyderabad |
| 3  | Arun  | 20   | Bangalore |
+----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> DELIMITER //
mysql> CREATE PROCEDURE GetAllStudents()
-> BEGIN
-> SELECT * FROM student_info;
-> END //
Query OK, 0 rows affected (0.02 sec)

mysql> DELIMITER ;
mysql> CALL GetAllStudents();
+----+-----+-----+-----+
| id | name  | age  | city  |
+----+-----+-----+-----+
| 1  | Ravi  | 20   | Chennai |
| 2  | Priya | 21   | Hyderabad |
| 3  | Arun  | 20   | Bangalore |
+----+-----+-----+-----+
3 rows in set (0.02 sec)

Query OK, 0 rows affected (0.03 sec)

mysql> |
```

32°C Mostly sunny 11:26 12-08-2026